

# Department of Homeland Security

**Expiration Date:** 

12 Apr 2028

THE LULU



For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name

Official Number

**IMO Number** 

UI PUIIUIUU

Call Sign

Service

CCL 28

1212828

Tank Barge

Hailing Port

NEW ORLEANS, LA

**Hull Material** 

Steel

Horsepower

Propulsion

UNITED STATES

Place Built

**Keel Laid Date** 

BELLE CHASSE, LA

19Sep2008

18Jun2008

R-735

R-735

R-200.0

10

UNITED STATES

Owner

RBBL LLC 1237 HIGHWAY 75 Sunshine, LA 70780 UNITED STATES

Operator

CHEM CARRIERS LLC **1237 HIGHWAY 75** SUNSHINE, LA 70780 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters

0 Licensed Mates

0 Chief Engineers

0 Oilers

0 Chief Mates

0 First Class Pilots

0 First Assistant Engineers

0 Third Mates

0 Able Seamen

0 Radio Officers

0 Second Assistant Engineers 0 Third Assistant Engineers

0 Qualified Member Engineer

0 Master First Class Pilot

0 Mate First Class Pilots

0 Second Mates

0 Ordinary Seamen 0 Deckhands

0 Licensed Engineers

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

# --- Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a: 12) 4 15 vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be district. salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in whiting of the results change in status occurs.

# \*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\*

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Charge, Manage, Ma Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicative vessel in all respects, is in conformity with the applicative vessel in all respects, is in conformity with the applicative vessel in all respects, is in conformity with the applicative vessel in all respects, is in conformity with the applicative vessel in all respects, is in conformity with the applicative vessel in all respects, is in conformity with the applicative vessel in all respects. laws and the rules and regulations prescribed thereunder.

Date	Zone	A/P/R	Si	gnature
1510624	5H6	A	0	MOSE
1176325	SHG	P	14/4/	The same

This certificate issued by:

K. A. Hantal, CDR, USCG, By direction

Officer in Charge, Marine Inspection

Marine Safety Unit Port Arthur

Inspection Zone



Department of Homeland Security United States Coast Guard Certification Date: 12 Apr 2023 Expiration Date: 12 Apr 2028

Certificate of Inspection

For stops on international waxgon this certificate fulfills the requirements of SCLAS 74 as amended, regulation V/14, for a SAFE MARKING COLDIENT

Versel Name	Official Num	lber	MO Numi	ber	Call Sign	Service	
CCL 28	121282	8				Tank	Barge
NEW ORLEANS, LA UNITED STATES		Material eel	Horse	epower	Propulsion		
Ptace Built BELLE CHASSE, LA	Deliver	y Date	Kee Laid Date	Gross Tens R-735	Net Tons R-735	DWT	Length
UNITED STATES	19S	ep2008	18Jun2008	L L	I.		R-200.0 1-0
Owner RBBL LLC 1237 HIGHWAY 75 Sunshine, LA 70780 UNITED STATES			1237 SUN	M CARRIE ' HIGHWA' SHINE, LA 'ED STATE	Y 75 . 70780		
This vessel must be mann 0 Certified Lifeboatmen, 0	ned with the following I Certified Tankermen	icensed 0 HSC	and unlicense Type Rating,	d Personne and 0 GMD	el. Included in v OSS Operators.	vhich there r	nust be
0 Masters 0 Chief Mates	Unicensed Mates     First Class Pilots		Engineers Assistant Enginee		Dilers		
0 Second Mates	0 Radio Officers		nd Assistant Engi				
0 Third Mates	0 Able Seamen	0 Third	Assistant Engine	ers			
Master First Class Pllot     Mate First Class Pilots	Ordinary Seamen     Deckhands		sed Engineers ied Member Engi	neer			

#### --- Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

#### \*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\*

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

	Allinual/Fell	ouic/Ne-ins	pection	This certificate issued by:
Date	Zone	A/P/R	Signature	K. A. Hantal, EDR, USCG, By direction
1510124	5H6	A	O More	Officer in Charge, Marine Inspection  Marine Safety Unit Port Arthur
				Inspection Zone



#### United States of America Department of Homeland Security United States Coast Guard

Certification Date: 12 Apr 2023 12 Apr 2028 **Expiration Date:** 

## Certificate of Inspection

se Marrie CCL 26

---Hull Exams---

Exam Type Next Exam Last Exam

Prior Exam

DryDock

31Mar2028

14Mar2018

19Sep2008

Internal Structure

30Apr2028

12Apr2023

14Mar2018

### --- Liquid/Gas/Solid Cargo Authority/Conditions ---

FLAMMABLE/COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

**Total Capacity** 

Units

Highest Grade Type Part151 Regulated Part153 Regulated

Part154 Regulated

11066

Barrel

A

Yes

No

No

#### \*Hazardous Bulk Solids Authority\*

Not Authorized

#### \*Loading Constraints - Structural\*

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1	647	12.80
2	755	12.80
3	671	12.80
40 -		

#### \*Loading Constraints - Stability\*

Section Section Section Section	Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
The state of the s	1	1434	8ft 9in	15.00	LBS, R
The state of the s	II	1524	9ft 2in	15.00	LBS, R
-	III	1722	10ft 1in	15.00	LBS, R
	III	1794	10ft 5in	13.50	LBS, R
-	III	1812	10ft 6in	12.00	LBS, R
-	III	1920	11ft Oin	15.00	R
-	III	1961	11ft 3in	13.50	
-		1980	11ft 4in	12.80	LBS, R LBS, R
ı	*Conditions Of				

#### \*Conditions Of Carriage\*

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), serial #C2-0703245, dated 22OCT07, and Grade "A" and lower cargoes may be carried and then only in the tanks indicated.

Per 46 CFR 150.130, the Person In Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group numbers from the "COMPAT GROUP NO" column listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for

Vapor Control Authorization\*

er 46 CFR 39, excluding Part 39.4000, this vessel's vapor control system (VCS) has been inspected to the plans approved Marine Safety Center letter serial #C2-0703245, dated 22OCT07, and found acceptable for collection of bulk liquid cargo



#### **United States of America** Department of Homeland Security **United States Coast Guard**

Certification Date: 12 Apr 2023 **Expiration Date:** 12 Apr 2028

### Certificate of Inspection

vapors annotated with "Yes" in the CAA's VCS column.

\*Stability and Trim\*

Per 46 CFR 151.10(c)(2), the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal.

#### --- Inspection Status ---

#### \*Cargo Tanks\*

	Internal Exam			External Exar	n	
Tank Id	Previous	Last	Next	Previous	Last	Next
1	19Sep2008	14Mar2018	31Mar2028	-	-	-
2	19Sep2008	14Mar2018	31Mar2028	-	-	-
3	19Sep2008	14Mar2018	31Mar2028	-	-	-
			Hydro Test			
Tank Id	Safety Valves	1	Previous	Last	Next	
1	-		-	-1	-	
2	-		-	-	_	
3	-		-	_	_	

### ---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

### --- Fire Fighting Equipment ---

### \*Fire Extinguishers - Hand portable and semi-portable\*

Quantity

Class Type

2

40-B

### ---Certificate Amendments---

Amending Unit

Amendment Date

Amendment Remark

Sector Houston/Galveston

21Dec2023

\*\*\*END\*\*\*

Changed signing authority to issue replacement COI due to damage.



# Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: CCL 28

Shipyard: C & C Marine & Repair

Hull #: 93

Official #: 1212828

46 CFR 151 Tank G	Group (	Chara	cteris	tics													
Tank Group Information	Cargo I	dentificati	ion		Cargo		Tanks		Carg Tran		Environ Control	mental	Fire	Special Require	ments		
Trik Grp Tanks in Group	Density	Press.	Temp.	Hull Typ	Seg	Туре	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space	Protection Provided	General	Materials of Construction		Temp Cont
A #1, #2, #3	15	Atmos.	Amb.	1		Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	40-1(f)(1), .50-60, .50-70(a), .50- 70(b), .50-73.	55-1(b), (c), (e), (f), (h), (j), 56-1(a), (b), (c), (d), (e), (f), (g)	NR	No

Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.

- 2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
- 3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

**List of Authorized Cargoes** 

Cargo Identification	n							Condi	tions of Carriage	
					LI LI		Vapor Re			
Name	Chem	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	App'd (Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
Authorized Subchapter O Cargoes										
Acetonitrile	ATN	37	0	С	111	Α	Yes	3	No	G
Acrylonitrile	ACN	15 <sup>2</sup>	0	С	Ш	Α	Yes	4	.50-70(a), .55-1(e)	G
Adiponitrile	ADN	37	0	E	11	Α	Yes	1	No	G
Alkyl(C7-C9) nitrates	AKN	34 2	0	NA	101	Α	No	N/A	.50-81, .50-86	G
Aminoethylethanolamine	AEE	8	0	E	- 111	Α	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 2	0	NA	III	Α	No	N/A	50-73, 56-1(a), (b), (c)	G
Ammonium hydroxide (28% or less NH3)	AMH	6	0	NA	III	Α	No	N/A	.56-1(a), (b), (c), (f), (g)	G
Anthracene oil (Coal tar fraction)	AHO	33	0	NA	П	Α	No	N/A	No	G
Benzene	BNZ	32	0	С	- 111	Α	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	внв	32 2	0	С	III	Α	Yes	1	50-60	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	ВНА	32 2	0	С	111	Α	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	0	B/C	111	A	Yes	1	.50-60	G
Butyl acrylate (all isomers)	BAR	14	0	D	III	А	Yes	2	50-70(a), 50-81(a), (b)	G
Butyl methacrylate	ВМН	14	0	D	111	Α	Yes	2	50-70(a), 50-81(a), (b)	G
Butyraldehyde (all isomers)	BAE	19	0	С	Ш	Α	Yes	1	.55-1(h)	G
Camphor oil (light)	CPO	18	0	D	П	Α	No	N/A	No	G
Carbon tetrachloride	CBT	36	0	NA	III	Α	No	N/A	No	G
Caustic potash solution	CPS	5 2	0	NA	- 111	Α	No	N/A	.50-73, .55-1(j)	G
Caustic soda solution	CSS	5 2	0	NA	111	Α	No	N/A	.50-73, .55-1(j)	G
Chemical Oil (refined, containing phenolics)	COD	21	0	Е	- II	Α	No	N/A	50-73	G
Chlorobenzene	CRB	36	0	D	111	Α	Yes	1	No	G
Chloroform	CRF	36	0	NA	III	Α	Yes	3	No	G
Coal tar naphtha solvent	NCT	33	0	D	III	Α	Yes	1	.50-73	G
Creosote	CCW	21 2	0	Е	. III.	А	Yes	1	No	G
Cresols (all isomers)	CRS	21	0	Е	111	А	Yes	1	No	G
Cresylate spent caustic	CSC	5	0	NA	111	Α	No	N/A	.50-73, .55-1(b)	G
Cresylic acid tar	CRX		0	Е	111	Α	Yes	1	.55-1(f)	G
Crotonaldehyde	CTA	19 2	0	С	- 11	Α	Yes	4	.55-1(h)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		0	С	111	А	No	N/A	No	G
Cyclohexanone	ССН	18	0	D	- 111	Α	Yes	1	.56-1(a), (b)	G
Cyclohexanone, Cyclohexanol mixture	CYX	18 2	0	Е	Ш	Α	Yes	1	.56-1 (b)	G
Cyclohexylamine	CHA	7	0	D	111	Α	Yes	1	.56-1(a), (b), (c), (g)	G
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	0	D	III	Α	Yes	1	.50-60, .56-1(b)	G
iso-Decyl acrylate	IAI	14	0	Е	111	Α	Yes	2	50-70(a), 50-81(a), (b), 55-1(c)	G

<sup>\*\*\*</sup> This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: CCL 28

Shipyard: C & C Marine &

Repair Co.

Hull #: 93

Official #: 1212828

Page 2 of 7

Cargo Identification							(	Condi	tions of Carriage	
			ETT.				Vapor R	ecovery		7.5
Name Dichlorobenzene (all isomers)	Chem Code DBX	Compat Group No 36	Sub Chapter O	Grade E	Hull Type III	Tank Group A	App'd (Y or N) Yes	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of .56-1(a), (b)	Insp. Period
1,1-Dichloroethane	DCH	36	0	C	HI				No	G
						A	Yes	1	.55-1(f)	G
2,2'-Dichloroethyl ether	DEE	41	0	D	II.	A	Yes	1	No No	G
Dichloromethane	DCM	36	0	NA	111	A	Yes	5		
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	0	E	- 111	Α	No	N/A	56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2		A	III.	Α	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 2	0	E	101	Α	No	N/A	.56-1(a), (b), (c), (g)	G
1,1-Dichloropropane	DPB	36	0	С	III	Α	Yes	3	No	G
1,2-Dichloropropane	DPP	36	0	С	111	Α	Yes	3	No	G
1,3-Dichloropropane	DPC	36	0	С	Ш	Α	Yes	3	No	G
1,3-Dichloropropene	DPU	15	0	D	Ш	Α	Yes	4	No	G
Dichloropropene, Dichloropropane mixtures	DMX	15	0	С	- 11	Α	Yes	1	No	G
Diethanolamine	DEA	8	0	E	Ш	Α	Yes	1	55-1(c)	G
Diethylamine	DEN	7	0	С	Ш	Α	Yes	3	.55-1(c)	G
Diethylenetriamine	DET	7 2	0	E	III	Α	Yes	1	.55-1(c)	G
Diisobutylamine	DBU	7	0	D	111	Α	Yes	3	.55-1(c)	G
Diisopropanolamine	DIP	8	0	Е	- 111	Α	Yes	1	.55-1(c)	G
Diisopropylamine	DIA	7	0	С	- II	Α	Yes	3	55-1(c)	G
N,N-Dimethylacetamide	DAC	10	0	Е	- 111	Α	Yes	3	.56-1(b)	G
Dimethylethanolamine	DMB	8	0	D	Ш	Α	Yes	1	56-1(b), (c)	G
Dimethylformamide	DMF	10	0	D	III	Α	Yes	1	.55-1(e)	G
Di-n-propylamine	DNA	7	0	С	- 11	Α	Yes	3	.55-1(c)	G
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	0	Е	111	Α	No	N/A	.56-1(b)	G
Dodecyl diphenyl ether disulfonate solution	DOS	43	0	#	- 11	Α	No	N/A	No	G
EE Glycol Ether Mixture	EEG	40	0	D	III	A	No	N/A	No	G
Ethanolamine	MEA	8	0	E	- 10	A	Yes	1	.55-1(c)	G
Ethyl acrylate	EAC	14	0	C	111	A	Yes	2	50-70(a), .50-81(a), (b)	G
Ethylamine solution (72% or less)	EAN	7	0	A	Н	A	No	N/A	.55-1(b)	G
N-Ethylbutylamine	EBA	7	0	D	111	A	Yes	3	.55-1(b)	G
N-Ethylcyclohexylamine N-Ethylcyclohexylamine	ECC	7	0	D	111	A	Yes	1	.55-1(b)	G
Ethylene cyanohydrin	ETC	20	0	E	III	A	Yes	1	No	G
Ethylenediamine Ethylenediamine	EDA	7 2	0	D	111	A	Yes	1	.55-1(c)	G
		36 <sup>2</sup>							No	G
Ethylene dichloride	EDC		0	С	111	A	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	0	E	111	A	No	N/A		G
Ethylene glycol monoalkyl ethers	EGC	40	0	D/E	III	A	Yes	1	No	
Ethylene glycol propyl ether	EGP	40	0	E	III	A	Yes	1	No	G
2-Ethylhexyl acrylate	EAI	14	0	Е	111	Α	Yes	2	50-70(a), 50-81(a), (b)	G
Ethyl methacrylate	ETM	14	0	D/E	Ш	Α	Yes	2	50-70(a)	G
2-Ethyl-3-propylacrolein	EPA	19 2	0	E	111	Α	Yes	1	No	G
Formaldehyde solution (37% to 50%)	FMS	19 <sup>2</sup>	0	D/E	III	Α	Yes	1	.55-1(h)	G
Furfural	FFA	19	0	D	III	Α	Yes	1	.55-1(h)	G
Glutaraldehyde solution (50% or less)	GTA	19	0	NA	Ш	Α	No	N/A	No	G
Hexamethylenediamine solution	HMC	7	0	E	111	Α	Yes	1	.55-1(c)	G
Hexamethyleneimine	HMI	7	0	С	H	Α	Yes	1	.56-1(b), (c)	G
Hydrocarbon 5-9	HFN		0	С	111	Α	Yes	1	50-70(a), .50-81(a), (b)	G
Isoprene	IPR	30	0	Α	111	Α	No	N/A	.50-70(a), .50-81(a), (b)	G
Isoprene, Pentadiene mixture	IPN		0	В	111	Α	No	N/A	.50-70(a), .55-1(c)	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	0	NA	111	Α	No	N/A	.50-73, .56-1(a), (c), (g)	G
Mesityl oxide	MSO	18 2	0	D	111	Α	Yes	1	No	G
Methyl acrylate	MAM	14	0	С	111	A	Yes	2	.50-70(a), 50-81(a), (b)	G



# Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: CCL 28

Shipyard: C & C Marine &

Repair Co.

Official #: 1212828

Page 3 of 7

of 7 Hull #: 93

Cargo Identification	1							Condi	tions of Carriage	
Name	Chem	Compat Group No	Sub	Grade	Hull Type	Tank	App'd	VCS	Special Requirements in 46 CFR	Insp.
Methylcyclopentadiene dimer	MCK	30	O	C	III	Group	(Y or N) Yes	Category 1	151 General and Mat'ls of	Perio
Methyl diethanolamine	MDE	8	0	Е	III	Α	Yes	1	.56-1(b), (c)	G
2-Methyl-5-ethylpyridine	MEP	9	0	Е	111	А	Yes	1	.55-1(e)	G
Methyl methacrylate	MMM	14	0	С	Ш	А	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	0	D	III	А	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	0	D	111	А	Yes	2	50-70(a), 50-81(a), (b)	G
Morpholine	MPL	7 2	0	D	111	Α	Yes	1	.55-1(c)	G
1- or 2-Nitropropane	NPM	42	0	D	III	A	Yes	1	.50-81	G
1,3-Pentadiene	PDE	30	0	Α	- 111	Α	No	N/A	.50-70(a), .50-81	G
Perchloroethylene	PER	36	0	NA	III	Α	No	N/A	No	G
Polyethylene polyamines	PEB	7 2	0	E	111	A	Yes	1	.55-1(e)	G
iso-Propanolamine	MPA	8	0	E	111	A	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	0	E	111	A	Yes	1	.56-1(b), (c)	G
iso-Propylamine	IPP	7	0	A	11	A	Yes	5	.55-1(c)	G
Pyridine	PRD	9	0	C	111	A	Yes	1	55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP	3	0		111	A	No	N/A	.50-73, .55-1(j)	G
Sodium aluminate solution (45% or less)	SAU	5	0	NIA	111	Λ	No	NIA	.50-73, .56-1(a), (b), (c)	G
Sodium chlorate solution (50% or less)	SDD	0 1,2		NA NA	111	A	No	N/A	50-73	G
				1000	-	A	No	N/A		G
Sodium hypochlorite solution (20% or less)	SHQ	5	0	NA	111	A	No	N/A	50-73, 56-1(a), (b)	
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 1,2	- 25	NA	III	A	Yes	1	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 1.2		NA	111	А	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 1,2		NA	11	Α	No	N/A	50-73, 55-1(b)	G
Styrene (crude)	STX		0	D	III	Α	Yes	2	No	G
Styrene monomer	STY	30	0	D	III	Α	Yes	2	.50-70(a), .50-81(a), (b)	G
1,1,2,2-Tetrachloroethane	TEC	36	0	NA	Ш	Α	No	N/A	No	G
Tetraethylenepentamine	TTP	7	0	E	III	Α	Yes	1	.55-1(c)	G
Tetrahydrofuran	THE	41	0	С	III	Α	Yes	1	.50-70(b)	G
Toluenediamine	TDA	9	0	E	- 11	Α	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G
1,2,4-Trichlorobenzene	TCB	36	0	E	111	Α	Yes	1	No	G
1,1,2-Trichloroethane	TCM	36	0	NA	III	Α	Yes	1	50-73, 56-1(a)	G
Trichloroethylene	TCL	36 <sup>2</sup>	0	NA	III	Α	Yes	1	No	G
1,2,3-Trichloropropane	TCN	36	0	E	- 11	Α	Yes	3	.50-73, .56-1(a)	G
Triethanolamine	TEA	8 2	0	Е	III	Α	Yes	1	.55-1(b)	G
Triethylamine	TEN	7	0	С	11	Α	Yes	3	55-1(e)	G
Triethylenetetramine	TET	7 2	0	E	Ш	Α	Yes	1	55-1(b)	G
Triphenylborane (10% or less), caustic soda solution	TPB	5	0	NA	- 111	A	No	N/A	.56-1(a), (b), (c)	G
Trisodium phosphate solution	TSP	5	0	NA	III	Α	No	N/A	.50-73, .56-1(a), (c).	G
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	0	NA	III	A	No	N/A	.56-1(b)	G
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	0	NA	111	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Vinyl acetate	VAM	13	0	С	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Vinyl neodecanate	VND	13	0	E	III	A	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyltoluene	VNT	13	0	D	111	Α	Yes	2	50-70(a), 50-81, 56-1(a), (b), (c), (	G
ubchapter D Cargoes Authorized for Vapor Contro									VI TO YEAR IS	16.1
Acetone	ACT	18 2	D	С		Α	Yes	1	35-17. 34. 37. 17. 17.	100
Acetophenone	ACP	18	D	E		Α	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		Α	Yes	-1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		Α	Yes	1		
Amyl acetate (all isomers)	AEC	34	D	D		Α	Yes	1		



# Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: CCL 28

Shipyard: C & C Marine & Repair Co.

Hull #: 93

Official #: 1212828

Page 4 of 7

Cargo Identification	1			14		Conditions of Carriage					
	1					-	Vapor	Recovery			
Name Amyl alcohol (iso-, n-, sec-, primary)	Chem Code AAI	Group No	Sub Chapter D	Grade D	Hull Type	Tank Group A	App'd (Y or N) Yes	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period	
Benzyl alcohol	BAL	21	D	E		A	Yes	1			
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		A	Yes	1			
Butyl acetate (all isomers)	BAX	34	D	D		Α	Yes	1			
Butyl alcohol (iso-)	IAL	20 2	D	D		Α	Yes	1			
Butyl alcohol (n-)	BAN		D	D		Α	Yes	1		1 1	
Butyl alcohol (sec-)	BAS		D	С		Α	Yes	1			
Butyl alcohol (tert-)	BAT		D	С		Α	Yes	1			
Butyl benzyl phthalate	BPH	34	D	Е		Α	Yes	1			
Butyl toluene	BUE	32	D	D	-	Α	Yes	1			
Caprolactam solutions	CLS	22	D	Е		Α	Yes	1			
Cyclohexane	CHX	31	D	С		A	Yes	1			
Cyclohexanol	CHN	20	D	E	-	A	Yes	1		-	
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2			
p-Cymene p-Cymene	CMP	32	D	D		A	Yes	1			
iso-Decaldehyde	IDA	19	D	E		A	Yes	1			
n-Decaldehyde	DAL	19	D	E	- A P	A	Yes	1			
Decene				D							
	DCE	30 20 <sup>2</sup>	D			A	Yes	1			
Decyl alcohol (all isomers)	DAX		D	E	-	A	Yes	1			
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		Α	Yes	1			
Diacetone alcohol	DAA	20 2	D	D		Α	Yes	1			
ortho-Dibutyl phthalate	DPA	34	D	E		Α	Yes	1			
Diethylbenzene	DEB	32	D	D		Α	Yes	1			
Diethylene glycol	DEG	40 2	D	E		Α	Yes	1			
Diisobutylene	DBL	30	D	С		Α	Yes	1			
Diisobutyl ketone	DIK	18	D	D		Α	Yes	1			
Diisopropylbenzene (all isomers)	DIX	32	D	Е		Α	Yes	1			
Dimethyl phthalate	DTL	34	D	E		Α	Yes	1			
Dioctyl phthalate	DOP	34	D	Е		Α	Yes	1			
Dipentene	DPN	30	D	D		Α	Yes	-1			
Diphenyl	DIL	32	D	D/E		Α	Yes	1			
Diphenyl, Diphenyl ether mixtures	DDO	33	D	Е		Α	Yes	1			
Diphenyl ether	DPE	41	D	{E}		A	Yes	1			
Dipropylene glycol	DPG	40	D	E		A	Yes	1	C Test St. In St.		
Distillates: Flashed feed stocks	DFF	33	D	E		Α	Yes	1			
Distillates: Straight run	DSR	33	D	E		Α	Yes	1			
Dodecene (all isomers)	DOZ	30	D	D		A	Yes	1			
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		A	Yes	1		_	
2-Ethoxyethyl acetate	EEA	34	D	D	-	A	Yes	1			
Ethoxy triglycol (crude)	ETG	40	D	E		A	Yes	1			
Ethyl acetate	ETA	34	D	C		A	Yes	1		_	
Ethyl acetoacetate	EAA	34	D	E		_		1			
		20 2				A	Yes				
Ethyl alcohol  Ethylhenzene	EAL		D	C		A	Yes	1			
Ethylbenzene	ETB	32	D	С		A	Yes	1		1 141	
Ethyl butanol	EBT	20	D	D		Α	Yes	1			
Ethyl tert-butyl ether	EBE	41	D	С		Α	Yes	1			
Ethyl butyrate	EBR	34	D	D		Α	Yes	1			
Ethyl cyclohexane	ECY	31	D	D		Α	Yes	1			
Ethylene glycol	EGL	20 2	D	E		Α	Yes	1			



# Certificate of Inspection

### Cargo Authority Attachment

Vessel Name: CCL 28

Shipyard: C & C Marine & Repair Co.

Hull #: 93

Official #: 1212828

Page 5 of 7

Cargo Identification	on	5.41.5				Conditions of Carriage						
	Char	0	0		13.00	Tools		Recovery		HE		
Name	Code	Compat Group No	Sub Chapter		Hull Type	Tank Group	(Y or N)	VCS Category	Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period		
Ethylene glycol butyl ether acetate	EMA	34	D	E		Α	Yes	1				
Ethylene glycol diacetate	EGY	34	D	E		Α	Yes	1				
Ethylene glycol phenyl ether	EPE	40	D	Е		Α	Yes	1				
Ethyl-3-ethoxypropionate	EEP	34	D	D		Α	Yes	1		-		
2-Ethylhexanol	EHX	20	D	E	11- "	Α	Yes	1	and the same of			
Ethyl propionate	EPR	34	D	С		Α	Yes	1	and the second second	100		
Ethyl toluene	ETE	32	D	D		A	Yes	1				
Formamide	FAM	10	D	E		Α	Yes	1				
Furfuryl alcohol	FAL	20 2	D	E		Α	Yes	1				
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		Α	Yes	1				
Gasoline blending stocks: Reformates	GRF	33	D	A/C		Α	Yes	1				
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	С		Α	Yes	1				
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	С		Α	Yes	1				
Gasolines: Casinghead (natural)	GCS	33	D	A/C	digit.	Α	Yes	1		1774		
Gasolines: Polymer	GPL	33	D	A/C	1	Α	Yes	1		11.11		
Gasolines: Straight run	GSR	33	D	A/C		Α	Yes	1				
Glycerine	GCR	20 2	D	Е		Α	Yes	1		77.		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	С	77	Α	Yes	1				
Heptanoic acid	HEP	4	D	Е		Α	Yes	1				
Heptanol (all isomers)	HTX	20	D	D/E	77	Α	Yes	1		-		
Heptene (all isomers)	HPX	30	D	С		Α	Yes	2	The state of the state of			
Heptyl acetate	HPE	34	D	Е		Α	Yes	1				
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 <sup>2</sup>	D	B/C	1111	А	Yes	1	TOUR DESIGNATION OF THE	112		
Hexanoic acid	НХО	4	D	Е		Α	Yes	1				
Hexanol	HXN	20	D	D		Α	Yes	1				
Hexene (all isomers)	HEX	30	D	С		Α	Yes	2				
Hexylene glycol	HXG	20	D	E	-	Α	Yes	1	THE RESERVE OF THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN COLUMN TW	OH 0		
Isophorone	IPH	18 <sup>2</sup>	D	Е		Α	Yes	1				
Jet fuel: JP-4	JPF	33	D	E	7	Α	Yes	1				
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		A	Yes	1				
Kerosene	KRS	33	D	D		A	Yes	1				
Methyl acetate	MTT	34	D	D		A	Yes	1		-		
Methyl alcohol	MAL	20 2	D	С		A	Yes	1				
Methylamyl acetate	MAC	34	D	D	-	A	Yes	1				
Methylamyl alcohol	MAA	20	D	D		A	Yes	1				
Methyl amyl ketone	MAK	18	D	D		A	Yes	1				
Methyl tert-butyl ether	MBE	41 2	D	С	-	A	Yes	1		-		
Methyl butyl ketone	MBK	18	D	С		A	Yes	1				
Methyl butyrate	MBU	34	D	C		A	Yes	1				
Methyl ethyl ketone	MEK	18 <sup>2</sup>	D	C		A	Yes	1				
Methyl heptyl ketone	MHK	18	D	D		A	Yes	1				
Methyl isobutyl ketone	MIK	18 2	D	С		A	Yes	1				
Methyl naphthalene (molten)	MNA	32	D	E		A	Yes	1				
Mineral spirits	MNS	33	D	D		A		1		100		
Myrcene	MRE	30	D	D			Yes			27.77		
Naphtha: Heavy	NAG	33	D	#		A	Yes	1				
						A	Yes	1				
Naphtha: Petroleum	PTN	33	D	#	7	A	Yes	1				
Naphtha: Solvent	NSV	33	D	D		A	Yes	1				
Naphtha: Stoddard solvent	NSS	33	D	D		Α	Yes	1				



# Certificate of Inspection

Cargo Identification

### Cargo Authority Attachment

Vessel Name: CCL 28

Triethyl phosphate

1-Undecyl alcohol

Undecene

Trimethylbenzene (all isomers) Trixylenyl phosphate

Xylenes (ortho-, meta-, para-)

Shipyard: C & C Marine & Repair Co.

Hull #: 93

**Conditions of Carriage** 

Official #: 1212828

Page 6 of 7

Vapor Recovery Chem Insp (Y or N) Yes Category 151 General and Mat'ls of Name Group No Chapter Type Naphtha: Varnish makers and painters (75%) NVM 33 Nonane (all isomers), see Alkanes (C6-C9) NAX 31 D D Yes NON D D Nonene (all isomers) 30 Yes NNS 20 D E Nonyl alcohol (all isomers) A Yes NNP D E Nonyl phenol Yes D Nonyl phenol poly(4+)ethoxylates Yes Octane (all isomers), see Alkanes (C6-C9) OAX D C A Octanoic acid (all isomers) OAY D E OCX 20 D Octanol (all isomers) E Yes Octene (all isomers) OTX 30 D C Yes Oil, fuel: No. 2 OTW D D/E Yes OTD D Oil, fuel: No. 2-D D A Yes Oil, fuel: No. 4 OFR 33 D D/E A Yes Oil, fuel: No. 5 OFV 33 D D/E Α Yes Oil, fuel: No. 6 OSX 33 D E Yes D OIL 33 C/D Oil, misc: Crude A Yes Oil, misc: Diesel ODS 33 D D/E A Yes Oil, misc: Lubricating OLB D A Yes ORL 33 D Oil, misc: Residual Oil, misc: Turbine OTB 33 D F PTY D Pentane (all isomers) 31 Yes PTX 30 D Pentene (all isomers) A Yes alpha-Pinene PIO 30 D D A Yes PIP 30 D A Yes Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether PAG D E 40 A Yes Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate PAF 34 D A Yes Polybutene PLB 30 D A Yes D Polypropylene glycol PGC 40 E A Yes IAC D C 34 A iso-Propyl acetate Yes PAT 34 D C A Yes n-Propyl acetate D iso-Propyl alcohol Yes PAL 20 2 D C n-Propyl alcohol Propylbenzene (all isomers) PRY 32 D D A Yes iso-Propylcyclohexane IPX 31 D D Yes PPG 20 D E Propylene glycol A Yes PGN 34 D D Propylene glycol methyl ether acetate A Yes Propylene tetramer PTT D D A Yes SFL D Α Yes Tetraethylene glycol TTG 40 D E A Yes Tetrahydronaphthalene THN 32 D E Α Yes TOL 32 D C A Yes Tricresyl phosphate (less than 1% of the ortho isomer) TCP 34 D E A Yes TEB 32 D Е Α Yes Triethylbenzene D A Yes Triethylene glycol

D

D

D

D

D

D

{D}

D/E

E

A

A

A

A

Yes

Yes

Yes

Yes

Yes

Yes

TPS

TRE

TRP

UDC

UND

XLX

32

30

20

32



#### Department of Homeland Security **United States Coast Guard**

Serial #: C2-0703245 Dated: 22 OCT 07

# Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 28 Official #: 1212828

Page 7 of 7

Shipyard: C & C Marine

#### Explanation of terms & symbols used in the Table:

Cargo Identification

Name Chem Code The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.

The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual Certain mixtures of cargoes may not have a CHRIS Code assigned.

Compatability Group No

The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.

Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility nart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone

See Appendix I to 46 CFR Part 150 - exceptions to the compatability chart.

Subchapter Subchapter D Subchapter O Note 3

Note 1 Note 2

The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.

Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.
Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2

Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges

Grade

The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

A.B.C

Note 4

Flammable liquid cargoes, as defined in 46 CFR 30-10.22. Combustible liquid cargoes, as defined in 46 CFR 30-10.15.

Combustible inquic cargoes, as defined in 46 CFR 30-10.15.

The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.

Those subchapter O cargoes which are not classified as a flammable or combustible liquid.

No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.

Hull Type

NA

The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.

Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).

Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).

Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D.

#### Conditions of Carriage

Vapor Recovery Approved (Y or N) The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo

Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

#### Conditions of Carriage

Tank Group Vapor Recover Approved (Y or N) The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo

es: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo

VCS Category

Category 2

Category 7

The specified cargo's provisional classification for vapor control systems

Category 1

(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.

(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety componenets and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.

Category 3

(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1

Category 4 (Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3

Category 5 (High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air

mixture densities and vapor growth rates as compared to Category 1cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. requirement is in addition to the requirements of Category 1 Category 6

(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5. (High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5

The cargo has not been evaluated/classified for use in vapor control systems



### UNITED STATES OF AMERICA

DEPARTMENT OF HOMELAND SECURITY UNITED STATES COAST GUARD

NATIONAL VESSEL DOCUMENTATION CENTER

### CERTIFICATE OF DOCUMENTATION

VESSEL NAME		OFFICIAL NUMBER	IM	O OR OTHER	NUMBER	Y	EAR COMPLETED								
CCL 28	Wierok ici	1212828	93			2008									
HAILING PORT		HULL MATERIAL					CHANICAL PROPULSION								
NEW ORLEANS LA		STEEL	Part No.	The Their	<b>位为中</b> 军	NO									
GROSS TONNAGE	NET TONNAGE		LENGTH		BREADTH		DEPTH								
735 GRT	735 NRT		200.0	-	35.0		12.5								
PLACE BUILT			MITAUL /	1	33.0		t Pirat Pa								
					1										
BELLE CHASSE LA	( I ( ) )	N Y PEAL		1/1	( )		ETO, BUETANA								
OWNERS	C(A)			NDORSEME	NTS	Ne									
RBBL LLC	<b>\</b>	COAS	TWISE		1										
		KILD.	~		1										
				1											
	I WE	MP	ED	PA	1//	1									
				N. A.	TW.	A STATE OF THE PARTY OF THE PAR									
	FIN			1	10										
				16	) 8										
MANAGING OWNER				1		- 3									
RBBL LLC					- 1										
1237 HIGHWAY 75	4111														
SUNSHINE LA 70780	11-7					1									
		A THE F		10		11									
		) IN A LIYE	-1154		A AL	H									
RESTRICTIONS	Veneria NA														
NONE															
TENCATE FOR LOW		Versus soldie				1									
						/									
		Milking													
ENTITLEMENTS		IN YEAR		7/											
NONE		TAOZE	VO.												
	Allerina		1	Secretary and Assessment of the Party of the											
REMARKS				HAVE TO											
NONE															
ISSUE DATE															
AUGUST 07, 2025															
THIS CERTIFICATE EXPIRES							Q TES CO								
		Christan	1,0,				STATE OF STA								
SEPTEMBER 30, 2026		Mustrus	1. Wal	au			(IIIII) \(\begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\								
		DIRECTOR, NATIO	NAL VESS	EL DOCUMEN	NTATION CE	NTER	ALL S								
AT BY 18 PER STREET A 19 PER STREET							1700								



Click on the Document Icon ( to the left of a record to display a COFR Confirmation in html. You may print the COFR Confirmation by right clicking your mouse and selecting "print" from the list.

Logout

INSURANCE CANCEL

FLAG

VESSEL VESSEL TYPE HULL GROSS COFR EFFECTIVE EXPIRATION COFR APPLICANT VIN

CCL 28 TANKBARGED 793 841310 - 21 9/9/2023 9/9/2026 CHEM CARRIERS, D1212828

< Prev Next >

<u>USCG Home • Privacy Policy • Customer Accessibility</u>

Contact the <u>Accessibility Coordinator</u> for comments and inquiries about accessibility.

Version 3.7 -- This version is designed for Internet Explorer, Edge, Chrome, Firefox and Safari.



#### SOUTHWEST SHIPYARD, L.P.

F-7.5.1(R).6.2-E

 18310 Market Street, Channelview, Texas
 77530
 Phone: 281-860-3200
 Fax: 281-860-3215

 8502 Cypress Street, Houston, Texas
 77012
 Phone: 713-967-6300
 Fax: 713-967-6301

 1002 Texas Clipper Rd., Galveston, Texas
 77554
 Phone: 409-740-3755
 Fax: 409-740-3451

### BARGE PIPELINE HYDROSTATIC TEST

THE FOLLOWING BARGE WAS TESTED IN ACCORDANCE WITH 33 CFR – PART 156.170, SECTION (c)(4) & (e), EQUIPMENT TESTS AND INSPECTIONS REQUIREMENTS.

BARGE NAME/NUMBER:CCLZ8
BARGE OWNER: RBBL/Chem CARRIERS
OWNER ADDRESS:
TESTING LOCATION:  SOUTHWEST SHIPYARD, L.P. 18310 MARKET STREET CHANNELVIEW, TX 77530  SOUTHWEST SHIPYARD, L.P. 8502 CYPRESS HOUSTON, TX 77012  SOUTHWEST SHIPYARD, L.P. 1002 TEXAS CLIPPER RD. GALVESTON, TX 77554
Identify Location by Checking Box
DATE OF TEST: 5/17/2025
SWSLP TESTER/POSITION: DAUC FIX
SWSLP TESTER SIGNATURE: DuFL
WITNESSING SWSLP INSPECTOR/POSITION:
SWSLP INSPECTOR SIGNATURE: 2
TEST RESULTS
THIS BARGE HAS BEEN TESTED IN ACCORDANCE WITH 33 CFR, PART 156.170, SECTION (C)(4) AND (E) WITH HYDROSTATIC TESTING.
TIME START: 9:00 TIME STOP: 10:00
TEST PRESSURE: 187.5 PSI WITH MINIMUM HOLD TIME OF 10 MINUTES
ENDING PRESSURE: /85PSI
NO LEAKS DETECTED AT JOINTS, CONNECTIONS AND HIGH STRESS

REGIONS AROUND OPENINGS AND THICKNESS TRANSITIONS.



F-7,5,1(R),19-0

SOUTHWEST SHIPYARD, L.P. F-7.5.1(R).19-18310 Market Street. Channelview, Taxas 77530 Phone: 281-860-3200 Fax: 281-860-3215 8502 Cypress Street. Houston, Taxas 77012 Phone: 713-967-6300 Fax: 713-967-6301 1002 Taxas Clipper Rd., Galveston, Taxas 77554 Phone: 409-740-3755 Fax: 409-740-3454

### BARGE VAPOR - TIGHTNESS DOCUMENT

THE FOLLOWING BARGE WAS TESTED IN ACCORDANCE WITH THE NATIONAL EMISSION STANDARD FOR BENZENE EMISSIONS FROM BENZENE TRANSFER OPERATIONS, 40 CFR - Sub-Chapter C, PART 61, SECTION 304(f), MARINE VESSEL VAPOR TIGHTNESS REQUIREMENTS.

#### SOUTHWEST SHIPYARD, L.P.

F-7.5.1(C/R).6 - A


18310 Market Street, Channelview, Texas 77530 Phone: 281-860-3200 Fax: 281-860-3215 8502 Cypress Street, Houston, Texas 77012 Phone: 713-967-6300 Fax: 713-967-6301 1002 Texas Clipper Rd., Galveston, Texas 77554 Phone: 409-740-3755 Fax: 409-740-3451

### BARGE PIPING TEST LETTER


Note: Test Results are valid for One (1) Year from Date of Test!

Chart	ISTRUCTIONS: FILL OUT COMPLETELY. WRITE "N	/A" ON ANY NON-APPLICABLE LINE.
BAR	GE NAME/NUMBER:CCL Z8	
LETT	TER EXPIRATION DATE (One Year from Test):	2/17/2026
1.	Cargo Piping and Valves (Date of Test):	2/17/2025
	Test Pressure (psi):	188 PSI
2.	Cargo Pressure Gauge (Date of Test):	2/17/2025
	Percent Accuracy (%):	98%
3.	Steam Piping and Valves (Date of Test):	NA
	Test Pressure (psi):	NIA
	SWSLP Signature:	Date: 02/18/2025

DISTRIBUTION: Place original as last page of "USCG Papers Folder" located in Barge document mailbox.



CCL 28 Cargo & Vapor Piping



					Parts List			
ITEM	QTY	NAME	ITEM	QTY	NAME	ITEM	QTY	NAME
1	2	Vapor Header Valve	7	1	Master Suction Valve	13	1	Pump Engine
2	2	Cargo Header Valve	8	1	No. 1 Cargo Tank Valve	14	1	High Velocity PV Valve
3	1	Drop Valve / Load	9	1	No. 2 Cargo Tank Valve	15	1	Emergency Shutdown
		Valve	10	1	No. 3 Cargo Tank Valve			
4	1	Pressure Release Valve	11	1	Vent Stack Valve			
5	1	Pump Discharge Check	12	1	Deep Well Pump			
		Valve				_		
6	1	Pump Discharge Valve						Edited 07/13/2020

#### CARGO TRANSFER PROCEDURES

#### CHEM CARRIERS L.L.C.

#### TRANSFER FROM BARGE TO DOCK

#### PARTS

- 1. PRODUCTS TRANSFERRED
- 2. DESCRIPTION OF SYSTEM
- 3. PERSONS ON DUTY
- 4. PERSONS IN CHARGE
- 5. EMERGENCY SHUTDOWN
- 6. TOPPING OFF PROCEDURE
- 7. COMPLETION OF TRANSFER
- 8. REPORTING CARGO SPILLS
- 9. VESSEL CLOSURES
- 10. PRODUCT DATA
- 11. Vapor Control Procedures
- 12. Inert system

Barge CCL 28

#### PARTS 1. PRODUCTS TRANSFERRED

#### 33 CFR 155.750 (a) (1) (i)

This vessel is certificated for the carriage of grades "A" and lower Sub-Chapter (D) and (O) Products. It has also been certified to carry vapor products. Reference Certificate of Inspection.

#### PARTS 2. DESCRIPTION OF CARGO TRANSFER SYSTEM

33 CFR 155.750 (a) (2) (i) (ii)

The cargo transfer procedures apply to all Chem Carrier L.L.C. owned or leased tank barges. In most cases other than series built barges, the cargo piping arrangement is usually slightly different on every barge, and for this reason, the piping diagram must be studied before loading or discharging a barge. The basic concept for loading and discharging is fairly standard depending on the location of the pump.

- A. (Reference the piping diagram for transfer system arrangement.)
- B. PROCEDURES FOR THE CONTAINMENT SYSTEM
  - 33 CFR 155.310 (a) (1) (iv)
  - 33 CFR 155.750 (a) (2) (iii)
    - 1). The containment pans are equipped with a drain for the removal of slops to shore facilities:

      NEVER DRAIN THE CONTAINMENT TANKS ONTO THE DECK.
    - 2). CCL 28 is equipped with a separate containment area for

the cargo trunk top and the forward deck area. Each containment area is equipped with drains and scupper plugs. Plugs should be installed prior to cargo transfer and removed after the cargo transfer is complete. PIC should notify Chem Carriers when containment areas need cleaning or if scupper plugs need replacing. Never Drain Product captured in containment area overboard.

#### PARTS 3. PERSONS ON DUTY DURING TRANSFER

33 CFR 155.750 (a) (3)

Number of persons required on duty during transfer operations:

A. At no time during the transfer operation will be less than one responsible person on duty. The certified tankerman assigned shall be in charge and responsible for the safe transfer of cargo.

#### PARTS 4. <u>PERSONS IN CHARGE</u>

The tankerman (person in charge) is responsible for transferring cargo and carrying out related operations on board in an efficient, safe, and pollution free manner. The tankerman whether employed by the towboat, owner, operator, a shore tankerman service, or Chem Carriers L.L.C., shall comply with all Coast Guard, State and local regulations. Tankerman's responsibility shall include but not be limited to the following:

- A. To have on his/her person a valid merchant marine document endorsed as tankerman, certified to handle the grade of cargo to be transferred.
- B. Make a thorough inspection of the barge prior to the start of transfer operation.
- To have proper connection of the grounding cable.
- D. The vessel's moorings are adequate to hold during all expected conditions of surge, current, wind, tide, ect., and lines are long enough to allow for surge, tide, wind, changes in draft ect.
- E. Proper hose sizes, lengths, support, and connections.
- F. The condition of fire extinguishers and required number.
- G. The person in charge of transfer operations on the transferring vessel or facility and the person in charge of transferring operations on the receiving vessel or facility agree to begin the transfer operations.
- H. The transfer operation between tank barges and dock facilities should be lighted between sunset and sunrise to comply with the U. S. Coast Guard regulation pertaining to the displaying of lights on barges as required by Title 33.
- The PIC (PERSON IN CHARGE) will be responsible for the DOI (declaration of inspection) and DOS (declaration of security).
- J. Always maintain communications with dock or shore personnel with an agreed upon approved system.

#### PARTS 5: EMERGENCY SHUTDOWN

33 CFR 155.750 (a) (6)

THE EMERGENCY SHUTDOWN IS LOCATED NEAR THE CENTER OF THE BARGE.

- A. In the event of an emergency, transfer operations can be stopped by pulling the remote shutdown cable.
- B. Familiarize yourself with its location and operation prior to transfer.

#### PARTS 6;

#### TOPPING OFF PROCEDURES

33 CFR 155.750 (a) (7)

In the process of topping off, tanks should be loaded at different levels to top off one at a time. Extra care should be taken to avoid over pressuring the connections, and hoses by closing valves against the receiving line. Since barges and facilities vary in their systems, no standard for topping off exist, but the following should be considered:

- A. The closing of one tank increases the rate of flow to other tanks on the same line.
- B. Always consider temperature and cargo in accordance with the amount of expansion that should be allowed.
- C. Always maintain communications with dock or shore personnel.
- D. A set of dipstick overfill devices have been installed on the CCL 28. Dipsticks can be made operational by releasing the covers or caps. Dipsticks should be used as a visual aid for overfill protection.

#### PARTS 7: COMPLETION OF TRANSFER

33 CFR 155.750 (a) (8)

Upon the completion of the transfer all pipelines should be drained into cargo tanks. The header valve used during the operation should then be closed, sealed off with a blind flange and shore personnel should seal lines and hatches on vessel.

#### PARTS 8:

#### REPORTING CARGO SPILLS

33 CFR 155.750 (a) (9)

Should an accidental discharge of product occur, you should consider the following:

A. Locate the source of the spill and try to stop it, if possible, and safe to do so.

- B. Make an attempt to contain the product if possible.
- C. Notify the Coast Guard. The national Response Center at 1-800-424-9300.
- E. Notify Chem Carriers L.L.C. at (225) 642-0060
- F. If loading, transfer the cargo from the leaking tank to an adjacent tank or back to the dock if safe to do so.
- G.If discharging, pump the product from the leaking tank as quickly as possible if safe to do so.

### \*When reporting a spill, the tankerman should provide the following information:

- A. Name (his or her)
- B. Name of Company: (employed by; (contracted by;
- C. Name of Barge.
- D. Spill Location
- E. Specify Product.
- F. Estimate Quantity of Spill
- G. Weather, Tide, Sea and Current Conditions.
- H. Cause of Spill.
- I. Action Being Taken to Contain and Stop Spill

#### PART 9

#### CLOSURES ON VESSELS

Upon completion of cargo transfer operations, all tank hatch covers, ullage covers, and gauging device covers shall be dogged down and secured. In addition, the vent drain valves, if installed, should be secured and left in the proper position. All drain valves should be closed, and drip pan covers, if installed, should be made up tight. Covers for void spaces, bow and stern compartments shall be secured at all times and checked for tightness. Closing devices on clean-out hatches and clean-out opening should be checked, especially when the barge is loaded.

#### PART 10

#### PRODUCT DATA

See specific MSDS sheets provided with these procedures.

In case of any other emergency, immediately shut down and notify the transferring facility, and Chem Carriers L.L.C. (225) 642-0060 24 Hour Line.

#### PART 11

#### VAPOR CONTROL PROCEDURES

This is a guide only and is not intended to replace experience, sound judgment, and a proper assessment of the task at hand.

The tankerman on duty is the acting Designated Person In Charge (PIC) and is responsible for cargo transfer operations and carrying out related operations on barges.

Vapor Recovery Transfer Maximum Rate is 2300 BBLS/HR for

- subchapter "D" Cargoes and 2400 BBBLS/Hr for subchapter "O" Cargoes.
- 1.1 Transfer rates, which exceed these maximums, must be approved by Chem Carriers.
- 1.2 Transfer rates for each cargo tank should not exceed the maximum transfer rate.

#### 2. Pre-transfer Inspection For Vapor Recovery Operations

- 2.1 Follow the procedures outlined below in addition to the procedures utilized during normal transfers:
- 2.1.1 Wear personal protective equipment (PPE) as needed for the cargo in the barge when testing P/V and, hooking up hoses, or draining low points.
- 2.1.2 Ensure that a Certificate of Vapor Tightness is onboard and valid.
- 2.1.3 Close the low point drain on the port/starboard vapor header, if applicable.
- 2.1.4 Close the low point drain near the vent stack, if applicable.
- 2.1.5 Close valve to the vent riser if applicable.
- 2.1.7 Blinds used for the vapor control manifold should have a hole to accommodate the ½" stud located in the vapor header.
- 2.1.8 Each cargo tank is fitted with a liquid level gauge stick. Remove the cap, raise the stick, This stick can be monitored visually to avoid overfilling.
- 2.1.9 Ensure that the last one meter (3.3 feet) of vapor piping before the vapor connection is painted red/yellow/red.
- 2.1.10 The cross-header should be stenciled with the word "VAPOR" in black letters at least 2'' high.
- 2.1.11 The vapor connection flange should be fixed with a 1" long by 1/2" diameter stud projecting outward from the face of the flange, midway between bolt holes.
- 2.1.12 The high level alarms/shutdowns are installed near the center of each cargo tank. Dock alarm/shutdown should be connected prior to loading, and plugs located near the forward end of the barge Port and Starboard should be labeled "ALARM/SHUTDOWN SENSOR." High level alarms are set to alarm at 90% of the cargo tanks capacity and Shut downs are set to shut transfer down at 95% of each tanks capacity.
- 2.1.13 Ensure that the P/V relief valve flame screen, if required, is in place and in good condition prior to testing.
- 2.1.14 Ensure that the facility has a Letter of Adequacy endorsed as meeting the requirements of 33 CFR Subpart E.

#### Vapor Piping

- 3.1 The PIC checks the vapor piping diagram.
- 3.2 Characteristics of a vapor header:
- 3.2.1 The vapor collection piping system on tank barges is permanently installed and located as close as practical to the loading manifold. The piping system is electrically bonded to the hull and electrically continuous.
- 3.2.2 The last one meter (3.3 feet) of vapor piping prior to the valve before the vapor connection is painted red/yellow/red. The red bands are 4" wide and the yellow band is 32" wide.
- 3.2.3 The vapor header is stenciled with the word "VAPOR" in black letters at least 2" high.
- 3.2.4 The vapor connection flange is to be fixed with a 1" by 1/2" diameter stud projecting outward from the face of the flange. This stud is located at the top of the flange, midway between bolt holes.
- 3.2.5 When not in use, blank off the vapor headers using a blind flange with a bolt in every hole. Each blind flange used on the vapor piping has a hole drilled to accommodate the pin.
- 4. Inspection And Verification Of Vent Lines
- 4.1 The Person in Charge performs the following steps:
- 4.1.1 Checks the Certificate of Inspection on board the barge;
- 4.1.2 Locates polymerizing or inhibited cargoes in the section of the COI marked Specific Hazardous Cargo Authority;
- 4.1.3 Refers to the MSDS or Chemical Data Guide on board the vessel to determine what cargoes are subject to polymerization, or what cargoes are inhibited;
- 4.1.4 Locates the MSDS for the cargo and determines its toxicity and whether or not it is a polymerizing or inhibited cargo; and,
- 4.1.5 Notifies the Dispatcher and Field Supervisor when polymerization is suspected.
- 5. Any problems with the Vapor Control system must be reported immediately to the person in charge and Chem Carriers.



Commandant United States Coast Guard 2703 Martin Luther King Jr. Ave SE Stop 7516
Washington, DC 20593-7516
Staff Symbol: CG-MER-4 (VRP)
Phone: (202) 372-1005
Fax: (202) 372-8376
Email: vrp@uscg.mil

16460 March 12, 2025

Chem Carriers, L.L.C. C/O: FOREFRONT EMERGENCY MANAGEMENT, LP ATTN: ALLIE MARTIN 1730 COTEAU ROAD HOUMA, LA 70364

Dear Sir or Madam:

Your Vessel Response Plan (Control Number 56041), submitted to meet the requirements of Title 33, Code of Federal Regulations (CFR), Part 155, Subparts D and I, is **approved**. Approval will remain valid until **March 21, 2030**.

The CCL 28 (1212828) is authorized to operate only in the ports or geographic areas indicated in the Captain of the Port zones listed below. If carrying oil as cargo, the vessel is prohibited from handling, storing, transferring, or lightering oil unless it is operating in full compliance with this plan. Compliance includes ensuring that required resources have been identified and planned for or are in place and available through contract or other approved means. If applicable to your routes, this includes the dispersant and aerial observation requirements of 33 CFR 155.1050.

You are reminded that your chosen salvage and marine firefighting resource provider may have submitted waivers from meeting one or more of the specified response times in accordance with 33 CFR 155.4055. If so, this may be rescinded by the U.S. Coast Guard if the appropriate response resources are not available when the approved waiver expires. You shall continue to assess the adequacy of your chosen salvors and firefighters as required by 33 CFR 155.4050.

The vessel must keep a copy of this approval letter onboard in addition to the minimum sections of the plan as required by 33 CFR 155.1030. In accordance with 33 CFR 155.1070, you are required to review your plan annually and submit plan amendments for approval. As per 33 CFR 155.1070(b), the entire plan must be resubmitted for a comprehensive review and approval six (6) months prior to the expiration date.

#### APPROVED CAPTAIN OF THE PORT ZONES

CORPUS CHRISTI HOUMA HOUSTON-GALVESTON LOWER MISSISSIPPI RIVER OHIO VALLEY

UPPER MISSISSIPPI RIVER

(MEMPHIS) PORT ARTHUR AND LAKE (ST. LOUIS)

MOBILE CHARLES

NEW ORLEANS

Sincerely,

CHARRON MCCOMBS

Lieutenant Commander

Acting Chief, Domestic Preparedness & Planning Division

U.S. Coast Guard

By direction



Commanding Officer United States Coast Guard Marine Safety Center US Coast Guard Stop 7430 2703 Martin Luther King Jr. Ave. SE Washington, DC 20593-7430 Staff Symbol: MSC-5 Phone: (202) 795-6729 Email: securityplaninfo@uscq.mil

16710 VS-326893 December 3, 2024

Chem Carriers, LLC Attn: Robert Banta 1237 Hwy 75 Sunshine, LA 70780 robert@chemcarriers.com

Subj: CHEM CARRIERS, LLC VESSELS

VESSEL SECURITY PLAN APPROVAL WITH AMENDMENTS

Ref: (a) Your correspondence dated November 6, 2024

(b) Title 33 Code of Federal Regulations (CFR) Part 104

(c) MSC Vessel Security Plan Approval letter dated October 16, 2024

Dear Mr. Banta:

We have conducted a review of the Vessel Security Plan (VSP) submitted with reference (a) in accordance with reference (b) and it is "**Approved**."

Your vessel must operate in compliance with this approved VSP and the requirements contained in reference (b). You are reminded to immediately report any deviation from this approved plan to the local Captain of the Port (COTP)/Officer in Charge, Marine Inspection (OCMI).

This approval will remain valid until five years from the date of reference (c) unless rescinded in writing by the local COTP/OCMI. You must review your plan annually and submit any amendments to this office for approval. Please ensure that a copy of the VSP is maintained on board the vessel if manned, or, if unmanned, at a suitable secure location so that it is readily available during an emergency or security incident. You shall make available to the Coast Guard, upon request, this letter, the VSP and any information related to the implementation of the VSP. Our Case Number for this plan is 326893. Please ensure that all future correspondence includes this Case Number.

Sincerely,

K. C. WILLIAMS Lieutenant Commander, U.S. Coast Guard Chief, Vessel Security Division By direction

Enclosures: (1) List of Vessel Security Plan Amendments

(2) List of Vessels Covered

#### **List of Vessels Covered**

Vessel Name	Official Number (O.N.)
CCL-1	518612
CCL 2	510107
CCL-3	296363
CCL 4	512519
CCL-5	512520
CCL-6	530996
CCL7	551980
CCL 8	551982
CCL 9	551983
CCL 10	551979
CCL 11	551976
CCL 14	1164451
CCL 14 CCL 15	1164452
CCL 13	1164666
CCL 10 CCL 17	1166179
CCL 17 CCL 18	1168981
CCL 18	
CCL 19 CCL 20	1168980
	1191598
CCL 21	1191599
CCL 22	1191600
CCL 23	1191601
CCL 24	1196547
CCL 25	1196548
CCL 26	1203816
CCL 27	1203817
CCL 28	1212828
CCL 29	1212829
CCL 30	1305871
CCL 31	1305870
CCL 32	1305869
CCL 33	1305868
CCL 401	1216671
CCL 402	1219910
CCL 403	1231311
CCL 404	1231312
CCL 405	1236867
CCL 406	1236866
CCL 407	1246320
CCL 408	1246097
CCL 409	1246098
CCL 410	1255906
CCL 411	1255907
CCL 414-L	1262941
CCL 415-T	1262942

Enclosure 2, page 2 of 2, to MSC letter VS-326893 of December 3, 2024

Vessel Name	Official Number (O.N.)
CCL 416-T	1264691
CCL 417 T	1298307
CCL 418-L	1306896
CCL 419-L	1306897
CCL 420-T	1348560
CCL 421-T	CG1843359
CCL 3202	1089031
HFL 413	1237482
HFL 415	1237483
HFL 435	1236563
HFL 605	1237484

Intertek Caleb Brett

### BARGE "CCL 28" HULL NO. C&C Marine # 07-093

TANK NO. 1 INNAGE TABLE

CAPA	CITIES GIVEN	IN BARE	RELS OF 42 U	S. GALL	.ONS	98 - 37		1000 - 011								- 26	C 2007					0-1-1							GAUGE HE	GHT:	16' 3 1/4"
IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.
0	0.56	0	236.97	0	481.62	0	725.63	0	970.00	0	1,214.54	0	1,459.09	0	1,703.64	0	1,948.26	0	2,192.94	0	2,437.61	0	2,663.09	0	2,876.92	0	3,090.74	0	3,304.57	0	3,505.94
1/4	4.94	1/4	242.06	1/4	486.72	1/4	730.71	1/4	975.10	1/4	1,219.63	1/4	1,464.18	1/4	1,708.73	1/4	1,953.35	1/4	2,198.04	1/4	2,442.70	1/4	2,667.55	1/4	2,881.37	1/4	3,095.20	1/4	3,309.02	1/4	3,508.10
1/2	9.32	1/2	247.16	1/2	491.81	1/2	735.79	1/2	980.19	1/2	1,224.73	1/2	1,469.28	1/2	1,713.83	1/2	1,958.45	1/2	2,203.14	1/2	2,447.80	1/2	2,672.00	1/2	2,885.83	1/2	3,099.65	1/2	3,313.48	1/2	3,510.26
3/4	13.71	3/4	252.26	3/4	496.91	3/4	740.87	3/4	985.28	3/4	1,229.82	3/4	1,474.37	3/4	1,718.92	3/4	1,963.55	3/4	2,208.23	3/4	2,452.89	3/4	2,676.46	3/4	2,890.28	3/4	3,104.11	3/4	3,317.93	3/4	3,511.53
1	18.09	1	257.35	1	502.00	1	745.95	1	990.37	1	1,234.92	1	1,479.47	1	1,724.02	1	1,968.65	1	2,213.33	1	2,457.99	1	2,680.91	1	2,894.74	1	3,108.56	1	3,322.39	1	3,512.80
1/4	22.63	1/4	262.45	1/4	507.10	1/4	751.02	1/4	995.47	1/4	1,240.01	1/4	1,484.56	1/4	1,729.11	1/4	1,973.74	1/4	2,218.43	1/4	2,463.08	1/4	2,685.37	1/4	2,899.19		3,113.02	1/4	3,326.84		3,514.07
1/2	27.17	1/2	267.55	1/2	512.20	1/2	756.10	1/2	1,000.56	1/2	1,245.11	1/2	1,489.66	1/2	1,734.21	1/2	1,978.84	1/2	2,223.53	1/2	2,468.18	1/2	2,689.82	1/2	2,903.65		3,117.47	1/2	3,331.30		3,515.35
3/4	31.70	3/4	272.64	3/4	517.29	3/4	761.18	3/4	1,005.65	3/4	1,250.20	3/4	1,494.75	3/4	1,739.30	3/4	1,983.94	3/4	2,228.62	3/4	2,473.28	3/4	2,694.28	3/4	2,908.10	3/4	3,121.93	3/4	3,335.75	3/4	-
2	36.24	2	277.74	2	522.39	2	766.26	2	1,010.75	2	1,255.30	2	1,499.85	2	1,744.40	2	1,989.04	2	2,233.72	2	2,478.37	2	2,698.73	2	2,912.56	2	3,126.38	2	3,340.21	2	
1/4	40.94	1/4	282.84	1/4	527.48	1/4	771.35	1/4	1,015.84	1/4	1,260.39	1/4	1,504.94	1/4	1,749.49	1/4	1,994.13	1/4	2,238.82	1/4	2,483.40	1/4	2,703.18	1/4	2,917.01	1/4	3,130.84	1/4	3,344.66	1/4	
1/2	45.63	1/2	287.93	1/2	532.57	1/2	776.45	1/2	1,020.94	1/2	1,265.49	1/2	1,510.04	1/2	1,754.59	1/2	1,999.23	1/2	2,243.92	1/2	2,488.43	1/2	2,707.64	1/2	2,921.46	1/2	3,135.29	1/2	3,349.12	1/2	- 1
3/4	50.33	3/4	293.03	3/4	537.67	3/4	781.54	3/4	1,026.03	3/4	1,270.58	3/4	1,515.13	3/4	1,759.68	3/4	2,004.33	3/4	2,249.01	3/4	2,493.47	3/4	2,712.09	3/4	2,925.92	3/4	3,139.75	3/4	THE RESERVE AND DESCRIPTION OF THE PARTY OF	3/4	
3	55.02	3	298.13	3	542.76	3	786.63	3	1,031.12	3	1,275.68	3	1,520.23	3	1,764.78	3	2,009.43	3	2,254.11	3	2,498.50	3	2,716.55	3	2,930.37	3	3,144.20	3	3,358.03	3	- 1
1/4	59.86	1/4	303.22	1/4	547.85	1/4	791.73	1/4	1,036.22	1/4	1,280.77	1/4	1,525.32	1/4	1,769.87	1/4	2,014.52	1/4	2,259.21	1/4	2,503.40	1/4	2,721.00	1/4	2,934.83		3,148.65	1/4		1/4	- 1
1/2	64.69	1/2	308.32	1/2	552.95	1/2	796.82	1/2	1,041.31	1/2	1,285.86	1/2	1,530.42	1/2	1,774.97	1/2	2,019.62	1/2	2,264.31	1/2	2,508.30	1/2	2,725.46		2,939.28		3,153.11	1/2	3,366.93	1/2	- 1
3/4	69.53	3/4	313.42	3/4	558.04	3/4	801.92	3/4	1,046.41	3/4	1,290.96	3/4	1,535.51	3/4	1,780.06	3/4	2,024.72	3/4	2,269.40	3/4	2,513.20	3/4	2,729.91	3/4	2,943.74	3/4	3,157.56	3/4	market between the control of the co	3/4	
4	74.36	4	318.51	4	563.14	4	807.01	4	1,051.50	4	1,296.05	4	1,540.60	4	1,785.16	4	2,029.82	4	2,274.50	4	2,518.11	4	2,734.37	4	2,948.19	4	3,162.02	4	3,375.84	4	
1/4	79.34	1/4	323.61	1/4	568.21	1/4	812.10	1/4	1,056.60	1/4	1,301.15	1/4	1,545.70	1/4	1,790.25	1/4	2,034.92	1/4	2,279.60	1/4	2,522.88	1/4	2,738.82	1/4	2,952.65	1/4	3,166.47	1/4	3,380.30	1/4	- 1
1/2	84.31	1/2	328.71	1/2	573.29	1/2	817.20	1/2	1,061.69	1/2	1,306.24	1/2	1,550.79	1/2	1,795.34	1/2	2,040.01	1/2	2,284.70	1/2	2,527.66	1/2	2,743.28	1/2	2,957.10		3,170.93	1/2	3,384.75	1/2	- 1
3/4	89.28	3/4	333.80	3/4	578.37	3/4	822.29	3/4	1,066.79	3/4	1,311.34	3/4	1,555.89	3/4	1,800.44	3/4	2,045.11	3/4	2,289.80	3/4	2,532.43	3/4	2,747.73	3/4	2,961.56	3/4	3,175.38	3/4	The second second	3/4	
5	94.26	5	338.90	5	583.45	5	827.38	5	1,071.88	5	1,316.43	5	1,560.98	5	1,805.53	5	2,050.21	5	2,294.89	5	2,537.21	5	2,752.19	5	2,966.01	5	3,179.84	5	3,393.66	5	
1/4	99.36	1/4	344.00	1/4	588.53	1/4	832.48	1/4	1,076.98	1/4	1,321.53	1/4	1,566.08	1/4	1,810.63	1/4	2,055.31	1/4	2,299.99	1/4	2,541.85	1/4	2,756.64	1/4	2,970.47	1/4	3,184.29	1/4		1/4	1
1/2	104.45	1/2	349.09	1/2	593.60	1/2	837.57	1/2	1,082.07	1/2	1,326.62	1/2	1,571.17	1/2	1,815.72	1/2	2,060.40	1/2	2,305.09	1/2	2,546.50	1/2	2,761.10		2,974.92		3,188.75	1/2		1/2	- 1
3/4	109.55	3/4	354.19	3/4	598.68	3/4	842.67	3/4	1,087.17	3/4	1,331.72	3/4	1,576.27	3/4	1,820.82	3/4	2,065.50	3/4	2,310.19	3/4	2,551.15	3/4	2,765.55	-	2,979.38	3/4	3,193.20	3/4		3/4	
6	114.65	6	359.29	6	603.76	6	847.76	6	1,092.26	6	1,336.81	6	1,581.36	6	1,825.91	6	2,070.60	6	2,315.28	6	2,555.79	6	2,770.01	6	2,983.83	6	3,197.66	6	3,411.48	6	- 1
1/4	119.75	1/4	364.38	1/4	608.84	1/4	852.85	1/4	1,097.36	1/4	1,341.91	1/4	1,586.46	1/4	1,831.01	1/4	2,075.70	1/4	2,320.38	1/4	2,560.35	1/4	2,774.46	1/4	2,988.29	1/4	3,202.11	1/4	3,415.94	1/4	- 1
1/2	124.84	1/2	369.48	1/2	613.92	1/2	857.95	1/2	1,102.45	1/2	1,347.00	1/2	1,591.55	1/2	1,836.11	1/2	2,080.79	1/2	2,325.48	1/2	2,564.90	1/2	2,778.91	1/2	2,992.74	1/2	3,206.57	1/2	3,420.39	1/2	- 1
3/4	129.94	3/4	374.58	3/4	618.99	3/4	863.04	3/4	1,107.55	3/4	1,352.10	3/4	1,596.65	3/4	1,841.21	3/4	2,085.89	3/4	2,330.58	3/4	2,569.45	3/4	2,783.37	3/4	2,997.19	3/4	3,211.02	3/4		3/4	
7	135.04	7	379.68	7	624.07	7	868.14	7	1,112.64	7	1,357.19	7	1,601.74	7	1,846.30	7	2,090.99	7	2,335.67	7	2,574.00	7	2,787.82	7	3,001.65	7	3,215.48	7	3,429.30	7	
1/4	140.13	1/4	384.78	1/4	629.15	1/4	873.23	1/4	1,117.74	1/4	1,362.29	1/4	1,606.84	1/4	1,851.40	1/4	2,096.09	1/4	2,340.77	1/4	2,578.45	1/4	2,792.28	1/4	3,006.10	1/4	3,219.93	1/4		1/4	- 1
1/2	145.23	1/2	389.87	1/2	634.23	1/2	878.32	1/2	1,122.83	1/2	1,367.38	1/2	1,611.93	1/2	1,856.50	1/2	2,101.18	1/2	2,345.87	1/2	2,582.91	1/2	2,796.73	- Inches	3,010.56		3,224.38	1/2		1/2	- 1
3/4	150.32	3/4	394.97	3/4	639.31	3/4	883.42	3/4	1,127.93	3/4	1,372.48	_	1,617.03	3/4	1,861.60	3/4	2,106.28	3/4	2,350.97	3/4	2,587.36	3/4	2,801.19	_	3,015.01	3/4	3,228.84	3/4		3/4	
8	155.42	8	400.07	8	644.38	8	888.51	8	1,133.02	8	1,377.57	8	1,622.12	8	1,866.69	8	2,111.38	8	2,356.06	8	2,591.82	8	2,805.64	8	3,019.47	8	3,233.29	8	3,447.12	8	- 1
1/4	160.52	1/4	405.17	1/4	649.46	1/4	893.60	1/4	1,138.12	1/4	1,382.67	1/4	1,627.22	1/4	1,871.79	1/4	2,116.48	1/4	2,361.16	1/4	2,596.27	1/4	2,810.10	1/4	3,023.92	1/4	3,237.75	1/4		1/4	- 1
1/2	165.61	1/2	410.27	1/2	654.54	1/2	898.70	1/2	1,143.21	1/2	1,387.76	1/2	1,632.31	1/2	1,876.89	1/2	2,121.57	1/2	2,366.26	1/2	2,600.73	1/2	2,814.55	1/2	3,028.38	1/2	3,242.20	1/2	3,456.03	1/2	- 1
3/4	170.71	3/4	415.36	3/4	659.62	3/4	903.79	3/4	1,148.31	3/4	1,392.86	3/4	1,637.41	3/4	1,881.99	3/4	2,126.67	3/4	2,371.36	3/4	2,605.18	3/4	2,819.01	3/4	3,032.83	3/4	3,246.66	3/4	The state of the s	3/4	
9	175.81	9	420.46	9	664.70	9	908.89	9	1,153.40	9	1,397.95	9	1,642.50	9	1,887.08	9	2,131.77	9	2,376.45	9	2,609.64	9	2,823.46	9	3,037.29	9	3,251.11	9	3,464.82	9	- 1
1/4	180.90	1/4	425.56	1/4	669.78	1/4	913.98	1/4	1,158.49	1/4	1,403.05	1/4	1,647.60	1/4	1,892.18	1/4	2,136.87	1/4	2,381.55	1/4	2,614.09	1/4	2,827.92	1/4	3,041.74	1/4	3,255.57	1/4	3,469.21	1/4	- 1
1/2	186.00	1/2	430.66	1/2	674.85	1/2	919.07	1/2	1,163.59	1/2	1,408.14	1/2	1,652.69	1/2	1,897.28	1/2	2,141.96	1/2	2,386.65	1/2	2,618.55	1/2	2,832.37	3/4	3,046.20	3/4	3,260.02	3/4		3/4	- 1
3/4	191.10	3/4	435.75	3/4	679.93	3/4	924.17	3/4	1,168.68	3/4	1,413.23	3/4	1,657.79	3/4	1,902.38	3/4	2,147.06	3/4	2,391.75	3/4	2,623.00	3/4	2,836.83	-	3,050.65	1	3,264.48	-		-	
10	196.19	10	440.85	10	685.01	10	929.26	10	1,173.78	10	1,418.33	10	1,662.88	10	1,907.48	10	2,152.16	10	2,396.84	10	2,627.45	10	2,841.28	10	3,055.11	10	3,268.93	10		10	
1/4	201.29	1/4	445.95	1/4	690.09	1/4	934.35	1/4	1,178.87	1/4	1,423.42	1/4	1,667.97	1/4	1,912.57	1/4	2,157.26	1/4	2,401.94	1/4	2,631.91	1/4	2,845.74	1/4	3,059.56	1/4	3,273.39	1/4	3,485.44	1/4	- 1
1/2	206.39	1/2	451.04	1/2	695.17	1/2	939.45	1/2	1,183.97	1/2	1,428.52		1,673.07	1/2	1,917.67	1/2	2,162.36	1/2	2,407.04	1/2	2,636.36	1/2	2,850.19	1/2	3,064.02	1/2	3,277.84	1/2	3,489.39	1/2	- 1
3/4	211.48	3/4	456.14	3/4	700.24	3/4	944.54	3/4	1,189.06	3/4	1,433.61	3/4	1,678.16	3/4	1,922.77	3/4	2,167.45	3/4	2,412.13	3/4	2,640.82	3/4	2,854.64	3/4	3,068.47	3/4	3,282.30	3/4	3,492.45	3/4	
11	216.58	11	461.24	11	705.32	11	949.63	11	1,194.16	11	1,438.71	11	1,683.26	11	1,927.87	11	2,172.55	11	2,417.23	11	2,645.27	11	2,859.10		3,072.92	1	3,286.75	11		11	- 1
1/4	221.68	1/4	466.33	1/4	710.40	1/4	954.72	1/4	1,199.25	1/4	1,443.80	1/4	1,688.35	1/4	1,932.96	1/4	2,177.65	1/4	2,422.32	1/4	2,649.73	1/4	2,863.55		3,077.38		3,291.20	1/4		1/4	- 1
1/2	226.77	1/2	471.43	1/2	715.48	1/2	959.82	1/2	1,204.35	1/2	1,448.90	1/2	1,693.45	1/2	1,938.06	1/2	2,182.75		2,427.42	1/2	2,654.18	1/2	2,868.01		3,081.83		3,295.66		3,501.61	1/2	- 1
3/4	231.87	3/4	476.52	3/4	720.56	3/4	964.91	3/4	1,209.44	3/4	1,453.99	3/4	1,698.54	3/4	1,943.16	3/4	2,187.84	3/4	2,432.51	3/4	2,658.64	3/4	2,872.46	3/4	3,086.29	3/4	3,300.11	distribution of the last	3,503.77	3/4	D DDETT
NOTE:	JAPACITY TABL	LE APPLIES	UNLY TO MANU	JAL INNAG	ISS TAKEN AT 1	HE TOP LI	P OF MMC VALV	Æ																	E OTDADDED			IN	TERTEK (	JALE	PREIL

NOTE: GAUGE POINT LOCATED IN GEOMETRIC CENTER OF TANK

NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

DATE STRAPPED 8/8/08 BY: JLF DATE COMPUTED: 8/13/08 BY: WHF DATE ISSUED: 8/15/08

Intertek Caleb Brett

### BARGE "CCL 28" HULL NO. C&C Marine # 07-093

TANK NO. 2 INNAGE TABLE

CAPA	CITIES GIVEN	IN BAR	RELS OF 42 U	S. GALI	.ons																								GAUGE HE	IGHT:	16' 2 3/4"
IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.
0	0.56	0	275.07	0	551.67	0	827.50	0	1,103.79	0	1,380.33	0	1,656.90	0	1,933.46	0	2,210.03	0	2,486.60	0	2,763.16	0	3,039.73	0	3,316.29	0	3,592.86	0	3,869.43	0	4,126.27
1/4	6.12	1/4	280.84	1/4	557.43	1/4	833,24	1/4	1,109.55	1/4	1,386.09	1/4	1,662.66	1/4	1,939.22	1/4	2,215.79	1/4	2,492.36	1/4	2,768.92	1/4	3,045.49	1/4	3,322.06	1/4	3,598.62	1/4	3,875.19	1/4	4,128.36
1/2	11.68	1/2	286.60	1/2	563.19	1/2	838.98	1/2	1,115.31	1/2	1,391.85	1/2	1,668.42	1/2	1,944.99	1/2	2,221.55	1/2	2,498.12	1/2	2,774.69	1/2	3,051.25	1/2	3,327.82	1/2	3,604.38	1/2	3,880.95	1/2	4,130.45
3/4	17.24	3/4	292.36	3/4	568.95	3/4	844.71	3/4	1,121.06	3/4	1,397.62	3/4	1,674.18	3/4	1,950.75	3/4	2,227.31	3/4	2,503.88	3/4	2,780.45	3/4	3,057.01	3/4	3,333.58	3/4	3,610.15	3/4	3,886.71	3/4	4,131.09
1	22.79	1	298.12	1	574.71	1	850.45	1	1,126.82	1	1,403.38	1	1,679.94	1	1,956.51	1	2,233.08	1	2,509.64	1	2,786.21	1	3,062.78	1	3,339.34	1	3,615.91		3,892.47	1	4,131.74
1/4	28.41	1/4	303.88	1/4	580.48	1/4	856.19	1/4	1,132.58	1/4	1,409.14	1/4	1,685.71	1/4	1,962.27	1/4	2,238.84	1/4	2,515.40	1/4	2,791.97	1/4	3,068.54	1/4	3,345.10	1/4	3,621.67		3,898.24	1/4	4,132.38
1/2	34.02	1/2	309.64	1/2	586.24	1/2	861.93	1/2	1,138.34	1/2	1,414.90	1/2	1,691.47	1/2	1,968.03	1/2	2,244.60	1/2	2,521.17	1/2	2,797.73	1/2	3,074.30	1/2	3,350.87	1/2	3,627.43	-	3,904.00	1/2	4,133.03
3/4	39,64	3/4	315.41	3/4	592.00	3/4	867.67	3/4	1,144.10	3/4	1,420.66	3/4	1,697.23	3/4	1,973.80	3/4	2,250.36	3/4	2,526.93	3/4	2,803.49	3/4	3,080.06	3/4	3,356.63	3/4	3,633.19	3/4	3,909.76	3/4	
2	45.25	2	321.17	2	597.76	2	873.41	2	1,149.86	2	1,426.42	2	1,702.99	2	1,979.56	2	2,256.12	2	2,532.69	2	2,809.26	2	3,085.82	2	3,362.39	2	3,638.96	-	3,915.52	2	
1/4	50.92	1/4	326.93	1/4	603.52	1/4	879.17	1/4	1,155.62	1/4	1,432.19	1/4	1,708.75	-	1,985.32	1/4	2,261.89	1/4	2,538.45	1/4	2,815.02	1/4	3,091.58	1/4	3,368.15	1/4	3,644.72		3,921.28	1/4	- 1
1/2	56.59	1/2	332.69	1/2	609.28	1/2	884.93	1/2	1,161.38	1/2	1,437.95	1/2	1,714.51	1/2	1,991.08	1/2	2,267.65	1/2	2,544.21	1/2	2,820.78	1/2	3,097.35	1/2	3,373.91	1/2	3,650.48		3,927.05	1/2	- 1
3/4	62.26	3/4	338.45	3/4	615.04	3/4	890.69	3/4	1,167.14	3/4	1,443.71	3/4	1,720.28	3/4	1,996.84	3/4	2,273.41	3/4	2,549.98	3/4	2,826.54	3/4	3,103.11	3/4	3,379.67	3/4	3,656.24	_	3,932.81	3/4	
3	67.93	3	344.22	3	620.80	3	896.45	3	1,172.91	3	1,449.47	3	1,726.04	3	2,002.60	3	2,279.17	3	2,555.74	3	2,832.30	3	3,108.87		3,385.44	3	3,662.00	-	3,938.57	3	
1/4	73.64	1/4	349.98	1/4	626.56	1/4	902.21	1/4	1,178.67	1/4	1,455.23	1/4	1,731.80	1/4	2,008.37	1/4	2,284.93	1/4	2,561.50	1/4	2,838.07	1/4	3,114.63	1/4	3,391.20	1/4	3,667.76	-	3,944.33	1/4	- 1
1/2	79.35	1/2	355.74	1/2	632.32	1/2	907.97	1/2	1,184.43	1/2	1,461.00	1/2	1,737.56	1/2	2,014.13	1/2	2,290.69	1/2	2,567.26	1/2	2,843.83	1/2	3,120.39	1/2	3,396.96	1/2	3,673.53		3,950.09	1/2	- 1
3/4	85.05	3/4	361.50	3/4	638.08	3/4	913.73	3/4	1,190.19	3/4	1,466.76	3/4	1,743.32	3/4	2,019.89	3/4	2,296.46	3/4	2,573.02	3/4	2,849.59	3/4	3,126.16	3/4	3,402.72	3/4	3,679.29		3,955.85	3/4	
4	90.76	4	367.26	4	643.84	4	919.49	4	1,195.95	4	1,472.52	4	1,749.09	4	2,025.65	4	2,302.22	4	2,578.78	4	2,855.35	4	3,131.92	4	3,408.48	4	3,685.05		3,961.62	4	- 1
1/4	96.50	1/4	373.02	1/4	649.57	1/4	925.25	1/4	1,201.71	1/4	1,478.28	1/4	1,754.85	1/4	2,031.41	1/4	2,307.98	1/4	2,584.55	1/4	2,861.11	1/4	3,137.68	1/4	3,414.25	1/4	3,690.81		3,967.38	1/4	- 1
1/2	102.25	1/2	378.79	1/2	655.31	1/2	931.01	1/2	1,207.48	1/2	1,484.04	1/2	1,760.61	1/2	2,037.18	1/2	2,313.74	1/2	2,590.31	1/2	2,866.87	1/2	3,143.44	1/2	3,420.01	1/2	3,696.57		3,973.14	1/2	- 1
3/4	107.99	3/4	384.55	3/4	661.05	3/4	936.77	3/4	1,213.24	3/4	1,489.80	3/4	1,766.37	3/4	2,042.94	3/4	2,319.50	3/4	2,596.07	3/4	2,872.64	3/4	3,149.20	3/4	3,425.77	3/4	3,702.34	_	3,978.90	3/4	
5	113.74	5	390.31	5	666.79	5	942.53	5	1,219.00	5	1,495.57	5	1,772.13	5	2,048.70	5	2,325.27	5	2,601.83	5	2,878.40	5	3,154.96	5	3,431.53	5	3,708.10		3,984.66	5	
1/4	119.50	1/4	396.07	1/4	672.53	1/4	948.29	1/4	1,224.76	1/4	1,501.33	1/4	1,777.89	1/4	2,054.46	1/4	2,331.03	1/4	2,607.59	1/4	2,884.16	1/4	3,160.73	1/4	3,437.29	1/4	3,713.86		3,990.43	1/4	- 1
1/2	125.26	1/2	401.83	1/2	678.27	1/2	954.05	1/2	1,230.52	1/2	1,507.09	1/2	1,783.66	1/2	2,060.22	1/2	2,336.79	1/2	2,613.36	1/2	2,889.92	1/2	3,166.49	1/2	3,443.05	1/2	3,719.62		3,996.19	1/2	- 1
3/4	131.03	3/4	407.60	3/4	684.01	3/4	959.81	3/4	1,236.28	3/4	1,512.85	3/4	1,789.42	3/4	2,065.98	3/4	2,342.55	3/4	2,619.12	3/4	2,895.68	3/4	3,172.25	3/4	3,448.82	3/4	3,725.38		4,001.95	3/4	
6	136.79	6	413.36	6	689,75	6	965.57	6	1,242.05	6	1,518.61	6	1,795.18	6	2,071.75	6	2,348.31	6	2,624.88	6	2,901.45	6	3,178.01	6	3,454.58	6	3,731.14	6	4,007.71	6	
1/4	142.55	1/4	419.12	1/4	695.49	1/4	971.32	1/4	1,247.81	1/4	1,524.37	1/4	1,800.94	1/4	2,077.51	1/4	2,354.07	1/4	2,630.64	1/4	2,907.21	1/4	3,183.77	1/4	3,460.34	1/4	3,736.91		4,013.47	1/4	- 1
1/2	148.31	1/2	424.88	1/2	701.23	1/2	977.08	1/2	1,253.57	1/2	1,530.14	1/2	1,806.70	1/2	2,083.27	1/2	2,359.84	1/2	2,636.40	1/2	2,912.97	1/2	3,189.54	1/2	3,466.10	1/2	3,742.67		4,019.23	1/2	- 1
3/4	154.07	3/4	430.65	3/4	706.97	3/4	982.84	3/4	1,259.33	3/4	1,535.90	3/4	1,812.46	3/4	2,089.03	3/4	2,365.60	3/4	2,642.16	3/4	2,918.73	3/4	3,195.30	3/4	3,471.86	3/4	3,748.43		4,025.00	3/4	
7	159.84	7	436.41	7	712.71	7	988.60	7	1,265.09	7	1,541.66	7	1,818.23	7	2,094.79	7	2,371.36	7	2,647.93	7	2,924.49	7	3,201.06	7	3,477.63	7	3,754.19	-	4,030.76	7	- 1
1/4	165.60	1/4	442.17	1/4	718.45	1/4	994.36	1/4	1,270.86	1/4	1,547.42	1/4	1,823.99	1/4	2,100.55	1/4	2,377.12	1/4	2,653.69	1/4	2,930.25	1/4	3,206.82	1/4	3,483.39	1/4	3,759.95	-	4,036.52	1/4	
1/2	171.36	1/2	447.94	1/2	724.19	1/2	1,000.12	1/2	1,276.62	1/2	1,553.18	1/2	1,829.75	1/2	2,106.32	1/2	2,382.88	1/2	2,659.45	1/2	2,936.02	1/2	3,212.58	1/2	3,489.15	1/2	3,765.72		4,042.28	1/2	- 1
3/4	177.12	3/4	453.70	3/4	729.93	3/4	1,005.88	3/4	1,282.38	3/4	1,558.95	3/4	1,835.51	3/4	2,112.08	3/4	2,388.64	3/4	2,665.21	3/4	2,941.78	3/4	3,218.34	3/4	3,494.91	3/4	3,771.48	_	4,048.04	3/4	
8	182.88	8	459.47	8	735.67	8	1,011.64	8	1,288.14	8	1,564.71	8	1,841.27	8	2,117.84	8	2,394.41	8	2,670.97	8	2,947.54	8	3,224.11	8	3,500.67	8	3,777.24		4,053.81	8	
1/4	188.65	1/4	465.23	1/4	741.41	1/4	1,017.40	1/4	1,293.90	1/4	1,570.47	1/4	1,847.04	1/4	2,123.60	1/4	2,400.17	1/4	2,676.73	1/4	2,953.30	1/4	3,229.87	1/4	3,506.43	1/4	3,783.00		4,059.57	1/4	- 1
1/2	194.41	1/2	470.99	1/2	747.14	1/2	1,023.16	1/2	1,299.66	1/2	1,576.23	1/2	1,852.80	1/2	2,129.36	1/2	2,405.93	1/2	2,682.50	1/2	2,959.06	1/2	3,235.63	1/2	3,512.20	1/2	3,788.76	1/2	4,065.33	1/2	- 1
3/4	200.17	3/4	476.76	3/4	752.88	3/4	1,028.92	3/4	1,305.43	3/4	1,581.99	3/4	1,858.56	3/4	2,135.13	3/4	2,411.69	3/4	2,688.26	3/4	2,964.82	3/4	3,241.39	3/4	3,517.96	3/4	3,794.52	_	4,071.02	3/4	
9	205.93	9	482.52	9	758.62	9	1,034.68	9	1,311.19	9	1,587.75	9	1,864.32	9	2,140.89	9	2,417.45	9	2,694.02	9	2,970.59	9	3,247.15	9	3,523.72	9	3,800.29	9	4,076.71	9	
1/4	211.69	1/4	488.28	1/4	764.36	1/4	1,040.44	1/4	1,316.95	1/4	1,593.52	1/4	1,870.08	1/4	2,146.65	1/4	2,423.22	1/4	2,699.78	1/4	2,976.35	1/4	3,252.91	1/4	3,529.48	1/4	3,806.05	1/4	4,082.41	1/4	- 1
1/2	217.45	1/2	494.05	1/2	770.10	1/2	1,046.20	1/2	1,322.71	1/2	1,599.28	1/2	1,875.84	1/2	2,152.41	1/2	2,428.98	1/2	2,705.54	1/2	2,982.11	1/2	3,258.68	1/2	3,535.24	1/2	3,811.81	1/2	4,088.10	1/2	- 1
3/4	223,22	3/4	499.81	3/4	775.84	3/4	1,051.96	3/4	1,328.47	3/4	1,605.04	3/4	1,881.61	3/4	2,158.17	3/4	2,434.74	3/4	2,711.31	3/4	2,987.87	3/4	3,264.44	3/4	3,541.00	3/4	3,817.57	3/4	4,093.07	3/4	
10	228,98	10	505.57	10	781.58	10	1,057.72	10	1,334.24	10	1,610.80	10	1,887.37	10	2,163.93	10	2,440.50	10	2,717.07	10	2,993.63	10	3,270.20	10	3,546.77	10	3,823.33	10	4,098.04	10	
1/4	234.74	1/4	511.33	1/4	787.32	1/4	1,063.48	1/4	1,340.00	1/4	1,616.56	1/4	1,893.13	1/4	2,169.70	1/4	2,446.26	1/4	2,722.83	1/4	2,999.40	1/4	3,275.96	1/4	3,552.53	1/4	3,829.09	1/4	4,103.01	1/4	- 1
1/2	240.50	1/2	517.10	1/2	793.06	1/2	1,069.24	1/2	1,345.76	1/2	1,622.33	1/2	1,898.89	1/2	2,175.46	1/2	2,452.02	1/2	2,728.59	1/2	3,005.16	1/2	3,281.72	1/2	3,558.29	1/2	3,834.86	1/2	4,107.98	1/2	- 1
3/4	246.26	3/4	522.86	3/4	798.80	3/4	1,074.99	3/4	1,351.52	3/4	1,628.09	3/4	1,904.65	3/4	2,181.22	3/4	2,457.79	3/4	2,734.35	3/4	3,010.92	3/4	3,287.49	3/4	3,564.05	3/4	3,840.62	3/4	4,111.51	3/4	
11	252.03	11	528.62	11	804.54	11	1,080.75	11	1,357.28	11	1,633.85	11	1,910.42	11	2,186.98	11	2,463.55	11	2,740.11	11	3,016.68	11	3,293.25	11	3,569.81	11	3,846.38		4,115.04	11	
1/4	257.79	1/4	534.38	1/4	810.28	1/4	1,086.51	1/4	1,363.04	1/4	1,639.61	1/4	1,916.18	1/4	2,192.74	1/4	2,469.31	1/4	2,745.88	1/4	3,022.44	1/4	3,299.01	1/4	3,575.58	1/4	3,852.14	1/4	4,118.57	1/4	- 1
1/2	263.55	1/2	540.14	1/2	816.02	1/2	1,092.27	1/2	1,368.81	1/2	1,645.37	1/2	1,921.94	1/2	2,198.51	1/2	2,475.07	1/2	2,751.64	1/2	3,028.20	1/2	3,304.77	1/2	3,581.34	1/2	3,857.90	1/2	4,122.10	1/2	- 1
3/4	269.31	3/4	545.91	3/4	821.76	3/4	1,098.03	3/4	1,374.57	3/4	1,651.13		1,927.70	3/4	2,204.27	3/4	2,480.83	3/4	2,757.40	3/4	3,033.97	3/4	3,310.53	3/4	3,587.10	3/4	3,863.67	3/4	4,124.19	3/4	
NOTE: 0	CAPACITY TABL	E APPLIES	ONLY TO MANU	JAL INNAC	ES TAKEN AT T	HE TOP L	IP OF MMC VALV	VE.																				IN.	TERTEK	CALE	B BRETT
NOTE: 0	SAUGE POINT L	OCATED II	N GEOMETRIC C	ENTER O	FTANK																			DAT	E STRAPPED	8/8/08 8	BY: JLF		_		/ 1.

NOTE: GAUGE POINT LOCATED IN GEOMETRIC CENTER OF TANK

NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

DATE STRAPPED 8/8/08 BY: JLF DATE COMPUTED: 8/13/08 BY: WHF DATE ISSUED: 8/15/08

Intertek Caleb Brett

### BARGE "CCL 28" HULL NO. C&C Marine # 07-093

TANK NO. 3 INNAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS  GAUGE HEIGHT: 16'2 3:4"  10 FT   11   10 FT   11														16' 2 3/4"																	
IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.	IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15.00
0	0.56	0	247.09	0	495.48	0	743.19	0	991.30	0	1,239.65	0	1,488.02	0	1,736.39	0	1,984.76	0	2,233.13	0	2,481.50	0	2,729.87	0	2,978.25	0	3,226.62	0	3,474.99	0	3,705.65
1/4	5.55	1/4	252.26	1/4	500.66	1/4	748.34	1/4	996.47	1/4	1,244.82	1/4	1,493.19	1/4	1,741.56	1/4	1,989.94	1/4	2,238.31	1/4	2,486.68	1/4	2,735.05	1/4	2,983.42	1/4	3,231.79	1/4	3,480.16	1/4	3,707.52
1/2	10.54	1/2	257.43	1/2	505.83	1/2	753.50	1/2	1,001.64	1/2	1,250.00	1/2	1,498.37	1/2	1,746.74	1/2	1,995.11	1/2	2,243.48	1/2	2,491.85	1/2	2,740.22	1/2	2,988.59	1/2	3,236.97	1/2	3,485.34	1/2	3,709.40
3/4	15.53	3/4	262.61	3/4	511.01	3/4	758.65	3/4	1,006.82	3/4	1,255.17	3/4	1,503.54	3/4	1,751.91	3/4	2,000.28	3/4	2,248.66	3/4	2,497.03	3/4	2,745.40	3/4	2,993.77	3/4	3,242.14		3,490.51		3,709.98
1	20.53	1	267.78	1	516.18	1	763.80	1	1,011.99	1	1,260.35	1	1,508.72	1	1,757.09	1	2,005.46	1	2,253.83	1	2,502.20	1	2,750.57	1	2,998.94	1	3,247.31	_	3,495.69	-	3,710.55
1/4	25.57	1/4	272.96	1/4	521.36	1/4	768.96	1/4	1,017.16	1/4	1,265.52	1/4	1,513.89	1/4	1,762.26	1/4	2,010.63	1/4	2,259.00	1/4	2,507.38	1/4	2,755.75	1/4	3,004.12	1/4	3,252.49	-	3,500.86	-	3,711.13
1/2	30.61	1/2	278.13	1/2	526.53	1/2	774.11	1/2	1,022.33	1/2	1,270.69	1/2	1,519.07	1/2	1,767.44	1/2	2,015.81	1/2	2,264.18	1/2	2,512.55	1/2	2,760.92	1/2	3,009.29	1/2	3,257.66		3,506.03	1/2	3,711.71
3/4	35.65	3/4	283.31	3/4	531.70	3/4	779.27	3/4	1,027.50	3/4	1,275.87	3/4	1,524.24	3/4	1,772.61	3/4	2,020.98	3/4	2,269.35	3/4	2,517.72	3/4	2,766.10	3/4	3,014.47	3/4	3,262.84		3,511.21	3/4	-
2	40.69	2	288.48	2	536.88	2	784.42	2	1,032.67	2	1,281.04	2	1,529.41	2	1,777.79	2	2,026.16	2	2,274.53	2	2,522.90	2	2,771.27	2	3,019.64	2	3,268.01	-	3,516.38	2	
1/4	45.79	1/4	293,65	1/4	542.05	1/4	789.59	1/4	1,037.85	1/4	1,286.22	1/4	1,534.59	1/4	1,782.96	1/4	2,031.33	1/4	2,279.70	1/4	2,528.07	1/4	2,776.44	1/4	3,024.82	1/4	3,273.19		3,521.56	1/4	
1/2	50.88	1/2	298.83	1/2	547.22	1/2	794.77	1/2	1,043.02	1/2	1,291.39	1/2	1,539.76	1/2	1,788.13	1/2	2,036.51	1/2	2,284.88	1/2	2,533.25	1/2	2,781.62	1/2	3,029.99	1/2	3,278.36		3,526.73	1/2	- 1
3/4	55.97	3/4	304.00	3/4	552.39	3/4	799.94	3/4	1,048.19	3/4	1,296.57	3/4	1,544.94	3/4	1,793.31	3/4	2,041.68	3/4	2,290.05	3/4	2,538.42	3/4	2,786.79	3/4	3,035.16	3/4	3,283.54	-	3,531.91	3/4	
3	61.06	3	309.18	3	557.57	3	805.11	3	1,053.37	3	1,301.74	3	1,550.11	3	1,798.48	3	2,046.85	3	2,295.23	3	2,543.60	3	2,791.97	3	3,040.34	3	3,288.71	-	3,537.08	3	
1/4	66.19	1/4	314.35	1/4	562.74	1/4	810.28	1/4	1,058.54	1/4	1,306.91	1/4	1,555.29	1/4	1,803.66	1/4	2,052.03	1/4	2,300.40	1/4	2,548.77	1/4	2,797.14	1/4	3,045.51	1/4	3,293.88	-	3,542.26	1/4	- 1
1/2	71.31	1/2	319.53	1/2	567.91	1/2	815.45	1/2	1,063.72	1/2	1,312.09	1/2	1,560.46	1/2	1,808.83	1/2	2,057.20	1/2	2,305.57	1/2	2,553.95	1/2	2,802.32	1/2	3,050.69	1/2	3,299.06		3,547.43	1/2	- 1
3/4	76.44	3/4	324.70	3/4	573.08	3/4	820.63	3/4	1,068.89	3/4	1,317.26	3/4	1,565.63	3/4	1,814.01	3/4	2,062.38	3/4	2,310.75	3/4	2,559.12	3/4	2,807.49	3/4	3,055.86	3/4	3,304.23	-	3,552.60	3/4	
4	81.56	4	329.88	4	578.25	4	825.80	4	1,074.07	4	1,322.44	4	1,570.81	4	1,819.18	4	2,067.55	4	2,315.92	4	2,564.29	4	2,812.67	4	3,061.04	4	3,309.41		3,557.78	4	
1/4	86.72	1/4	335.05	1/4	583.41	1/4	830.97	1/4	1,079.24	1/4	1,327.61	1/4	1,575.98	1/4	1,824.35	1/4	2,072.73	1/4	2,321.10	1/4	2,569.47	1/4	2,817.84	1/4	3,066.21	1/4	3,314.58		3,562.95	1/4	- 1
1/2	91.88	1/2	340.22	1/2	588.56	1/2	836.14	1/2	1,084.42	1/2	1,332.79	1/2	1,581.16	1/2	1,829.53	1/2	2,077.90	1/2	2,326.27	1/2	2,574.64	1/2	2,823.01	1/2	3,071.39	1/2	3,319.76		3,568.13	1/2	- 1
3/4	97.04	3/4	345.40	3/4	593.72	3/4	841.32	3/4	1,089.59	3/4	1,337.96	3/4	1,586.33	3/4	1,834.70	3/4	2,083.07	3/4	2,331.45	3/4	2,579.82	3/4	2,828.19	3/4	3,076.56	3/4	3,324.93	-	3,573.30	3/4	
5	102.20	5	350.57	5	598.87	5	846.49	5	1,094.76	5	1,343.14	5	1,591.51	5	1,839.88	5	2,088.25	5	2,336.62	5	2,584.99	5	2,833.36	5	3,081.73	5	3,330.11	5	3,578.48	5	
1/4	107.37	1/4	355.75	1/4	604.02	1/4	851.66	1/4	1,099.94	1/4	1,348.31	1/4	1,596.68	1/4	1,845.05	1/4	2,093.42	1/4	2,341.79	1/4	2,590.17	1/4	2,838.54	1/4	3,086.91	1/4	3,335.28		3,583.65	1/4	- 1
1/2	112.55	1/2	360.92	1/2	609.18	1/2	856.83	1/2	1,105.11	1/2	1,353.48	1/2	1,601.86	1/2	1,850.23	1/2	2,098.60	1/2	2,346.97	1/2	2,595.34	1/2	2,843.71	1/2	3,092.08	1/2	3,340.45		3,588.83	1/2	- 1
3/4	117.72	3/4	366.10	3/4	614.33	3/4	862.00	3/4	1,110.29	3/4	1,358.66	3/4	1,607.03	3/4	1,855.40	3/4	2,103.77	3/4	2,352.14	3/4	2,600.51	3/4	2,848.89	3/4	3,097.26	3/4	3,345.63		3,594.00	3/4	
6	122.90	6	371.27	6	619.49	6	867.18	6	1,115.46	6	1,363.83	6	1,612.20	6	1,860.58	6	2,108.95	6	2,357.32	6	2,605.69	6	2,854.06	6	3,102.43	6	3,350.80	6	3,599.17	6	
1/4	128.07	1/4	376.45	1/4	624.64	1/4	872.35	1/4	1,120.64	1/4	1,369.01	1/4	1,617.38	1/4	1,865.75	1/4	2,114.12	1/4	2,362.49	1/4	2,610.86	1/4	2,859.23	1/4	3,107.61	1/4	3,355.98	1/4	3,604.35	1/4	- 1
1/2	133.25	1/2	381.62	1/2	629.80	1/2	877.52	1/2	1,125.81	1/2	1,374.18	1/2	1,622.55	1/2	1,870.92	1/2	2,119.30	1/2	2,367.67	1/2	2,616.04	1/2	2,864.41	1/2	3,112.78	1/2	3,361.15	1/2	3,609.52	1/2	- 1
3/4	138.42	3/4	386.80	3/4	634.95	3/4	882.69	3/4	1,130.99	3/4	1,379.36	3/4	1,627.73	3/4	1,876.10	3/4	2,124.47	3/4	2,372.84	3/4	2,621.21	3/4	2,869.58	3/4	3,117.95	3/4	3,366.33	3/4	3,614.70	3/4	
7	143.60	7	391.98	7	640.10	7	887.87	7	1,136.16	7	1,384.53	7	1,632.90	7	1,881.27	7	2,129.64	7	2,378.02	7	2,626.39	7	2,874.76	7	3,123.13	7	3,371.50	7	3,619.87	7	
1/4	148.77	1/4	397.15	1/4	645.26	1/4	893.04	1/4	1,141.33	1/4	1,389.71	1/4	1,638.08	1/4	1,886.45	1/4	2,134.82	1/4	2,383.19	1/4	2,631.56	1/4	2,879.93	1/4	3,128.30	1/4	3,376.67	1/4	3,625.05	1/4	- 1
1/2	153.94	1/2	402.33	1/2	650.41	1/2	898.21	1/2	1,146.51	1/2	1,394.88	1/2	1,643.25	1/2	1,891.62	1/2	2,139.99	1/2	2,388.36	1/2	2,636.74	1/2	2,885.11	1/2	3,133.48	1/2	3,381.85	1/2	3,630.22	1/2	- 1
3/4	159.12	3/4	407.50	3/4	655.57	3/4	903.38	3/4	1,151.68	3/4	1,400.05	3/4	1,648.43	3/4	1,896.80	3/4	2,145.17	3/4	2,393.54	3/4	2,641.91	3/4	2,890.28	3/4	3,138.65	3/4	3,387.02	3/4	3,635.39	3/4	
8	164.29	8	412.68	8	660.72	8	908.55	8	1,156.86	8	1,405.23	8	1,653.60	8	1,901.97	8	2,150.34	8	2,398.71	8	2,647.08	8	2,895.46	8	3,143.83	8	3,392.20	8	3,640.57	8	
1/4	169.47	1/4	417.86	1/4	665.87	1/4	913.73	1/4	1,162.03	1/4	1,410.40	1/4	1,658.77	1/4	1,907.15	1/4	2,155.52	1/4	2,403.89	1/4	2,652.26	1/4	2,900.63	1/4	3,149.00	1/4	3,397.37	1/4	3,645.74	1/4	- 1
1/2	174.64	1/2	423.03	1/2	671.03	1/2	918.90	1/2	1,167.21	1/2	1,415.58	1/2	1,663.95	1/2	1,912.32	1/2	2,160.69	1/2	2,409.06	1/2	2,657.43	1/2	2,905.80	1/2	3,154.18	1/2	3,402.55	1/2	3,650.92	1/2	- 1
3/4	179.82	3/4	428.21	3/4	676.18	3/4	924.07	3/4	1,172.38	3/4	1,420.75	3/4	1,669.12	3/4	1,917.49	3/4	2,165.87	3/4	2,414.24	3/4	2,662.61	3/4	2,910.98	3/4	3,159.35	3/4	3,407.72	3/4	3,656.03	3/4	
9	184.99	9	433.38	9	681.34	9	929.24	9	1,177.55	9	1,425.93	9	1,674.30	9	1,922.67	9	2,171.04	9	2,419.41	9	2,667.78	9	2,916.15	9	3,164.52	9	3,412.90	9	3,661.14	9	- 1
1/4	190.17	1/4	438.56	1/4	686.49	1/4	934.41	1/4	1,182.73	1/4	1,431.10	1/4	1,679.47	1/4	1,927.84	1/4	2,176.21	1/4	2,424.59	1/4	2,672.96	1/4	2,921.33	1/4	3,169.70	1/4	3,418.07	1/4	3,666.25	1/4	
1/2	195.34	1/2	443.74	1/2	691.65	1/2	939.59	1/2	1,187.90	1/2	1,436.27	1/2	1,684.65	1/2	1,933.02	1/2	2,181.39	1/2	2,429.76	1/2	2,678.13	1/2	2,926.50	1/2	3,174.87	1/2	3,423.24	1/2	3,671.37	1/2	
3/4	200.51	3/4	448.91	3/4	696.80	3/4	944.76	3/4	1,193.08	3/4	1,441.45	3/4	1,689.82	3/4	1,938.19	3/4	2,186.56	3/4	2,434.93	3/4	2,683.31	3/4	2,931.68	3/4	3,180.05	3/4	3,428.42	3/4	3,675.83	3/4	
10	205.69	10	454.09	10	701.95	10	949.93	10	1,198.25	10	1,446.62	10	1,694.99	10	1,943.37	10	2,191.74	10	2,440.11	10	2,688.48	10	2,936.85	10	3,185.22	10	3,433.59	10	3,680.29	10	
1/4	210.86	1/4	459.26	1/4	707.11	1/4	955.10	1/4	1,203.43	1/4	1,451.80	1/4	1,700.17	1/4	1,948.54	1/4	2,196.91	1/4	2,445.28	1/4	2,693.65	1/4	2,942.03	1/4	3,190.40	1/4	3,438.77	1/4	3,684.76	1/4	
1/2	216.04	1/2	464.44	1/2	712.26	1/2	960.27	1/2	1,208.60	1/2	1,456.97	1/2	1,705.34	1/2	1,953.71	1/2	2,202.09	1/2	2,450.46	1/2	2,698.83	1/2	2,947.20	1/2	3,195.57	1/2	3,443.94	1/2	3,689.22	1/2	
3/4	221.21	3/4	469.61	3/4	717.42	3/4	965.45	3/4	1,213.78	3/4	1,462.15	3/4	1,710.52	3/4	1,958.89	3/4	2,207.26	3/4	2,455.63	3/4	2,704.00	3/4	2,952.37	3/4	3,200.75	3/4	3,449.12	3/4	3,692.39	3/4	
11	226.39	11	474.79	11	722.57	11	970.62	11	1,218.95	11	1,467.32	11	1,715.69	11	1,964.06	11	2,212.43	11	2,460.81	11	2,709.18	11	2,957.55	11	3,205.92	11	3,454.29	11	3,695.56	11	
1/4	231.56	1/4	479.96	1/4	727.72	1/4	975.79	1/4	1,224.12	1/4	1,472.50	1/4	1,720.87	1/4	1,969.24	1/4	2,217.61	1/4	2,465.98	1/4	2,714.35	1/4	2,962.72	1/4	3,211.09	1/4	3,459.47	1/4	3,698.73	1/4	
1/2	236.74	1/2	485.13	1/2	732.88	1/2	980.96	-	1,229.30	1/2	1,477.67	1/2	1,726.04	1/2	1,974.41	1/2	2,222.78	1/2	2,471.15	1/2	2,719.53	1/2	2,967.90	1/2	3,216.27	1/2	3,464.64	1/2	3,701.90	1/2	- 1
3/4	241.91	3/4	490.31	3/4	738.03	3/4	986.13	3/4	1,234.47	3/4	1,482.84	3/4	1,731.22	3/4		3/4	2,227.96	3/4	2,476.33	3/4	2,724.70	3/4	2,973.07	3/4	3,221.44	3/4	3,469.81	3/4	3,703.77	3/4	
NOTE:	CAPACITY TABL	E APPLIES	ONLY TO MAN	UAL INNAG	ES TAKEN AT	THE TOP LI	IP OF MMC VAL	VE.		- Annahaman		and the second																IN.	TERTEK	CALE	B BRETT
MOTE:	SALIGE DOBIT!	CATEDI	N GEOMETRIC (	ENTED OF	ETANK																			DAT	E STRAPPED	8/8/08 F	RY: JLF				/ .

NOTE: GAUGE POINT LOCATED IN GEOMETRIC CENTER OF TANK NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL

DATE STRAPPED 8/8/08 BY: JLF DATE COMPUTED: 8/13/08 BY: WHF DATE ISSUED: 8/15/08