



**United States of America  
Department of Homeland Security  
United States Coast Guard**

Certification Date: 18 Dec 2025  
Expiration Date: 18 Dec 2026

## Temporary Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

This Temporary Certificate of Inspection is issued under the provision of Title 46 United States Code, Section 399, in lieu of the regular certificate of inspection, and shall be in force only until the receipt on board said vessel of the original certificate of inspection, this certificate in no case to be valid after one year from the date of inspection.

Vessel Name	Official Number	IMO Number	Call Sign	Service
CCL 18	1168981			Tank Barge

Hailing Port	Hull Material	Horsepower	Propulsion
NEW ORLEANS, LA	Steel		
UNITED STATES			

Place Built	Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
BELLE CHASSE, LA	01Jul2005	01Apr2005	R-735	R-735		R-200.0
UNITED STATES			1	1		10

Owner	Operator
CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES	CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters	0 Licensed Mates	0 Chief Engineers	0 Oilers
0 Chief Mates	0 First Class Pilots	0 First Assistant Engineers	
0 Second Mates	0 Radio Officers	0 Second Assistant Engineers	
0 Thrd Mates	0 Able Seamen	0 Thrd Assistant Engineers	
0 Master First Class Pilot	0 Ordinary Seamen	0 Licensed Engineers	
0 Mate First Class Pilots	0 Deckhands	0 Qualified Member Engineer	

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

**Route Permitted And Conditions Of Operation:**  
**---Lakes, Bays, and Sounds plus Limited Coastwise---**

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCM notified in writing as soon as this change in status occurs.

**\*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\***

With this inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Re-Inspection				This certificate issued by: <i>L. L. Woodman</i> L. L. WOODMAN, CDR, USCG, By direction Officer In Charge, Marine Inspection Marine Safety Unit Port Arthur Inspection Zone
Date	Zone	A/P/R	Signature	



## Temporary Certificate of Inspection

Vessel Name: CCL 18

### ---Hull Exams---

Exam Type	Next Exam	Last Exam	Prior Exam
DryDock	31Dec2035	18Dec2025	14Aug2015
Internal Structure	31Dec2030	18Dec2025	05Aug2020

### --- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization: FLAMMABLE, COMBUSTIBLE LIQUIDS AND SPECIFIED HAZARDOUS CARGOES

Total Capacity	Units	Highest Grade Type	Part151 Regulated	Part153 Regulated	Part154 Regulated
11430	Barrel	A	Yes	No	No

#### \*Hazardous Bulk Solids Authority\*

Not Authorized

#### \*Loading Constraints - Structural\*

Tank Location Description	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 C/L	649	13.60
2 C/L	760	13.60
3 C/L	676	13.60

#### \*Loading Constraints - Stability\*

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
I	1429	8ft 9in	15.00	Rivers & Lakes, Bays, & Sounds
II	1519	9ft 2in	15.00	Rivers & Lakes, Bays, & Sounds
III	1735	10ft 2in	15.00	Rivers & Lakes, Bays, & Sounds
III	1807	10ft 6in	13.50	Rivers & Lakes, Bays, & Sounds
III	1825	10ft 7in	12.80	Rivers & Lakes, Bays, & Sounds
III	1915	11ft 0in	15.00	Rivers & Lakes, Bays, & Sounds
III	1969	11ft 3in	13.50	Rivers & Lakes, Bays, & Sounds
III	1987	11ft 4in	12.80	Rivers & Lakes, Bays, & Sounds

#### \*Conditions Of Carriage\*

Only those specified hazardous cargoes named in the vessel's Cargo Authority Attachment (CAA), Serial #C1-1302040, dated June 18, 2013, may be carried. The specified hazardous cargoes may be carried only in the tanks indicated.

Per 46 CFR 150.130, the person in charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group number from the "Compat Group No" column is listed in the vessel's CAA.

When the vessel is carrying cargoes containing 0.5% or greater benzene by volume, the person in charge is responsible for ensuring the provisions of 46 CFR 197, Subpart C, are applied.

46 CFR 151.45-2(b) contains restrictions on operation box and square end barges as the lead barges of tows.

#### \*Vapor Control Authorization\*



United States of America  
 Department of Homeland Security  
 United States Coast Guard

Certification Date:	18 Dec 2025
Expiration Date:	18 Dec 2026

## Temporary Certificate of Inspection

Vessel Name: CCL 19

Per 46 CFR 39, excluding Part 39.4000, this vessel's vapor control system (VCS) has been inspected to the plans approved by Marine Safety Center letter serial Marine Safety Center letters Serial #C1-1302040, dated June 18, 2013, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the CAA's VCS column.

**\*Stability and Trim\***

Per 46 CFR 151.10(c)(2), the maximum tank weights listed above reflect uniform (within 5%) loading at the deepest draft allowed. When carrying Subchapter "O" cargoes at shallower drafts, the barge should always be loaded uniformly.

The maximum design density of cargo which may be filled to the tank top is 8.745 lbs/gal. Cargoes with higher densities, up to 15.0 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

**--- Inspection Status ---**

**\*Cargo Tanks\***

Tank Id	Internal Exam			External Exam		
	Previous	Last	Next	Previous	Last	Next
1 C/L	14Aug2015	18Dec2025	31Dec2035	-	-	-
2 C/L	14Aug2015	18Dec2025	31Dec2035	-	-	-
3 C/L	14Aug2015	18Dec2025	31Dec2035	-	-	-

Tank Id	Safety Valves	Hydro Test		
		Previous	Last	Next
1 C/L	-	-	-	-
2 C/L	-	-	-	-
3 C/L	-	-	-	-

**---Conditional Portable Fire Extinguisher Requirements---**

Required Only During Transfer of Cargo or Operation of Barge Machinery

**--- Fire Fighting Equipment ---**

**\*Fire Extinguishers - Hand portable and semi-portable\***

Quantity	Class Type
2	40-B

\*\*\*END\*\*\*



United States of America  
Department of Homeland Security  
United States Coast Guard

Certification Date: 05 Aug 2020  
Expiration Date: 05 Aug 2025

# Certificate of Inspection

For ships on International voyages this certificate fulfills the requirements of SOLAS 74 as amended, per 46 CFR 1.01 for a SAFE MANNING DOCUMENT

Vessel Name	Official Number	IMO Number	Call Sign	Service
CCL 18	1168981			Tank Barge

Hailing Port	Hull Material	Construction	Construction
NEW ORLEANS, LA	Steel		
UNITED STATES			

Place Built	Delivery Date	Keel Laid Date	Deck Laid	Hull Laid	DWT	Length
BELLE CHASSE, LA	01Jul2005	01Apr2005				R-200.0
UNITED STATES						1-0

Owner	Operator
CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES	CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters	0 Licensed Mates	0 Chief Engineers	0 Oilers
0 Chief Mates	0 First Class Pilots	0 First Assistant Engineers	
0 Second Mates	0 Radio Officers	0 Second Assistant Engineer	
0 Third Mates	0 Able Seamen	0 Third Assistant Engineers	
0 Master First Class Pilot	0 Ordinary Seamen	0 Licensed Engineers	
0 Mate First Class Pilots	0 Deckhands	0 Qualified Member Engineer	

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:  
---Lakes, Bays, and Sounds plus Limited Coastwise---

Also, in fair weather only, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted a fresh water service examination interval per 46 CFR 31.10-21(a)(2). If this vessel is operated in salt water more than 6 months in any 12 month period, the vessel must be inspected using salt water intervals per 46 CFR 31.10-21(a)(1) and the cognizant OCMI notified in writing as soon as this change in status occurs.

\*\*\*SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION\*\*\*

With this Inspection for Certification having been completed at Port Arthur, TX, UNITED STATES, the Officer in Charge, Marine Inspection, Marine Safety Unit Port Arthur certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Re-Inspection				This Amended certificate issued by: <i>Joseph W. Morgan</i> JR., USCG, By Direction Officer in Charge, Marine Inspection Sector Houston-Galveston Inspection Zone
Date	Zone	A/P/R	Signature	
27Oct2021	SEC HouGalvstn	A	BATT BRIAN	
12Oct2022	SEC HouGalvstn	A	SPICARICH BRANDON	
04Oct2023	SEC Hou/GAL	P	<i>JR Morgan</i> USCG	
06Oct2024	SHG	A	<i>JR Morgan</i> USCG	



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**  
Official #: 1168981

Page 8 of 8

Shipyard: C & C Marine  
Hull #: 023

### Explanation of terms & symbols used in the Table:

#### Cargo Identification

Name	The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.
Chem Code none	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.
Compatability Group No.	The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.
Note 1	Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425.
Note 2	See Appendix I to 46 CFR Part 150 - exceptions to the compatibility chart.
Subchapter	The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified.
Subchapter D	Those flammable and combustible liquids listed in 46 CFR Table 30.25-1.
Subchapter O	Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2.
Note 3	Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
A, B, C	Flammable liquid cargoes, as defined in 46 CFR 30-10.22.
D, E	Combustible liquid cargoes, as defined in 46 CFR 30-10.15.
Note 4	The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
NA	Those subchapter O cargoes which are not classified as a flammable or combustible liquid.
#	No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.
Hull Type	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1.
I	Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1).
II	Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3).
III	Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4).
NA	Not applicable to barges certificated under Subchapter D.

#### Conditions of Carriage

Tank Group	The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

#### Conditions of Carriage

Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

VCS Category:	The specified cargo's provisional classification for vapor control systems.
Category 1	(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.
Category 2	(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation
Category 3	(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.
Category 4	(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.
Category 5	(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.
Category 6	(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5.
Category 7	(High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.
none	The cargo has not been evaluated/classified for use in vapor control systems.



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**  
 Official #: 1168981

Page 7 of 8

Shipyard: C & C Marine  
 Hull #: 023

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
Propylene glycol methyl ether acetate	PGN	34	D	D		A	Yes	1		
Propylene tetramer	PTT	30	D	D		A	Yes	1		
Sulfolane	SFL	39	D	E		A	Yes	1		
Tetraethylene glycol	TTG	40	D	E		A	Yes	1		
Tetrahydronaphthalene	THN	32	D	E		A	Yes	1		
Toluene	TOL	32	D	C		A	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		A	Yes	1		
Triethylbenzene	TEB	32	D	E		A	Yes	1		
Triethylene glycol	TEG	40	D	E		A	Yes	1		
Triethyl phosphate	TPS	34	D	E		A	Yes	1		
Trimethylbenzene (all isomers)	TRE	32	D	{D}		A	Yes	1		
Trixylenyl phosphate	TRP	34	D	E		A	Yes	1		
Undecene	UDC	30	D	D/E		A	Yes	1		
1-Undecyl alcohol	UND	20	D	E		A	Yes	1		
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		A	Yes	1		



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**

Official #: 1168981

Page 6 of 8

Shipyard: C & C Marine

Hull #: 023

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
Methyl butyrate	MBU	34	D	C		A	Yes	1		
Methyl ethyl ketone	MEK	18 <sup>2</sup>	D	C		A	Yes	1		
Methyl heptyl ketone	MHK	18	D	D		A	Yes	1		
Methyl isobutyl ketone	MIK	18 <sup>2</sup>	D	C		A	Yes	1		
Methyl naphthalene (molten)	MNA	32	D	E		A	Yes	1		
Mineral spirits	MNS	33	D	D		A	Yes	1		
Myrcene	MRE	30	D	D		A	Yes	1		
Naphtha: Heavy	NAG	33	D	#		A	Yes	1		
Naphtha: Petroleum	PTN	33	D	#		A	Yes	1		
Naphtha: Solvent	NSV	33	D	D		A	Yes	1		
Naphtha: Stoddard solvent	NSS	33	D	D		A	Yes	1		
Naphtha: Varnish makers and painters (75%)	NVM	33	D	C		A	Yes	1		
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		A	Yes	1		
Nonene (all isomers)	NON	30	D	D		A	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 <sup>2</sup>	D	E		A	Yes	1		
Nonyl phenol	NNP	21	D	E		A	Yes	1		
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		A	Yes	1		
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	C		A	Yes	1		
Octanoic acid (all isomers)	OAY	4	D	E		A	Yes	1		
Octanol (all isomers)	OCX	20 <sup>2</sup>	D	E		A	Yes	1		
Octene (all isomers)	OTX	30	D	C		A	Yes	2		
Oil, fuel: No. 2	OTW	33	D	D/E		A	Yes	1		
Oil, fuel: No. 2-D	OTD	33	D	D		A	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		A	Yes	1		
Oil, fuel: No. 5	OFV	33	D	D/E		A	Yes	1		
Oil, fuel: No. 6	OSX	33	D	E		A	Yes	1		
Oil, misc: Crude	OIL	33	D	C/D		A	Yes	1		
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1		
Oil, misc: Gas, high pour	OGP	33	D	E		A	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1		
Oil, misc: Residual	ORL	33	D	E		A	Yes	1		
Oil, misc: Turbine	OTB	33	D	E		A	Yes	1		
Pentane (all isomers)	PTY	31	D	A		A	Yes	5		
Pentene (all isomers)	PTX	30	D	A		A	Yes	5		
n-Pentyl propionate	PPE	34	D	D		A	Yes	1		
alpha-Pinene	PIO	30	D	D		A	Yes	1		
beta-Pinene	PIP	30	D	D		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	E		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		A	Yes	1		
Polybutene	PLB	30	D	E		A	Yes	1		
Polypropylene glycol	PGC	40	D	E		A	Yes	1		
iso-Propyl acetate	IAC	34	D	C		A	Yes	1		
n-Propyl acetate	PAT	34	D	C		A	Yes	1		
iso-Propyl alcohol	IPA	20 <sup>2</sup>	D	C		A	Yes	1		
n-Propyl alcohol	PAL	20 <sup>2</sup>	D	C		A	Yes	1		
Propylbenzene (all isomers)	PBY	32	D	D		A	Yes	1		
iso-Propylcyclohexane	IPX	31	D	D		A	Yes	1		
Propylene glycol	PPG	20 <sup>2</sup>	D	E		A	Yes	1		

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**  
Official #: 1168981

Page 5 of 8

Shipyard: C & C Marine  
Hull #: 023

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of	Insp. Period
							App'd (Y or N)	VCS Category		
Ethyl acetate	ETA	34	D	C		A	Yes	1		
Ethyl acetoacetate	EAA	34	D	E		A	Yes	1		
Ethyl alcohol	EAL	20 <sup>2</sup>	D	C		A	Yes	1		
Ethylbenzene	ETB	32	D	C		A	Yes	1		
Ethyl butanol	EBT	20	D	D		A	Yes	1		
Ethyl tert-butyl ether	EBE	41	D	C		A	Yes	1		
Ethyl butyrate	EBR	34	D	D		A	Yes	1		
Ethyl cyclohexane	ECY	31	D	D		A	Yes	1		
Ethylene glycol	EGL	20 <sup>2</sup>	D	E		A	Yes	1		
Ethylene glycol butyl ether acetate	EMA	34	D	E		A	Yes	1		
Ethylene glycol diacetate	EGY	34	D	E		A	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	E		A	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		A	Yes	1		
2-Ethylhexanol	EHX	20	D	E		A	Yes	1		
Ethyl propionate	EPR	34	D	C		A	Yes	1		
Ethyl toluene	ETE	32	D	D		A	Yes	1		
Formamide	FAM	10	D	E		A	Yes	1		
Furfuryl alcohol	FAL	20 <sup>2</sup>	D	E		A	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		A	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		A	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	C		A	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	C		A	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		A	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		A	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		A	Yes	1		
Glycerine	GCR	20 <sup>2</sup>	D	E		A	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	C		A	Yes	1		
Heptanoic acid	HEP	4	D	E		A	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		A	Yes	1		
Heptene (all isomers)	HPX	30	D	C		A	Yes	2		
Heptyl acetate	HPE	34	D	E		A	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 <sup>2</sup>	D	B/C		A	Yes	1		
Hexanoic acid	HXO	4	D	E		A	Yes	1		
Hexanol	HXN	20	D	D		A	Yes	1		
Hexene (all isomers)	HEX	30	D	C		A	Yes	2		
Hexylene glycol	HXG	20	D	E		A	Yes	1		
Isophorone	IPH	18 <sup>2</sup>	D	E		A	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		A	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		A	Yes	1		
Kerosene	KRS	33	D	D		A	Yes	1		
Methyl acetate	MTT	34	D	D		A	Yes	1		
Methyl alcohol	MAL	20 <sup>2</sup>	D	C		A	Yes	1		
Methylamyl acetate	MAC	34	D	D		A	Yes	1		
Methylamyl alcohol	MAA	20	D	D		A	Yes	1		
Methyl amyl ketone	MAK	18	D	D		A	Yes	1		
Methyl tert-butyl ether	MBE	41 <sup>2</sup>	D	C		A	Yes	1		
Methyl butyl ketone	MBK	18	D	C		A	Yes	1		

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: CCL 18

Shipyard: C & C Marine

Official #: 1168981

Page 4 of 8

Hull #: 023

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of	Insp. Period
							App'd (Y or N)	VCS Category		

### Subchapter D Cargoes Authorized for Vapor Control

Acetone	ACT	18 <sup>2</sup>	D	C		A	Yes	1		
Acetophenone	ACP	18	D	E		A	Yes	1		
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	1		
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		A	Yes	1		
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1		
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		A	Yes	1		
Benzyl alcohol	BAL	21	D	E		A	Yes	1		
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		A	Yes	1		
Butyl acetate (all isomers)	BAX	34	D	D		A	Yes	1		
Butyl alcohol (iso-)	IAL	20 <sup>2</sup>	D	D		A	Yes	1		
Butyl alcohol (n-)	BAN	20 <sup>2</sup>	D	D		A	Yes	1		
Butyl alcohol (sec-)	BAS	20 <sup>2</sup>	D	C		A	Yes	1		
Butyl alcohol (tert-)	BAT		D	C		A	Yes	1		
Butyl benzyl phthalate	BPH	34	D	E		A	Yes	1		
Butyl toluene	BUE	32	D	D		A	Yes	1		
Caprolactam solutions	CLS	22	D	E		A	Yes	1		
Cyclohexane	CHX	31	D	C		A	Yes	1		
Cyclohexanol	CHN	20	D	E		A	Yes	1		
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2		
p-Cymene	CMP	32	D	D		A	Yes	1		
iso-Decaldehyde	IDA	19	D	E		A	Yes	1		
n-Decaldehyde	DAL	19	D	E		A	Yes	1		
Decene	DCE	30	D	D		A	Yes	1		
Decyl alcohol (all isomers)	DAX	20 <sup>2</sup>	D	E		A	Yes	1		
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		A	Yes	1		
Diacetone alcohol	DAA	20 <sup>2</sup>	D	D		A	Yes	1		
ortho-Dibutyl phthalate	DPA	34	D	E		A	Yes	1		
Diethylbenzene	DEB	32	D	D		A	Yes	1		
Diethylene glycol	DEG	40 <sup>2</sup>	D	E		A	Yes	1		
Diisobutylene	DBL	30	D	C		A	Yes	1		
Diisobutyl ketone	DIK	18	D	D		A	Yes	1		
Diisopropylbenzene (all isomers)	DIX	32	D	E		A	Yes	1		
Dimethyl phthalate	DTL	34	D	E		A	Yes	1		
Diocetyl phthalate	DOP	34	D	E		A	Yes	1		
Dipentene	DPN	30	D	D		A	Yes	1		
Diphenyl	DIL	32	D	D/E		A	Yes	1		
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		A	Yes	1		
Diphenyl ether	DPE	41	D	{E}		A	Yes	1		
Dipropylene glycol	DPG	40	D	E		A	Yes	1		
Distillates: Flashed feed stocks	DFF	33	D	E		A	Yes	1		
Distillates: Straight run	DSR	33	D	E		A	Yes	1		
Dodecene (all isomers)	DOZ	30	D	D		A	Yes	1		
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		A	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		A	Yes	1		
Ethoxy triglycol (crude)	ETG	40	D	E		A	Yes	1		

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**  
Official #: 1168981

Page 3 of 8

Shipyard: C & C Marine  
Hull #: 023

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of	Insp. Period
							App'd (Y or N)	VCS Category		
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Mesityl oxide	MSO	18 <sup>2</sup>	O	D	III	A	Yes	1	No	G
Methyl acrylate	MAM	14	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Methylcyclopentadiene dimer	MCK	30	O	C	III	A	Yes	1	No	G
Methyl diethanolamine	MDE	8	O	E	III	A	Yes	1	.56-1(b), (c)	G
2-Methyl-5-ethylpyridine	MEP	9	O	E	III	A	Yes	1	.55-1(e)	G
Methyl methacrylate	MMM	14	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	O	D	III	A	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Morpholine	MPL	7 <sup>2</sup>	O	D	III	A	Yes	1	.55-1(c)	G
Nitroethane	NTE	42	O	D	II	A	No	N/A	.50-81, .56-1(b)	G
1- or 2-Nitropropane	NPM	42	O	D	III	A	Yes	1	.50-81	G
Pentachloroethane	PCE	36	O	NA	III	A	No	N/A	No	G
1,3-Pentadiene	PDE	30	O	A	III	A	No	N/A	.50-70(a), .50-81	G
Perchloroethylene	PER	36	O	NA	III	A	No	N/A	No	G
Polyethylene polyamines	PEB	7 <sup>2</sup>	O	E	III	A	Yes	1	.55-1(e)	G
iso-Propanolamine	MPA	8	O	E	III	A	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	O	E	III	A	Yes	1	.56-1(b), (c)	G
iso-Propylamine	IPP	7	O	A	II	A	Yes	5	.55-1(c)	G
Pyridine	PRD	9	O	C	III	A	Yes	1	.55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		O		III	A	No	N/A	.50-73, .55-1(f)	G
Sodium aluminate solution (45% or less)	SAU	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)	G
Sodium chlorate solution (50% or less)	SDD	0 <sup>1,2</sup>	O	NA	III	A	No	N/A	.50-73	G
Sodium hypochlorite solution (20% or less)	SHQ	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b)	G
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 <sup>1,2</sup>	O	NA	III	A	Yes	1	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 <sup>1,2</sup>	O	NA	III	A	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 <sup>1,2</sup>	O	NA	II	A	No	N/A	.50-73, .55-1(b)	G
Styrene (crude)	STX		O	D	III	A	Yes	2	No	G
Styrene monomer	STY	30	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
1,1,2,2-Tetrachloroethane	TEC	36	O	NA	III	A	No	N/A	No	G
Tetraethylenepentamine	TTP	7	O	E	III	A	Yes	1	.55-1(c)	G
Tetrahydrofuran	THF	41	O	C	III	A	Yes	1	.50-70(b)	G
Toluenediamine	TDA	9	O	E	II	A	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G
1,2,4-Trichlorobenzene	TCB	36	O	E	III	A	Yes	1	No	G
1,1,2-Trichloroethane	TCM	36	O	NA	III	A	Yes	1	.50-73, .56-1(a)	G
Trichloroethylene	TCL	36 <sup>2</sup>	O	NA	III	A	Yes	1	No	G
1,2,3-Trichloropropane	TCN	36	O	E	II	A	Yes	3	.50-73, .56-1(a)	G
Triethanolamine	TEA	8 <sup>2</sup>	O	E	III	A	Yes	1	.55-1(b)	G
Triethylamine	TEN	7	O	C	II	A	Yes	3	.55-1(e)	G
Triethylenetetramine	TET	7 <sup>2</sup>	O	E	III	A	Yes	1	.55-1(b)	G
Triphenylborane (10% or less), caustic soda solution	TPB	5	O	NA	III	A	No	N/A	.56-1(a), (b), (c)	G
Trisodium phosphate solution	TSP	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c)	G
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	O	NA	III	A	No	N/A	.56-1(b)	G
Vanillin black liquor (free alkali content, 3% or more).	VBL	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Vinyl acetate	VAM	13	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Vinyl neodecanate	VND	13	O	E	III	A	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyltoluene	VNT	13	O	D	III	A	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (g)	G

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**  
Official #: 1168981

Page 2 of 8

Shipyard: C & C Marine  
Hull #: 023

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of	Insp. Period
							App'd (Y or N)	VCS Category		
iso-Decyl acrylate	IAI	14	O	E	III	A	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G
Dichlorobenzene (all isomers)	DBX	36	O	E	III	A	Yes	3	.56-1(a), (b)	G
1,1-Dichloroethane	DCH	36	O	C	III	A	Yes	1	No	G
2,2'-Dichloroethyl ether	DEE	41	O	D	II	A	Yes	1	.55-1(f)	G
Dichloromethane	DCM	36	O	NA	III	A	Yes	5	No	G
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	O	E	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 <sup>1,2</sup>	O	A	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 <sup>2</sup>	O	E	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
1,1-Dichloropropane	DPB	36	O	C	III	A	Yes	3	No	G
1,2-Dichloropropane	DPP	36	O	C	III	A	Yes	3	No	G
1,3-Dichloropropane	DPC	36	O	C	III	A	Yes	3	No	G
1,3-Dichloropropene	DPU	15	O	D	II	A	Yes	4	No	G
Dichloropropene, Dichloropropane mixtures	DMX	15	O	C	II	A	Yes	1	No	G
Diethanolamine	DEA	8	O	E	III	A	Yes	1	.55-1(c)	G
Diethylamine	DEN	7	O	C	III	A	Yes	3	.55-1(c)	G
Diethylenetriamine	DET	7 <sup>2</sup>	O	E	III	A	Yes	1	.55-1(c)	G
Diisobutylamine	DBU	7	O	D	III	A	Yes	3	.55-1(c)	G
Diisopropanolamine	DIP	8	O	E	III	A	Yes	1	.55-1(c)	G
Diisopropylamine	DIA	7	O	C	II	A	Yes	3	.55-1(c)	G
N,N-Dimethylacetamide	DAC	10	O	E	III	A	Yes	3	.56-1(b)	G
Dimethylethanolamine	DMB	8	O	D	III	A	Yes	1	.56-1(b), (c)	G
Dimethylformamide	DMF	10	O	D	III	A	Yes	1	.55-1(e)	G
Di-n-propylamine	DNA	7	O	C	II	A	Yes	3	.55-1(c)	G
Dodecyl dimethylamine, Tetradecyldimethylamine mixture	DOT	7	O	E	III	A	No	N/A	.56-1(b)	G
Dodecyl diphenyl ether disulfonate solution	DOS	43	O	#	II	A	No	N/A	No	G
EE Glycol Ether Mixture	EEG	40	O	D	III	A	No	N/A	No	G
Ethanolamine	MEA	8	O	E	III	A	Yes	1	.55-1(c)	G
Ethyl acrylate	EAC	14	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethylamine solution (72% or less)	EAN	7	O	A	II	A	No	N/A	.55-1(b)	G
N-Ethylbutylamine	EBA	7	O	D	III	A	Yes	3	.55-1(b)	G
N-Ethylcyclohexylamine	ECC	7	O	D	III	A	Yes	1	.55-1(b)	G
Ethylene cyanohydrin	ETC	20	O	E	III	A	Yes	1	No	G
Ethylenediamine	EDA	7 <sup>2</sup>	O	D	III	A	Yes	1	.55-1(c)	G
Ethylene dichloride	EDC	36 <sup>2</sup>	O	C	III	A	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	O	E	III	A	No	N/A	No	G
Ethylene glycol monoalkyl ethers	EGC	40	O	D/E	III	A	Yes	1	No	G
Ethylene glycol propyl ether	EGP	40	O	E	III	A	Yes	1	No	G
2-Ethylhexyl acrylate	EAI	14	O	E	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethyl methacrylate	ETM	14	O	D/E	III	A	Yes	2	.50-70(a)	G
2-Ethyl-3-propylacrolein	EPA	19 <sup>2</sup>	O	E	III	A	Yes	1	No	G
Formaldehyde solution (37% to 50%)	FMS	19 <sup>2</sup>	O	D/E	III	A	Yes	1	.55-1(h)	G
Furfural	FFA	19	O	D	III	A	Yes	1	.55-1(h)	G
Glutaraldehyde solution (50% or less)	GTA	19	O	NA	III	A	No	N/A	No	G
Hexamethylenediamine solution	HMC	7	O	E	III	A	Yes	1	.55-1(c)	G
Hexamethyleneimine	HMI	7	O	C	II	A	Yes	1	.56-1(b), (c)	G
Hydrocarbon 5-9	HFN		O	C	III	A	Yes	1	.50-70(a), .50-81(a), (b)	G
Isoprene	IPR	30	O	A	III	A	No	N/A	.50-70(a), .50-81(a), (b)	G
Isoprene, Pentadiene mixture	IPN		O	B	III	A	No	N/A	.50-70(a), .55-1(c)	G

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*



# Certificate of Inspection

## Cargo Authority Attachment

Vessel Name: **CCL 18**

Official #: 1168981

Shipyard: C & C Marine

Hull #: 023

### 46 CFR 151 Tank Group Characteristics

Tank Group Information		Cargo Identification			Hull Type	Tanks			Cargo Transfer		Environmental Control		Fire Protection Provided	Special Requirements				
Tnk Grp	Tanks in Group	Density	Press.	Temp.		Type	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space		General	Materials of Construction	Elec Haz	Temp Cont	
A	#1C, #2C, #3C	15	Atmos.	Amb.	I	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	40-1(f)(1), .50-60, .50-70(a), .50-70(b), .50-73,	55-1(b), (c), (e), (f), (h), (i), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	No

- Notes:
- Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.
  - Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
  - Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

### List of Authorized Cargoes

Cargo Identification							Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period	
							App'd (Y or N)	VCS Category			

#### Authorized Subchapter O Cargoes

Acetonitrile	ATN	37	O	C	III	A	Yes	3	No	G
Acrylonitrile	ACN	15 <sup>2</sup>	O	C	II	A	Yes	4	.50-70(a), .55-1(e)	G
Adiponitrile	ADN	37	O	E	II	A	Yes	1	No	G
Alkyl(C7-C9) nitrates	AKN	34 <sup>2</sup>	O	NA	III	A	No	N/A	.50-81, .50-86	G
Aminoethylethanolamine	AEE	8	O	E	III	A	Yes	1	.55-1(b)	G
Ammonium bisulfite solution (70% or less)	ABX	43 <sup>2</sup>	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)	G
Ammonium hydroxide (28% or less NH3)	AMH	6	O	NA	III	A	No	N/A	.56-1(a), (b), (c), (f), (g)	G
Anthracene oil (Coal tar fraction)	AHO	33	O	NA	II	A	No	N/A	No	G
Benzene	BNZ	32	O	C	III	A	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 <sup>2</sup>	O	C	III	A	Yes	1	.50-60	G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	BHA	32 <sup>2</sup>	O	C	III	A	Yes	1	.50-60, .56-1(b), (d), (f), (g)	G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	O	B/C	III	A	Yes	1	.50-60	G
Butyl acrylate (all isomers)	BAR	14	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyl methacrylate	BMH	14	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Butyraldehyde (all isomers)	BAE	19	O	C	III	A	Yes	1	.55-1(h)	G
Camphor oil (light)	CPO	18	O	D	II	A	No	N/A	No	G
Carbon tetrachloride	CBT	36	O	NA	III	A	No	N/A	No	G
Caustic potash solution	CPS	5 <sup>2</sup>	O	NA	III	A	No	N/A	.50-73, .55-1(i)	G
Caustic soda solution	CSS	5 <sup>2</sup>	O	NA	III	A	No	N/A	.50-73, .55-1(i)	G
Chemical Oil (refined, containing phenolics)	COD	21	O	E	II	A	No	N/A	.50-73	G
Chlorobenzene	CRB	36	O	D	III	A	Yes	1	No	G
Chloroform	CRF	36	O	NA	III	A	Yes	3	No	G
Coal tar naphtha solvent	NCT	33	O	D	III	A	Yes	1	.50-73	G
Creosote	CCW	21 <sup>2</sup>	O	E	III	A	Yes	1	No	G
Cresols (all isomers)	CRS	21	O	E	III	A	Yes	1	No	G
Cresylate spent caustic	CSC	5	O	NA	III	A	No	N/A	.50-73, .55-1(b)	G
Cresylic acid tar	CRX		O	E	III	A	Yes	1	.55-1(f)	G
Crotonaldehyde	CTA	19 <sup>2</sup>	O	C	II	A	Yes	4	.55-1(h)	G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		O	C	III	A	No	N/A	No	G
Cyclohexanone	CCH	18	O	D	III	A	Yes	1	.56-1(a), (b)	G
Cyclohexanone, Cyclohexanol mixture	CYX	18 <sup>2</sup>	O	E	III	A	Yes	1	.56-1 (b)	G
Cyclohexylamine	CHA	7	O	D	III	A	Yes	1	.56-1(a), (b), (c), (g)	G
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	O	D	III	A	Yes	1	.50-60, .56-1(b)	G

\*\*\* This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. \*\*\*




# UNITED STATES OF AMERICA

DEPARTMENT OF HOMELAND SECURITY  
UNITED STATES COAST GUARD

NATIONAL VESSEL DOCUMENTATION CENTER

## CERTIFICATE OF DOCUMENTATION


VESSEL NAME CCL 18		OFFICIAL NUMBER 1168981	IMO OR OTHER NUMBER 023	YEAR COMPLETED 2005	
HAILING PORT NEW ORLEANS LA		HULL MATERIAL STEEL		MECHANICAL PROPULSION NO	
GROSS TONNAGE 735 GRT	NET TONNAGE 735 NRT	LENGTH 200.0	BREADTH 35.0	DEPTH 12.5	
PLACE BUILT BELLE CHASSE LA					
OWNERS CHEM CARRIERS LLC COMPRISED OF ONE MEMBER			OPERATIONAL ENDORSEMENTS COASTWISE		
MANAGING OWNER CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE LA 70780					
RESTRICTIONS NONE					
ENTITLEMENTS NONE					
REMARKS NONE					
ISSUE DATE OCTOBER 10, 2025		 DIRECTOR, NATIONAL VESSEL DOCUMENTATION CENTER			
THIS CERTIFICATE EXPIRES NOVEMBER 30, 2026					





# National Pollution Funds Center

- Vessel COFR Search
- E-COFR
- Online Enrollment
- Contact Us
- Logout
- Frequently Asked Questions
- Disclaimer
- Forms/Regulations
- NPFC Home

Click on the Document Icon  to the left of a record to display a COFR Confirmation in html. You may print the COFR Confirmation by right clicking your mouse and selecting "print" from the list.


VESSEL NAME	VESSEL TYPE	HULL TYPE	GROSS TONNAGE	COFR NUMBER	EFFECTIVE DATE	EXPIRATION DATE	COFR APPLICANT	VIN	INSURANCE CANCEL FLAG
 CCL 18	TANKBARGED		735	841310 - 21	7/1/2023	7/1/2026	CHEM CARRIERS, L.L.C	D1168981	

< Prev Next >

[USCG Home](#) • [Privacy Policy](#) • [Customer Accessibility](#)

Contact the [Accessibility Coordinator](#) for comments and inquiries about accessibility.

Version 3.7 -- This version is designed for Internet Explorer; Edge, Chrome, Firefox and Safari.



BARGE PIPING TEST LETTER

INSTRUCTIONS: FILL OUT COMPLETELY. WRITE "N/A" ON ANY NON-APPLICABLE LINE.

BARGE NAME / NUMBER: CCL18

Last Hydro Test Date (188 PSI) 12/22/2025
(USCG Required Twice a year in five years)

Note: Test Results are valid for (1) One year from date of test!

Letter of Expiration Date (one year from test): 12/22/25

1. Cargo Piping and Valves (Date of test): 12/22/21

Annual Test Pressure (125 psi): 125 PSI

2. Cargo Relief Valve (Date of test): 12/22/25

Annual Test Pressure (125 psi): 125 PSI

3. Cargo Pressure Gauge (Date of test): 12/22/21

Annual percent of Accuracy (%): 96%

4. Steam Piping and Relief Valves (Date of test): 12/22/25

Annual Test Pressure (125 psi): 125 PSI

Signature: [Handwritten Signature]



# WESTPORT MARINE SHIPYARD LLC.

## VAPOR TIGHTNESS TEST

Note: Test Result are valid for (1) one year from date of test

Vessel Name: CCL 18 Test Date: 12/22/25  
 Testing Location: WESTPORT CRANESHIPYARD Maximum Load Rate: (BPH) 0500  
 Tanks Tested: ALL WAGO TANKS Pressure Indicator: 0.25T. GAUGE

### TEST RESULTS

Test Duration: 30 minutes Beginning Pressure: 28.0 Inches H2O  
 Ending Pressure: 27.1 Inches H2O  
 Total Pressure Loss: .9 Inches H2O  
 Allowable Pressure Loss: 2.92 Inches H2O

Barge is Vapor Tight if "Total Pressure Loss" is Less than "Allowable Pressure Loss"

This vessel has been tested in accordance with section 61.304F and has been found to be vapor tight.

CHRISTINA SHILLINEY  
 Tester (Print)  
[Signature]  
 Tester (Signature)


ANAND RAMANURTHY  
 Witness: (Print)  
[Signature]  
 Witness: (Signature)

WESTPORT CRANESHIPYARD  
 Affiliation of Witness:

- (P1) - Beginning Pressure
- (P2) - Ending Pressure
- (Delta P) - Total Pressure Loss
- (Delta PM) - Allowable Pressure Loss
- (TP) - 14.7 plus Barge Test Pressure in PSI
- (L) - Maximum Load Rate in BPH
- (V) - Volume of Tank (s)
- (Delta T) = Test Duration
- 0.861 - PIA @ (P1)

$$0.861 \times \frac{15.7}{(TP)} \times \left( \frac{0500}{(L)} \right) \times \left( \frac{30,000}{(V)} \right) = \frac{2.92}{(Delta PM)}$$


# CCL 18 Piping Diagram



- A = Access Hatch
- E = Engine
- P = Pump
- D.H. = Discharge Header
- B = Transverse Header Valves
- C = Pump Discharge Valve
- D = No. 1 Suction Valve
- E = No. 2 Suction Valve
- F = No. 3 Suction Valve
- G = Discharge Valve
- H = High Velocity PV VALVE
- I = VAPOR LINE Butterfly Valves (Port & starbd.)
- ES = EMERGENCY ShutDown
- J = High level Plug-in High level Shut-Down Plugs
- K = High level Shut-Down High level alarms
- L = High level sticks
- M = Cargo Tank Sight Glasses
- N = VAPOR STACK Butterfly valve

VS = Vent stack

## CCL 18 Cargo & Vapor Piping



Parts List

ITEM	QTY	NAME	ITEM	QTY	NAME	ITEM	QTY	NAME
1	2	Vapor Header Valve	7	1	Master Suction Valve	13	1	Pump Engine
2	2	Cargo Header Valve	8	1	No. 1 Cargo Tank Valve	14	1	High Velocity PV Valve
3	1	Drop Valve / Load Valve	9	1	No. 2 Cargo Tank Valve	15	1	Emergency Shutdown
4	1	Pressure Release Valve	10	1	No. 3 Cargo Tank Valve			
5	1	Pump Discharge Check Valve	11	1	Vent Stack Valve			
6	1	Pump Discharge Valve	12	1	Deep Well Pump			

Edited 07/13/2020

# CARGO TRANSFER PROCEDURES

*Chem Carriers LLC*

## TRANSFER FROM BARGE TO DOCK

### PARTS

1. PRODUCTS TRANSFERRED
2. DESCRIPTION OF SYSTEM
3. PERSONS ON DUTY
4. PERSONS IN CHARGE
5. EMERGENCY SHUTDOWN
6. TOPPING OFF PROCEDURE
7. COMPLETION OF TRANSFER
8. REPORTING CARGO SPILLS
9. VESSEL CLOSURES
10. PRODUCT DATA
11. Vapor Control Procedures  
Barge CCL 18

### PARTS 1. PRODUCTS TRANSFERRED

33 CFR 155.750 (a) (1) (i)

This vessel is certificated for the carriage of grades "A" and lower Sub-Chapter (D) and (O) Products. It has also been certified to carry vapor products. Reference Certificate of Inspection.

### PARTS 2. DESCRIPTION OF CARGO TRANSFER SYSTEM

33 CFR 155.750 (a) (2) (i) (ii)

The cargo transfer procedures applies to all Chem Carriers LLC owned or leased tank barges. In most cases other than series built barges, the cargo piping arrangement is usually slightly different on every barge, and for this reason, the piping diagram must be studied before loading or discharging a barge. The basic concept for loading and discharging is fairly standard depending on the location of the pump.

A. (Reference the piping diagram for transfer system arrangement.)

B. PROCEDURES FOR THE CONTAINMENT SYSTEM

33 CFR 155.310 (a) (1) (iv)

33 CFR 155.750 (a) (2) (iii)

- 1). The containment pans are equipped with a drain for the removal of slops to shore facilities:

NEVER DRAIN THE CONTAINMENT TANKS ONTO THE DECK.

2). CCL 18 is equipped with a separate containment area for the cargo trunk top and the forward deck area. Each containment area is equipped with drains and scupper plugs. Plugs should be installed prior to cargo transfer and removed after the cargo transfer is complete. PIC should notify Chem Carriers LLC when containment areas need cleaning or if scupper plugs need replacing. **Never Drain Product captured in containment area overboard. Notify Olin for arrangements to drain at an approved facility.**

### **PARTS 3. PERSONS ON DUTY DURING TRANSFER**

33 CFR 155.750 (a) (3)

Number of persons required on duty during transfer operations:

- A. At no time during the transfer operation will be less than one responsible person on duty. The certified tankerman assigned shall be in charge and responsible for the safe transfer of cargo.

### **PARTS 4. PERSONS IN CHARGE**

The tanker man (person in charge) is responsible for transferring cargo and carrying out related operations on board in an efficient, safe, and pollution free manner. The tanker man whether employed by the towboat, owner, operator, a shore tanker man service, or Chem Carriers LLC, shall comply with all Coast Guard, State and local regulations. Tanker man's responsibility shall include but not be limited to the following:

- A. To have on his/her person a valid merchant marine document endorsed as tanker man, certified to handle the grade of cargo to be transferred.
- B. Make a thorough inspection of the barge prior to the start of transfer operation.
- C. To have proper connection of the grounding cable.
- D. The vessel's moorings are adequate to hold during all expected conditions of surge, current, wind, tide, ect., and lines are long enough to allow for surge, tide, wind, changes in draft ect.
- E. Proper hose sizes, lengths, support, and connections.
- F. CCL 18 requires Two B-II Fire Extinguishers.
- G. The person in charge of transfer operations on the transferring vessel or facility and the person in charge of transferring operations on the receiving vessel or facility agree to begin the transfer operations.
- H. The transfer operation between tank barges and dock facilities should be lighted between sunset and sunrise to comply with the U. S. Coast Guard regulation pertaining to the displaying of lights on barges as required by Title 33.
- I. The PIC (PERSON IN CHARGE) will be responsible for the DOI (declaration of inspection) and DOS (declaration of security).

**PARTS 5:                    EMERGENCY SHUTDOWN**

33 CFR 155.750 (a) (6)

THE EMERGENCY SHUTDOWN IS LOCATED NEAR THE CENTER OF THE BARGE.

- A. In the event of an emergency, transfer operations can be stopped by pulling the remote shutdown cable.
- B. Familiarize yourself with its location and operation prior to transfer.
- C. Always maintain communications with dock or shore personnel.

**PARTS 6;                    TOPPING OFF PROCEDURES**

33 CFR 155.750 (a) (7)

In the process of topping off, tanks should be loaded at different levels to top off one at a time. Extra care should be taken to avoid over pressuring the connections, and hoses by closing valves against the receiving line. Since barges and facilities vary in their systems, no standard for topping off exist, but the following should be considered:

- A. The closing of one tank increases the rate of flow to other tanks on the same line.
- B. Always consider temperature and cargo in accordance with the amount of expansion that should be allowed.
- C. Always maintain communications with dock or shore personnel.
- D. A set of dipstick overfill devices have been installed on the CCL 18. Dipsticks can be made operational by releasing the covers or caps. Dipsticks should be used as a visual aid for overfill protection.

**PARTS 7:                    COMPLETION OF TRANSFER**

33 CFR 155.750 (a) (8)

Upon the completion of the transfer all pipelines should be drained into cargo tanks. The header valve used during the operation should than be closed, sealed off with a blind flange and shore personnel should seal lines and hatches on vessel.

**PARTS 8:                    REPORTING CARGO SPILLS**

33 CFR 155.750 (a) (9)

Should an accidental discharge of product occur, you should consider the following:

- A. Locate the source of the spill and try to stop it, if possible, and safe to do so.

- B. Make an attempt to contain the product if possible.
- C. Notify the Coast Guard. The national Response Center at 1-800-424-8802.
- D. Notify Chem Carriers LLC at 225-642-0060.
- E. If loading, transfer the cargo from the leaking tank to an adjacent tank or back to the dock if safe to do so.
- E. If discharging, pump the product from the leaking tank as quickly as possible if safe to do so.

**\*When reporting a spill, the tankerman should provide the following information:**

- A. Name (his or her)
- B. Name of Company: (employed by; (contracted by;
- C. Name of Barge.
- D. Spill Location
- E. Specify Product.
- F. Estimate Quantity of Spill.
- G. Weather, Tide, Sea and Current Conditions.
- H. Cause of Spill.
- I. Action Being Taken to Contain and Stop Spill.

## **PART 9**

### **CLOSURES ON VESSELS**

Upon completion of Cargo transfer operations, all tank hatch covers, ullage covers, and gauging device covers shall be dogged down and secured. All drain valves should be closed, and drip pan covers, should be made up tight. Covers for void spaces, bow and stern compartments shall be secured at all times and checked for tightness. Closing devices on clean-out hatches and clean-out opening should be checked, especially when the barge is loaded.

## **PART 10**

### **PRODUCT DATA**

See specific MSDS sheets provided with these procedures.

Incase of any other emergency, immediately shut down and notify the transferring facility, and Chem Carriers LLC at 225-642-0060 24 Hour Line.

## **PART 11**

### **VAPOR CONTROL PROCEDURES**

This is a guide only and is not intended to replace experience, sound judgment, and a proper assessment of the task at hand.

The tankerman on duty is the acting Designated Person In Charge (PIC) and is responsible for cargo transfer operations and carrying out related operations on barges.

1. Vapor Recovery Transfer Maximum Rate is 2300 BBLs/HR for subchapter "D" Cargoes and 2400 BBBLs/Hr for subchapter

"O" Cargoes.

- 1.1 Transfer rates, which exceed these maximums, must be approved by Chem Carriers LLC.
- 1.2 Transfer rates for each cargo tank should not exceed the maximum transfer rate.

## **2. Pre-transfer Inspection For Vapor Recovery Operations**

2.1 Follow the procedures outlined below in addition to the procedures utilized during normal transfers:

2.1.1 Wear personal protective equipment (PPE) as needed for the cargo in the barge when testing P/V and, hooking up hoses, or draining low points.

2.1.2 Ensure that a Certificate of Vapor Tightness is onboard and valid.

2.1.3 Close the low point drain located about midway on the vapor header .

2.1.4 Close the low point drain near the vent stack.

2.1.5 Open Vapor Stack valve to the vent riser prior to discharging cargo.

2.1.7 Blinds used for the vapor control manifold should have a hole to accommodate the ½" stud located in the vapor header.

2.1.8 Each cargo tank is fitted with a liquid level gauge stick. Remove the cap, raise the stick, This stick can be monitored visually to avoid overfilling.

2.1.9 Ensure that the last one meter (3.3 feet) of vapor piping before the vapor connection is painted red/yellow/red.

2.1.10 The cross-header should be stenciled with the word "VAPOR" in black letters at least 2'' high.

2.1.11 The vapor connection flange should be fixed with a 1" long by 1/2" diameter stud projecting outward from the face of the flange, midway between bolt holes.

2.1.12 The high level alarms/shutdowns are installed near the center of each cargo tank. Dock alarm/shutdown should be connected prior to loading, and plugs located near the forward end of the barge Port and Starboard should be labeled "ALARM/SHUTDOWN SENSOR." High level alarms are set to alarm at 90% of the cargo tanks capacity and Shut downs are set to shut transfer down at 95% of each tanks capacity.

2.1.13 Ensure that the P/V relief valve flame screen, if required, is in place and in good condition prior to testing.

2.1.14 Ensure that the facility has a Letter of Adequacy endorsed as meeting the requirements of 33 CFR Subpart E.

### 3. Vapor Piping

3.1 The PIC checks the vapor piping diagram.

3.2 Characteristics of a vapor header:

3.2.1 The vapor collection piping system on tank barges is permanently installed and located as close as practical to the loading manifold. The piping system is electrically bonded to the hull and electrically continuous.

3.2.2 The last one meter (3.3 feet) of vapor piping prior to the valve before the vapor connection is painted red/yellow/red. The red bands are 4" wide and the yellow band is 32" wide.

3.2.3 The vapor header is stenciled with the word "VAPOR" in black letters at least 2" high.

3.2.4 The vapor connection flange is to be fixed with a 1" by 1/2" diameter stud projecting outward from the face of the flange. This stud is located at the top of the flange, midway between bolt holes.

3.2.5 When not in use, blank off the vapor headers using a blind flange with a bolt in every hole. Each blind flange used on the vapor piping has a hole drilled to accommodate the pin.

4. Inspection And Verification Of Vent Lines

4.1 The Person in Charge performs the following steps:

4.1.1 Checks the Certificate of Inspection on board the barge;

4.1.2 Locates polymerizing or inhibited cargoes in the section of the COI marked *Specific Hazardous Cargo Authority*;

4.1.3 Refers to the MSDS or Chemical Data Guide on board the vessel to determine what cargoes are subject to polymerization, or what cargoes are inhibited;

4.1.4 Locates the MSDS for the cargo and determines its toxicity and whether or not it is a polymerizing or inhibited cargo; and,

4.1.5 Notifies the Dispatcher and Field Supervisor when polymerization is suspected.

5. Any problems with the Vapor Control system must be reported immediately to the person in charge and Chem Carriers LLC.

U.S. Department of  
Homeland Security

United States  
Coast Guard



Commanding Officer  
United States Coast Guard  
Marine Safety Center

2100 2nd Street, S.W.  
Washington, DC 20593-0001  
Staff Symbol: MSC-3  
Phone: (202) 475-3403  
Fax: (202) 475-3920  
Email: msc@uscg.mil

16710/P009758  
Serial: C1-1302040  
June 18, 2013

Chem Carriers, LLC  
Attn: Mr. Robert J. Banta, Sr.  
1237 Louisiana 75  
Sunshine, LA 70780  
Email: Robert@chemcarriers.com

Subj: CCL 18, O.N. 1168981, C&C Marine & Repair Co. Hull No. 023  
200' x 35' x 12.5' Unmanned Hull Type I/II/III Tank Barge (D/O)  
Grade A (max. 25 psia Reid) and Lower Flammable or Combustible Liquids Identified in  
46 CFR Table 30.25-1 or 46 CFR Part 153 Table 2 and Specified Hazardous Cargoes  
Design Density 8.7 lbs/gal; Maximum Density (slack load) 15.0 lbs/gal  
Rivers; Lakes, Bays, and Sounds; Limited Coastwise on unmanned fair weather voyages  
only, not more than 12 miles offshore between St. Marks and Carrabelle, Florida  
Updated: VCS List of Cargoes & Cargo Authority Attachment (CAA)

Ref: (a) MSC letter C2-0400276, dated February 4, 2004  
(b) MSC letter C1-0504038, dated March 23, 2005

Dear Mr. Banta:

We have reviewed the information in your email dated June 13, 2013 (MSC Document No. 1314069), wherein you requested an updated CAA to include VCS cargoes. The vapor control system (VCS) was originally approved by reference (a), extended to subject vessel by reference (b), and was subsequently converted to an overhead loading line system. From the information contained in your email, you indicate that the system was recently converted back to collect vapor. Therefore, we have updated the carriage authority to include VCS cargoes. The following comments apply:

1. This approval is based on our understanding that the VCS approved by reference (a) has not been altered. The Marine Safety Center must be notified of all modifications to the subject vessel which alter any plan listed in enclosure (1) of reference (a).
2. All comments provided in the original approval letter, reference (a) and plan approval extension letter, reference (b), still remain valid with the exception of the maximum vapor densities and maximum allowable loading transfer rates as listed below:
  - a. VCS Category 1- 4 cargoes that have a maximum vapor density of **0.240 lbm/ft<sup>3</sup>** and that generate a total pressure drop less than or equal to **Gasoline**. These cargoes are restricted to a maximum liquid loading rate of **2,300 bbl/hr** and a maximum discharge rate of **1,714 bbl/hr**.

16710/P009758  
Serial: C1-1302040  
June 18, 2013

Subj: CCL 18, O.N. 1168981, C&C Marine & Repair Co. Hull No. 023  
Updated: VCS List of Cargoes & Cargo Authority Attachment (CAA)

b. VCS Category 5 (high vapor growth rate) cargoes that have a maximum vapor density of **0.379 lbm/ft<sup>3</sup>** and that generate a total pressure drop less than or equal to **Pentane (all isomers)**. These cargoes are restricted to a maximum liquid loading rate of **1,600 bbl/hr** and a maximum discharge rate of **1,714 bbl/hr**.

3. The updated VCS List of Cargoes and the VCS Plan Review Information Sheet (PRIS) are included as enclosures (1) and (2). The updated Cargo Authority Attachment (CAA) for the subject vessel has been uploaded into the Coast Guard's MISLE database where it is now available to the Officer in Charge, Marine Inspections (OCMI). Only the cognizant OCMI can issue a vessel's CAA, which is valid only when referenced by and attached to a valid Certificate of Inspection (COI). The OCMI will also verify the carriage authority and vapor control tank group characteristics we used to create enclosures (1) and (2) are consistent with the vessel's actual construction.

Our Project Number for this vessel is **P009758**. Please ensure that future correspondence includes the Project Number, and the vessels official number.

If you have any questions concerning our review, please contact Lieutenant Rachel Beckmann at the number above.

Sincerely,



M. J. SEXTON  
Lieutenant, U. S. Coast Guard  
Assistant Chief, Tank Vessel and Offshore Division  
By direction

Encl: (1) VCS List of Cargoes; CCL 18, O.N. 1168981, C&C MARINE & REPAIR Hull No. 023, dated June 18, 2013  
(2) VCS PRIS; CCL 18, O.N. 1168981, C&C MARINE & REPAIR Hull No. 023, dated June 18, 2013

Copy: Commanding Officer, Coast Guard Marine Safety Unit Baton Rouge, w/ enclosures

U.S. Department of  
Homeland Security

United States  
Coast Guard



Commandant  
United States Coast Guard

2703 Martin Luther King Jr. Ave SE  
Stop 7516  
Washington, DC 20593-7516  
Staff Symbol: CG-MER-4 (VRP)  
Phone: (202) 372-1005  
Fax: (202) 372-8376  
Email: vrp@uscg.mil

16460  
March 12, 2025

Chem Carriers, L.L.C.  
C/O: FOREFRONT EMERGENCY MANAGEMENT, LP  
ATTN: ALLIE MARTIN  
1730 COTEAU ROAD  
HOUMA, LA 70364

Dear Sir or Madam:

Your Vessel Response Plan (Control Number 56041), submitted to meet the requirements of Title 33, Code of Federal Regulations (CFR), Part 155, Subparts D and I, is **approved**. Approval will remain valid until **March 21, 2030**.

The CCL 18 (1168981) is authorized to operate only in the ports or geographic areas indicated in the Captain of the Port zones listed below. If carrying oil as cargo, the vessel is prohibited from handling, storing, transporting, transferring, or lightering oil unless it is operating in full compliance with this plan. Compliance includes ensuring that required resources have been identified and planned for or are in place and available through contract or other approved means. If applicable to your routes, this includes the dispersant and aerial observation requirements of 33 CFR 155.1050.

You are reminded that your chosen salvage and marine firefighting resource provider may have submitted waivers from meeting one or more of the specified response times in accordance with 33 CFR 155.4055. If so, this may be rescinded by the U.S. Coast Guard if the appropriate response resources are not available when the approved waiver expires. You shall continue to assess the adequacy of your chosen salvors and firefighters as required by 33 CFR 155.4050.

The vessel must keep a copy of this approval letter onboard in addition to the minimum sections of the plan as required by 33 CFR 155.1030. In accordance with 33 CFR 155.1070, you are required to review your plan annually and submit plan amendments for approval. As per 33 CFR 155.1070(b), the entire plan must be resubmitted for a comprehensive review and approval six (6) months prior to the expiration date.

**APPROVED CAPTAIN OF THE PORT ZONES**

CORPUS CHRISTI  
HOUMA  
HOUSTON-GALVESTON

LOWER MISSISSIPPI RIVER OHIO VALLEY  
(MEMPHIS) PORT ARTHUR AND LAKE  
MOBILE CHARLES  
NEW ORLEANS

UPPER MISSISSIPPI RIVER  
(ST. LOUIS)

Sincerely,



CHARRON MCCOMBS

Lieutenant Commander

Acting Chief, Domestic Preparedness & Planning Division

U.S. Coast Guard

By direction

U.S. Department of  
Homeland Security

United States  
Coast Guard



Commanding Officer  
United States Coast Guard  
Marine Safety Center

US Coast Guard Stop 7430  
2703 Martin Luther King Jr. Ave. SE  
Washington, DC 20593-7430  
Staff Symbol: MSC-5  
Phone: (202) 795-6729  
Email: securityplaninfo@uscg.mil

16710  
VS-326893  
December 3, 2024

Chem Carriers, LLC  
Attn: Robert Banta  
1237 Hwy 75  
Sunshine, LA 70780  
robert@chemcarriers.com

Subj: CHEM CARRIERS, LLC VESSELS  
VESSEL SECURITY PLAN APPROVAL WITH AMENDMENTS

Ref: (a) Your correspondence dated November 6, 2024  
(b) Title 33 Code of Federal Regulations (CFR) Part 104  
(c) MSC Vessel Security Plan Approval letter dated October 16, 2024

Dear Mr. Banta:

We have conducted a review of the Vessel Security Plan (VSP) submitted with reference (a) in accordance with reference (b) and it is **“Approved.”**

Your vessel must operate in compliance with this approved VSP and the requirements contained in reference (b). You are reminded to immediately report any deviation from this approved plan to the local Captain of the Port (COTP)/Officer in Charge, Marine Inspection (OCMI).

This approval will remain valid until five years from the date of reference (c) unless rescinded in writing by the local COTP/OCMI. You must review your plan annually and submit any amendments to this office for approval. Please ensure that a copy of the VSP is maintained on board the vessel if manned, or, if unmanned, at a suitable secure location so that it is readily available during an emergency or security incident. You shall make available to the Coast Guard, upon request, this letter, the VSP and any information related to the implementation of the VSP. Our Case Number for this plan is 326893. Please ensure that all future correspondence includes this Case Number.

Sincerely,

K. C. WILLIAMS  
Lieutenant Commander, U.S. Coast Guard  
Chief, Vessel Security Division  
By direction

Enclosures: (1) List of Vessel Security Plan Amendments  
(2) List of Vessels Covered

**List of Vessels Covered**

<u>Vessel Name</u>	<u>Official Number (O.N.)</u>
CCL-1	518612
CCL 2	510107
CCL-3	296363
CCL 4	512519
CCL-5	512520
CCL-6	530996
CCL7	551980
CCL 8	551982
CCL 9	551983
CCL 10	551979
CCL 11	551976
CCL 14	1164451
CCL 15	1164452
CCL 16	1164666
CCL 17	1166179
CCL 18	1168981
CCL 19	1168980
CCL 20	1191598
CCL 21	1191599
CCL 22	1191600
CCL 23	1191601
CCL 24	1196547
CCL 25	1196548
CCL 26	1203816
CCL 27	1203817
CCL 28	1212828
CCL 29	1212829
CCL 30	1305871
CCL 31	1305870
CCL 32	1305869
CCL 33	1305868
CCL 401	1216671
CCL 402	1219910
CCL 403	1231311
CCL 404	1231312
CCL 405	1236867
CCL 406	1236866
CCL 407	1246320
CCL 408	1246097
CCL 409	1246098
CCL 410	1255906
CCL 411	1255907
CCL 414-L	1262941
CCL 415-T	1262942

<u>Vessel Name</u>	<u>Official Number (O.N.)</u>
CCL 416-T	1264691
CCL 417 T	1298307
CCL 418-L	1306896
CCL 419-L	1306897
CCL 420-T	1348560
CCL 421-T	CG1843359
CCL 3202	1089031
HFL 413	1237482
HFL 415	1237483
HFL 435	1236563
HFL 605	1237484

**BARGE "CCL 18"  
HULL NO. 023**

**TANK NO. 1  
INNAGE TABLE**

CAPACITIES GIVEN IN WHOLE GALLONS

OFFICIAL NUMBER 1168981

GAUGE HEIGHT 16' 02 3/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	209	0	10,285	0	20,617	0	30,918	0	41,241	0	51,572	0	61,902	0	72,233	0	82,563	0	92,894
1/4	393	1/4	10,500	1/4	20,833	1/4	31,132	1/4	41,456	1/4	51,787	1/4	62,117	1/4	72,448	1/4	82,778	1/4	93,109
1/2	580	1/2	10,715	1/2	21,048	1/2	31,347	1/2	41,672	1/2	52,002	1/2	62,333	1/2	72,663	1/2	82,994	1/2	93,324
3/4	770	3/4	10,931	3/4	21,263	3/4	31,561	3/4	41,887	3/4	52,217	3/4	62,548	3/4	72,878	3/4	83,209	3/4	93,539
1	962	1	11,146	1	21,478	1	31,775	1	42,102	1	52,433	1	62,763	1	73,093	1	83,424	1	93,754
1/4	1,157	1/4	11,361	1/4	21,693	1/4	31,989	1/4	42,317	1/4	52,648	1/4	62,978	1/4	73,309	1/4	83,639	1/4	93,970
1/2	1,354	1/2	11,577	1/2	21,909	1/2	32,204	1/2	42,533	1/2	52,863	1/2	63,193	1/2	73,524	1/2	83,854	1/2	94,185
3/4	1,551	3/4	11,792	3/4	22,124	3/4	32,418	3/4	42,748	3/4	53,078	3/4	63,409	3/4	73,739	3/4	84,070	3/4	94,400
2	1,751	2	12,007	2	22,339	2	32,633	2	42,963	2	53,293	2	63,624	2	73,954	2	84,285	2	94,615
1/4	1,951	1/4	12,223	1/4	22,554	1/4	32,848	1/4	43,178	1/4	53,509	1/4	63,839	1/4	74,170	1/4	84,500	1/4	94,830
1/2	2,154	1/2	12,438	1/2	22,769	1/2	33,064	1/2	43,393	1/2	53,724	1/2	64,054	1/2	74,385	1/2	84,715	1/2	95,046
3/4	2,357	3/4	12,653	3/4	22,985	3/4	33,279	3/4	43,609	3/4	53,939	3/4	64,270	3/4	74,600	3/4	84,930	3/4	95,261
3	2,563	3	12,869	3	23,200	3	33,494	3	43,824	3	54,154	3	64,485	3	74,815	3	85,146	3	95,476
1/4	2,769	1/4	13,084	1/4	23,415	1/4	33,709	1/4	44,039	1/4	54,370	1/4	64,700	1/4	75,030	1/4	85,361	1/4	95,691
1/2	2,977	1/2	13,299	1/2	23,630	1/2	33,924	1/2	44,254	1/2	54,585	1/2	64,915	1/2	75,246	1/2	85,576	1/2	95,907
3/4	3,187	3/4	13,515	3/4	23,845	3/4	34,139	3/4	44,469	3/4	54,800	3/4	65,130	3/4	75,461	3/4	85,791	3/4	96,122
4	3,398	4	13,730	4	24,060	4	34,355	4	44,685	4	55,015	4	65,346	4	75,676	4	86,007	4	96,337
1/4	3,610	1/4	13,945	1/4	24,274	1/4	34,570	1/4	44,900	1/4	55,230	1/4	65,561	1/4	75,891	1/4	86,222	1/4	96,552
1/2	3,824	1/2	14,161	1/2	24,488	1/2	34,785	1/2	45,115	1/2	55,446	1/2	65,776	1/2	76,107	1/2	86,437	1/2	96,767
3/4	4,040	3/4	14,376	3/4	24,703	3/4	35,000	3/4	45,330	3/4	55,661	3/4	65,991	3/4	76,322	3/4	86,652	3/4	96,983
5	4,255	5	14,591	5	24,917	5	35,215	5	45,546	5	55,876	5	66,207	5	76,537	5	86,867	5	97,198
1/4	4,470	1/4	14,807	1/4	25,131	1/4	35,430	1/4	45,761	1/4	56,091	1/4	66,422	1/4	76,752	1/4	87,083	1/4	97,413
1/2	4,686	1/2	15,022	1/2	25,346	1/2	35,646	1/2	45,976	1/2	56,306	1/2	66,637	1/2	76,967	1/2	87,298	1/2	97,628
3/4	4,901	3/4	15,237	3/4	25,560	3/4	35,861	3/4	46,191	3/4	56,522	3/4	66,852	3/4	77,183	3/4	87,513	3/4	97,844
6	5,117	6	15,453	6	25,774	6	36,076	6	46,406	6	56,737	6	67,067	6	77,398	6	87,728	6	98,059
1/4	5,332	1/4	15,668	1/4	25,989	1/4	36,291	1/4	46,622	1/4	56,952	1/4	67,283	1/4	77,613	1/4	87,944	1/4	98,274
1/2	5,547	1/2	15,883	1/2	26,203	1/2	36,506	1/2	46,837	1/2	57,167	1/2	67,498	1/2	77,828	1/2	88,159	1/2	98,489
3/4	5,763	3/4	16,098	3/4	26,417	3/4	36,722	3/4	47,052	3/4	57,383	3/4	67,713	3/4	78,043	3/4	88,374	3/4	98,704
7	5,978	7	16,313	7	26,632	7	36,937	7	47,267	7	57,598	7	67,928	7	78,259	7	88,589	7	98,920
1/4	6,193	1/4	16,529	1/4	26,846	1/4	37,152	1/4	47,483	1/4	57,813	1/4	68,143	1/4	78,474	1/4	88,804	1/4	99,135
1/2	6,409	1/2	16,744	1/2	27,060	1/2	37,367	1/2	47,698	1/2	58,028	1/2	68,359	1/2	78,689	1/2	89,020	1/2	99,350
3/4	6,624	3/4	16,959	3/4	27,274	3/4	37,583	3/4	47,913	3/4	58,243	3/4	68,574	3/4	78,904	3/4	89,235	3/4	99,565
8	6,839	8	17,174	8	27,489	8	37,798	8	48,128	8	58,459	8	68,789	8	79,120	8	89,450	8	99,781
1/4	7,055	1/4	17,389	1/4	27,703	1/4	38,013	1/4	48,343	1/4	58,674	1/4	69,004	1/4	79,335	1/4	89,665	1/4	99,996
1/2	7,270	1/2	17,605	1/2	27,917	1/2	38,228	1/2	48,559	1/2	58,889	1/2	69,220	1/2	79,550	1/2	89,880	1/2	100,211
3/4	7,485	3/4	17,820	3/4	28,132	3/4	38,443	3/4	48,774	3/4	59,104	3/4	69,435	3/4	79,765	3/4	90,096	3/4	100,426
9	7,701	9	18,035	9	28,346	9	38,659	9	48,989	9	59,320	9	69,650	9	79,980	9	90,311	9	100,641
1/4	7,916	1/4	18,250	1/4	28,560	1/4	38,874	1/4	49,204	1/4	59,535	1/4	69,865	1/4	80,196	1/4	90,526	1/4	100,857
1/2	8,131	1/2	18,465	1/2	28,775	1/2	39,089	1/2	49,419	1/2	59,750	1/2	70,080	1/2	80,411	1/2	90,741	1/2	101,072
3/4	8,347	3/4	18,681	3/4	28,989	3/4	39,304	3/4	49,635	3/4	59,965	3/4	70,296	3/4	80,626	3/4	90,957	3/4	101,287
10	8,562	10	18,896	10	29,203	10	39,519	10	49,850	10	60,180	10	70,511	10	80,841	10	91,172	10	101,502
1/4	8,777	1/4	19,111	1/4	29,418	1/4	39,735	1/4	50,065	1/4	60,396	1/4	70,726	1/4	81,057	1/4	91,387	1/4	101,717
1/2	8,993	1/2	19,326	1/2	29,632	1/2	39,950	1/2	50,280	1/2	60,611	1/2	70,941	1/2	81,272	1/2	91,602	1/2	101,933
3/4	9,208	3/4	19,541	3/4	29,846	3/4	40,165	3/4	50,496	3/4	60,826	3/4	71,157	3/4	81,487	3/4	91,817	3/4	102,148
11	9,423	11	19,757	11	30,061	11	40,380	11	50,711	11	61,041	11	71,372	11	81,702	11	92,033	11	102,363
1/4	9,639	1/4	19,972	1/4	30,275	1/4	40,596	1/4	50,926	1/4	61,256	1/4	71,587	1/4	81,917	1/4	92,248	1/4	102,578
1/2	9,854	1/2	20,187	1/2	30,489	1/2	40,811	1/2	51,141	1/2	61,472	1/2	71,802	1/2	82,133	1/2	92,463	1/2	102,794
3/4	10,069	3/4	20,402	3/4	30,704	3/4	41,026	3/4	51,356	3/4	61,687	3/4	72,017	3/4	82,348	3/4	92,678	3/4	103,009

NOTE: BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.  
 NOTE: GAUGE POINT: TO TOP LIP OF 2" DIAMETER MMC BALL VALVE, LOCATED NEAR GEOMETRIC CENTER OF TANK 26' 03" AFT OF FORWARD BULKHEAD; NO TRIM CORRECTION REQUIRED  
 NOTE: CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK AT CENTERLINE.  
 NOTE: CAPACITY TABLE REFLECTS GAUGING ON ZERO DATUM LOCATED 1/4" ABOVE TANK BOTTOM.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED 5/12/05 BY: WHF/DJS  
 DATE COMPUTED: 5/31/05 BY: WHF  
 DATE ISSUED: 6/7/05

**INTERTEK - CALEB BRETT**



**BARGE "CCL 18"**  
**HULL NO. 023**

**TANK NO. 1**  
**INNAGE TABLE**

CAPACITIES GIVEN IN WHOLE GALLONS

OFFICIAL NUMBER 1168981

GAUGE HEIGHT 16' 02 3/4"

IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	103,224	0	112,439	0	121,368	0	130,297	0	139,226	0		0		0		0		0	
1/4	103,439	1/4	112,625	1/4	121,554	1/4	130,483	1/4	139,412	1/4		1/4		1/4		1/4		1/4	
1/2	103,654	1/2	112,811	1/2	121,740	1/2	130,669	1/2	139,598	1/2		1/2		1/2		1/2		1/2	
3/4	103,870	3/4	112,997	3/4	121,926	3/4	130,855	3/4	139,784	3/4		3/4		3/4		3/4		3/4	
1	104,078	1	113,183	1	122,112	1	131,041	1	139,970	1		1		1		1		1	
1/4	104,287	1/4	113,369	1/4	122,298	1/4	131,227	1/4	140,156	1/4		1/4		1/4		1/4		1/4	
1/2	104,495	1/2	113,555	1/2	122,484	1/2	131,413	1/2	140,342	1/2		1/2		1/2		1/2		1/2	
3/4	104,704	3/4	113,741	3/4	122,670	3/4	131,599	3/4	140,528	3/4		3/4		3/4		3/4		3/4	
2	104,905	2	113,927	2	122,856	2	131,785	2	140,714	2		2		2		2		2	
1/4	105,107	1/4	114,113	1/4	123,042	1/4	131,971	1/4	140,900	1/4		1/4		1/4		1/4		1/4	
1/2	105,309	1/2	114,299	1/2	123,228	1/2	132,157	1/2	141,086	1/2		1/2		1/2		1/2		1/2	
3/4	105,511	3/4	114,485	3/4	123,414	3/4	132,343	3/4	141,272	3/4		3/4		3/4		3/4		3/4	
3	105,706	3	114,671	3	123,600	3	132,529	3	141,458	3		3		3		3		3	
1/4	105,901	1/4	114,857	1/4	123,786	1/4	132,715	1/4	141,645	1/4		1/4		1/4		1/4		1/4	
1/2	106,096	1/2	115,043	1/2	123,972	1/2	132,901	1/2	141,831	1/2		1/2		1/2		1/2		1/2	
3/4	106,291	3/4	115,229	3/4	124,158	3/4	133,087	3/4	142,017	3/4		3/4		3/4		3/4		3/4	
4	106,479	4	115,415	4	124,344	4	133,273	4	142,203	4		4		4		4		4	
1/4	106,668	1/4	115,601	1/4	124,530	1/4	133,459	1/4	142,389	1/4		1/4		1/4		1/4		1/4	
1/2	106,856	1/2	115,787	1/2	124,716	1/2	133,646	1/2	142,575	1/2		1/2		1/2		1/2		1/2	
3/4	107,044	3/4	115,973	3/4	124,902	3/4	133,832	3/4	142,761	3/4		3/4		3/4		3/4		3/4	
5	107,230	5	116,159	5	125,088	5	134,018	5	142,947	5		5		5		5		5	
1/4	107,416	1/4	116,345	1/4	125,274	1/4	134,204	1/4	143,133	1/4		1/4		1/4		1/4		1/4	
1/2	107,602	1/2	116,531	1/2	125,461	1/2	134,390	1/2	143,319	1/2		1/2		1/2		1/2		1/2	
3/4	107,788	3/4	116,717	3/4	125,647	3/4	134,576	3/4	143,505	3/4		3/4		3/4		3/4		3/4	
6	107,974	6	116,903	6	125,833	6	134,762	6	143,691	6		6		6		6		6	
1/4	108,160	1/4	117,089	1/4	126,019	1/4	134,948	1/4	143,877	1/4		1/4		1/4		1/4		1/4	
1/2	108,346	1/2	117,276	1/2	126,205	1/2	135,134	1/2	144,063	1/2		1/2		1/2		1/2		1/2	
3/4	108,532	3/4	117,462	3/4	126,391	3/4	135,320	3/4	144,249	3/4		3/4		3/4		3/4		3/4	
7	108,718	7	117,648	7	126,577	7	135,506	7	144,398	7		7		7		7		7	
1/4	108,904	1/4	117,834	1/4	126,763	1/4	135,692	1/4	144,546	1/4		1/4		1/4		1/4		1/4	
1/2	109,090	1/2	118,020	1/2	126,949	1/2	135,878	1/2	144,695	1/2		1/2		1/2		1/2		1/2	
3/4	109,277	3/4	118,206	3/4	127,135	3/4	136,064	3/4	144,844	3/4		3/4		3/4		3/4		3/4	
8	109,463	8	118,392	8	127,321	8	136,250	8	144,955	8		8		8		8		8	
1/4	109,649	1/4	118,578	1/4	127,507	1/4	136,436	1/4	145,067	1/4		1/4		1/4		1/4		1/4	
1/2	109,835	1/2	118,764	1/2	127,693	1/2	136,622	1/2	145,178	1/2		1/2		1/2		1/2		1/2	
3/4	110,021	3/4	118,950	3/4	127,879	3/4	136,808	3/4	145,290	3/4		3/4		3/4		3/4		3/4	
9	110,207	9	119,136	9	128,065	9	136,994	9	145,364	9		9		9		9		9	
1/4	110,393	1/4	119,322	1/4	128,251	1/4	137,180	1/4	145,439	1/4		1/4		1/4		1/4		1/4	
1/2	110,579	1/2	119,508	1/2	128,437	1/2	137,366	1/2	145,513	1/2		1/2		1/2		1/2		1/2	
3/4	110,765	3/4	119,694	3/4	128,623	3/4	137,552	3/4	145,587	3/4		3/4		3/4		3/4		3/4	
10	110,951	10	119,880	10	128,809	10	137,738	10	145,624	10		10		10		10		10	
1/4	111,137	1/4	120,066	1/4	128,995	1/4	137,924	1/4	145,661	1/4		1/4		1/4		1/4		1/4	
1/2	111,323	1/2	120,252	1/2	129,181	1/2	138,110	1/2	145,698	1/2		1/2		1/2		1/2		1/2	
3/4	111,509	3/4	120,438	3/4	129,367	3/4	138,296	3/4	145,735	3/4		3/4		3/4		3/4		3/4	
11	111,695	11	120,624	11	129,553	11	138,482	11	145,754	11		11		11		11		11	
1/4	111,881	1/4	120,810	1/4	129,739	1/4	138,668	1/4	145,772	1/4		1/4		1/4		1/4		1/4	
1/2	112,067	1/2	120,996	1/2	129,925	1/2	138,854	1/2	145,791	1/2		1/2		1/2		1/2		1/2	
3/4	112,253	3/4	121,182	3/4	130,111	3/4	139,040	3/4	145,810	3/4		3/4		3/4		3/4		3/4	

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED 5/12/05 BY: WHF/DJS  
DATE COMPUTED: 5/31/05 BY: WHF  
DATE ISSUED: 6/7/05

**INTERTEK - CALEB BRETT**  


**BARGE "CCL 18"  
HULL NO. 023**

**TANK NO. 2  
INNAGE TABLE**

CAPACITIES GIVEN IN WHOLE GALLONS

OFFICIAL NUMBER 1168981

GAUGE HEIGHT 16' 02"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	262	0	11,802	0	23,427	0	35,012	0	46,629	0	58,255	0	69,882	0	81,508	0	93,135	0	104,762
1/4	496	1/4	12,044	1/4	23,669	1/4	35,253	1/4	46,871	1/4	58,497	1/4	70,124	1/4	81,751	1/4	93,377	1/4	105,004
1/2	731	1/2	12,286	1/2	23,911	1/2	35,494	1/2	47,113	1/2	58,740	1/2	70,366	1/2	81,993	1/2	93,620	1/2	105,246
3/4	965	3/4	12,528	3/4	24,153	3/4	35,735	3/4	47,355	3/4	58,982	3/4	70,609	3/4	82,235	3/4	93,862	3/4	105,488
1	1,201	1	12,770	1	24,396	1	35,976	1	47,598	1	59,224	1	70,851	1	82,477	1	94,104	1	105,731
1/4	1,437	1/4	13,012	1/4	24,638	1/4	36,216	1/4	47,840	1/4	59,466	1/4	71,093	1/4	82,720	1/4	94,346	1/4	105,973
1/2	1,673	1/2	13,255	1/2	24,880	1/2	36,457	1/2	48,082	1/2	59,709	1/2	71,335	1/2	82,962	1/2	94,588	1/2	106,215
3/4	1,909	3/4	13,497	3/4	25,122	3/4	36,698	3/4	48,324	3/4	59,951	3/4	71,577	3/4	83,204	3/4	94,831	3/4	106,457
2	2,147	2	13,739	2	25,364	2	36,941	2	48,566	2	60,193	2	71,820	2	83,446	2	95,073	2	106,699
1/4	2,384	1/4	13,981	1/4	25,607	1/4	37,183	1/4	48,809	1/4	60,435	1/4	72,062	1/4	83,688	1/4	95,315	1/4	106,942
1/2	2,622	1/2	14,223	1/2	25,849	1/2	37,425	1/2	49,051	1/2	60,677	1/2	72,304	1/2	83,931	1/2	95,557	1/2	107,184
3/4	2,859	3/4	14,466	3/4	26,091	3/4	37,667	3/4	49,293	3/4	60,920	3/4	72,546	3/4	84,173	3/4	95,800	3/4	107,426
3	3,098	3	14,708	3	26,333	3	37,909	3	49,535	3	61,162	3	72,789	3	84,415	3	96,042	3	107,668
1/4	3,338	1/4	14,950	1/4	26,575	1/4	38,151	1/4	49,778	1/4	61,404	1/4	73,031	1/4	84,657	1/4	96,284	1/4	107,911
1/2	3,577	1/2	15,192	1/2	26,818	1/2	38,394	1/2	50,020	1/2	61,646	1/2	73,273	1/2	84,900	1/2	96,526	1/2	108,153
3/4	3,816	3/4	15,434	3/4	27,060	3/4	38,636	3/4	50,262	3/4	61,889	3/4	73,515	3/4	85,142	3/4	96,768	3/4	108,395
4	4,056	4	15,676	4	27,301	4	38,878	4	50,504	4	62,131	4	73,757	4	85,384	4	97,011	4	108,637
1/4	4,297	1/4	15,919	1/4	27,542	1/4	39,120	1/4	50,746	1/4	62,373	1/4	74,000	1/4	85,626	1/4	97,253	1/4	108,879
1/2	4,538	1/2	16,161	1/2	27,783	1/2	39,362	1/2	50,989	1/2	62,615	1/2	74,242	1/2	85,868	1/2	97,495	1/2	109,122
3/4	4,778	3/4	16,403	3/4	28,024	3/4	39,604	3/4	51,231	3/4	62,857	3/4	74,484	3/4	86,111	3/4	97,737	3/4	109,364
5	5,021	5	16,645	5	28,265	5	39,847	5	51,473	5	63,100	5	74,726	5	86,353	5	97,979	5	109,606
1/4	5,263	1/4	16,887	1/4	28,506	1/4	40,089	1/4	51,715	1/4	63,342	1/4	74,969	1/4	86,595	1/4	98,222	1/4	109,848
1/2	5,505	1/2	17,129	1/2	28,747	1/2	40,331	1/2	51,958	1/2	63,584	1/2	75,211	1/2	86,837	1/2	98,464	1/2	110,091
3/4	5,747	3/4	17,372	3/4	28,988	3/4	40,573	3/4	52,200	3/4	63,826	3/4	75,453	3/4	87,080	3/4	98,706	3/4	110,333
6	5,989	6	17,614	6	29,229	6	40,815	6	52,442	6	64,069	6	75,695	6	87,322	6	98,948	6	110,575
1/4	6,232	1/4	17,856	1/4	29,469	1/4	41,058	1/4	52,684	1/4	64,311	1/4	75,937	1/4	87,564	1/4	99,191	1/4	110,817
1/2	6,474	1/2	18,098	1/2	29,710	1/2	41,300	1/2	52,926	1/2	64,553	1/2	76,180	1/2	87,806	1/2	99,433	1/2	111,059
3/4	6,716	3/4	18,340	3/4	29,951	3/4	41,542	3/4	53,169	3/4	64,795	3/4	76,422	3/4	88,048	3/4	99,675	3/4	111,302
7	6,958	7	18,583	7	30,192	7	41,784	7	53,411	7	65,037	7	76,664	7	88,291	7	99,917	7	111,544
1/4	7,200	1/4	18,825	1/4	30,433	1/4	42,026	1/4	53,653	1/4	65,280	1/4	76,906	1/4	88,533	1/4	100,159	1/4	111,786
1/2	7,442	1/2	19,067	1/2	30,674	1/2	42,269	1/2	53,895	1/2	65,522	1/2	77,148	1/2	88,775	1/2	100,402	1/2	112,028
3/4	7,685	3/4	19,309	3/4	30,915	3/4	42,511	3/4	54,138	3/4	65,764	3/4	77,391	3/4	89,017	3/4	100,644	3/4	112,271
8	7,927	8	19,551	8	31,156	8	42,753	8	54,380	8	66,006	8	77,633	8	89,260	8	100,886	8	112,513
1/4	8,169	1/4	19,794	1/4	31,397	1/4	42,995	1/4	54,622	1/4	66,249	1/4	77,875	1/4	89,502	1/4	101,128	1/4	112,755
1/2	8,411	1/2	20,036	1/2	31,638	1/2	43,238	1/2	54,864	1/2	66,491	1/2	78,117	1/2	89,744	1/2	101,371	1/2	112,997
3/4	8,653	3/4	20,278	3/4	31,879	3/4	43,480	3/4	55,106	3/4	66,733	3/4	78,360	3/4	89,986	3/4	101,613	3/4	113,239
9	8,896	9	20,520	9	32,120	9	43,722	9	55,349	9	66,975	9	78,602	9	90,228	9	101,855	9	113,482
1/4	9,138	1/4	20,762	1/4	32,361	1/4	43,964	1/4	55,591	1/4	67,217	1/4	78,844	1/4	90,471	1/4	102,097	1/4	113,724
1/2	9,380	1/2	21,005	1/2	32,602	1/2	44,206	1/2	55,833	1/2	67,460	1/2	79,086	1/2	90,713	1/2	102,339	1/2	113,966
3/4	9,622	3/4	21,247	3/4	32,843	3/4	44,449	3/4	56,075	3/4	67,702	3/4	79,328	3/4	90,955	3/4	102,582	3/4	114,208
10	9,864	10	21,489	10	33,084	10	44,691	10	56,318	10	67,944	10	79,571	10	91,197	10	102,824	10	114,451
1/4	10,106	1/4	21,731	1/4	33,325	1/4	44,933	1/4	56,560	1/4	68,186	1/4	79,813	1/4	91,440	1/4	103,066	1/4	114,693
1/2	10,349	1/2	21,974	1/2	33,566	1/2	45,175	1/2	56,802	1/2	68,429	1/2	80,055	1/2	91,682	1/2	103,308	1/2	114,935
3/4	10,591	3/4	22,216	3/4	33,807	3/4	45,418	3/4	57,044	3/4	68,671	3/4	80,297	3/4	91,924	3/4	103,551	3/4	115,177
11	10,833	11	22,458	11	34,048	11	45,660	11	57,286	11	68,913	11	80,540	11	92,166	11	103,793	11	115,419
1/4	11,075	1/4	22,700	1/4	34,289	1/4	45,902	1/4	57,529	1/4	69,155	1/4	80,782	1/4	92,408	1/4	104,035	1/4	115,662
1/2	11,317	1/2	22,942	1/2	34,530	1/2	46,144	1/2	57,771	1/2	69,397	1/2	81,024	1/2	92,651	1/2	104,277	1/2	115,904
3/4	11,559	3/4	23,185	3/4	34,771	3/4	46,386	3/4	58,013	3/4	69,640	3/4	81,266	3/4	92,893	3/4	104,519	3/4	116,146

NOTE: BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.  
 NOTE: GAUGE POINT: TO TOP LIP OF 2" DIAMETER MMC BALL VALVE, LOCATED NEAR GEOMETRIC CENTER OF TANK 29' 01" AFT OF FORWARD BULKHEAD; NO TRIM CORRECTION REQUIRED  
 NOTE: CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK AT CENTERLINE.  
 NOTE: CAPACITY TABLE REFLECTS GAUGING ON ZERO DATUM LOCATED 1/4" ABOVE TANK BOTTOM.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED 5/12/05 BY: WHF/DJS  
 DATE COMPUTED: 5/31/05 BY: WHF  
 DATE ISSUED: 6/7/05

**INTERTEK - CALEB BRETT**



**BARGE "CCL 18"**  
**HULL NO. 023**

**TANK NO. 2**  
**INNAGE TABLE**

CAPACITIES GIVEN IN WHOLE GALLONS

OFFICIAL NUMBER 1168981

GAUGE HEIGHT 16' 02"

IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	116,388	0	128,015	0	139,641	0	151,268	0	162,895	0		0		0		0		0	
1/4	116,630	1/4	128,257	1/4	139,884	1/4	151,510	1/4	163,137	1/4		1/4		1/4		1/4		1/4	
1/2	116,873	1/2	128,499	1/2	140,126	1/2	151,753	1/2	163,379	1/2		1/2		1/2		1/2		1/2	
3/4	117,115	3/4	128,742	3/4	140,368	3/4	151,995	3/4	163,621	3/4		3/4		3/4		3/4		3/4	
1	117,357	1	128,984	1	140,610	1	152,237	1	163,864	1		1		1		1		1	
1/4	117,599	1/4	129,226	1/4	140,853	1/4	152,479	1/4	164,106	1/4		1/4		1/4		1/4		1/4	
1/2	117,842	1/2	129,468	1/2	141,095	1/2	152,721	1/2	164,348	1/2		1/2		1/2		1/2		1/2	
3/4	118,084	3/4	129,710	3/4	141,337	3/4	152,964	3/4	164,590	3/4		3/4		3/4		3/4		3/4	
2	118,326	2	129,953	2	141,579	2	153,206	2	164,832	2		2		2		2		2	
1/4	118,568	1/4	130,195	1/4	141,821	1/4	153,448	1/4	165,075	1/4		1/4		1/4		1/4		1/4	
1/2	118,810	1/2	130,437	1/2	142,064	1/2	153,690	1/2	165,317	1/2		1/2		1/2		1/2		1/2	
3/4	119,053	3/4	130,679	3/4	142,306	3/4	153,932	3/4	165,559	3/4		3/4		3/4		3/4		3/4	
3	119,295	3	130,922	3	142,548	3	154,175	3	165,801	3		3		3		3		3	
1/4	119,537	1/4	131,164	1/4	142,790	1/4	154,417	1/4	166,044	1/4		1/4		1/4		1/4		1/4	
1/2	119,779	1/2	131,406	1/2	143,033	1/2	154,659	1/2	166,286	1/2		1/2		1/2		1/2		1/2	
3/4	120,022	3/4	131,648	3/4	143,275	3/4	154,901	3/4	166,528	3/4		3/4		3/4		3/4		3/4	
4	120,264	4	131,890	4	143,517	4	155,144	4	166,770	4		4		4		4		4	
1/4	120,506	1/4	132,133	1/4	143,759	1/4	155,386	1/4	167,012	1/4		1/4		1/4		1/4		1/4	
1/2	120,748	1/2	132,375	1/2	144,001	1/2	155,628	1/2	167,255	1/2		1/2		1/2		1/2		1/2	
3/4	120,990	3/4	132,617	3/4	144,244	3/4	155,870	3/4	167,497	3/4		3/4		3/4		3/4		3/4	
5	121,233	5	132,859	5	144,486	5	156,112	5	167,739	5		5		5		5		5	
1/4	121,475	1/4	133,102	1/4	144,728	1/4	156,355	1/4	167,981	1/4		1/4		1/4		1/4		1/4	
1/2	121,717	1/2	133,344	1/2	144,970	1/2	156,597	1/2	168,224	1/2		1/2		1/2		1/2		1/2	
3/4	121,959	3/4	133,586	3/4	145,213	3/4	156,839	3/4	168,466	3/4		3/4		3/4		3/4		3/4	
6	122,202	6	133,828	6	145,455	6	157,081	6	168,668	6		6		6		6		6	
1/4	122,444	1/4	134,070	1/4	145,697	1/4	157,324	1/4	168,869	1/4		1/4		1/4		1/4		1/4	
1/2	122,686	1/2	134,313	1/2	145,939	1/2	157,566	1/2	169,071	1/2		1/2		1/2		1/2		1/2	
3/4	122,928	3/4	134,555	3/4	146,181	3/4	157,808	3/4	169,273	3/4		3/4		3/4		3/4		3/4	
7	123,170	7	134,797	7	146,424	7	158,050	7	169,467	7		7		7		7		7	
1/4	123,413	1/4	135,039	1/4	146,666	1/4	158,292	1/4	169,661	1/4		1/4		1/4		1/4		1/4	
1/2	123,655	1/2	135,281	1/2	146,908	1/2	158,535	1/2	169,854	1/2		1/2		1/2		1/2		1/2	
3/4	123,897	3/4	135,524	3/4	147,150	3/4	158,777	3/4	170,048	3/4		3/4		3/4		3/4		3/4	
8	124,139	8	135,766	8	147,393	8	159,019	8	170,193	8		8		8		8		8	
1/4	124,382	1/4	136,008	1/4	147,635	1/4	159,261	1/4	170,339	1/4		1/4		1/4		1/4		1/4	
1/2	124,624	1/2	136,250	1/2	147,877	1/2	159,504	1/2	170,484	1/2		1/2		1/2		1/2		1/2	
3/4	124,866	3/4	136,493	3/4	148,119	3/4	159,746	3/4	170,629	3/4		3/4		3/4		3/4		3/4	
9	125,108	9	136,735	9	148,361	9	159,988	9	170,726	9		9		9		9		9	
1/4	125,350	1/4	136,977	1/4	148,604	1/4	160,230	1/4	170,823	1/4		1/4		1/4		1/4		1/4	
1/2	125,593	1/2	137,219	1/2	148,846	1/2	160,472	1/2	170,920	1/2		1/2		1/2		1/2		1/2	
3/4	125,835	3/4	137,461	3/4	149,088	3/4	160,715	3/4	171,017	3/4		3/4		3/4		3/4		3/4	
10	126,077	10	137,704	10	149,330	10	160,957	10	171,065	10		10		10		10		10	
1/4	126,319	1/4	137,946	1/4	149,573	1/4	161,199	1/4	171,114	1/4		1/4		1/4		1/4		1/4	
1/2	126,562	1/2	138,188	1/2	149,815	1/2	161,441	1/2	171,162	1/2		1/2		1/2		1/2		1/2	
3/4	126,804	3/4	138,430	3/4	150,057	3/4	161,684	3/4	171,210	3/4		3/4		3/4		3/4		3/4	
11	127,046	11	138,673	11	150,299	11	161,926	11	171,235	11		11		11		11		11	
1/4	127,288	1/4	138,915	1/4	150,541	1/4	162,168	1/4	171,259	1/4		1/4		1/4		1/4		1/4	
1/2	127,530	1/2	139,157	1/2	150,784	1/2	162,410	1/2	171,283	1/2		1/2		1/2		1/2		1/2	
3/4	127,773	3/4	139,399	3/4	151,026	3/4	162,652	3/4	171,307	3/4		3/4		3/4		3/4		3/4	

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED 5/12/05 BY: WHF/DJS  
DATE COMPUTED: 5/31/05 BY: WHF  
DATE ISSUED: 5/7/05

**INTERTEK - CALEB BRETT**  


**BARGE "CCL 18"**  
**HULL NO. 023**

**TANK NO. 3**  
**INNAGE TABLE**

CAPACITIES GIVEN IN WHOLE GALLONS

OFFICIAL NUMBER 1168981

GAUGE HEIGHT 16' 02 1/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	236	0	10,484	0	20,804	0	31,112	0	41,427	0	51,745	0	62,064	0	72,382	0	82,701	0	93,019
1/4	444	1/4	10,899	1/4	21,019	1/4	31,326	1/4	41,642	1/4	51,960	1/4	62,279	1/4	72,597	1/4	82,916	1/4	93,234
1/2	652	1/2	10,914	1/2	21,234	1/2	31,541	1/2	41,857	1/2	52,175	1/2	62,494	1/2	72,812	1/2	83,131	1/2	93,449
3/4	860	3/4	11,129	3/4	21,449	3/4	31,755	3/4	42,072	3/4	52,390	3/4	62,709	3/4	73,027	3/4	83,346	3/4	93,664
1	1,070	1	11,344	1	21,664	1	31,970	1	42,287	1	52,605	1	62,924	1	73,242	1	83,561	1	93,879
1/4	1,279	1/4	11,559	1/4	21,879	1/4	32,185	1/4	42,502	1/4	52,820	1/4	63,139	1/4	73,457	1/4	83,776	1/4	94,094
1/2	1,489	1/2	11,774	1/2	22,094	1/2	32,399	1/2	42,717	1/2	53,035	1/2	63,354	1/2	73,672	1/2	83,991	1/2	94,309
3/4	1,699	3/4	11,990	3/4	22,309	3/4	32,614	3/4	42,932	3/4	53,250	3/4	63,569	3/4	73,887	3/4	84,206	3/4	94,524
2	1,910	2	12,205	2	22,524	2	32,829	2	43,147	2	53,465	2	63,784	2	74,102	2	84,421	2	94,739
1/4	2,121	1/4	12,420	1/4	22,739	1/4	33,044	1/4	43,362	1/4	53,680	1/4	63,999	1/4	74,317	1/4	84,636	1/4	94,954
1/2	2,332	1/2	12,635	1/2	22,954	1/2	33,259	1/2	43,577	1/2	53,895	1/2	64,214	1/2	74,532	1/2	84,850	1/2	95,169
3/4	2,542	3/4	12,850	3/4	23,168	3/4	33,474	3/4	43,792	3/4	54,110	3/4	64,428	3/4	74,747	3/4	85,065	3/4	95,384
3	2,755	3	13,065	3	23,383	3	33,689	3	44,007	3	54,325	3	64,643	3	74,962	3	85,280	3	95,599
1/4	2,967	1/4	13,280	1/4	23,598	1/4	33,904	1/4	44,221	1/4	54,540	1/4	64,858	1/4	75,177	1/4	85,495	1/4	95,814
1/2	3,180	1/2	13,495	1/2	23,813	1/2	34,118	1/2	44,436	1/2	54,755	1/2	65,073	1/2	75,392	1/2	85,710	1/2	96,029
3/4	3,392	3/4	13,710	3/4	24,028	3/4	34,333	3/4	44,651	3/4	54,970	3/4	65,288	3/4	75,607	3/4	85,925	3/4	96,244
4	3,606	4	13,925	4	24,243	4	34,548	4	44,866	4	55,185	4	65,503	4	75,822	4	86,140	4	96,459
1/4	3,819	1/4	14,140	1/4	24,458	1/4	34,763	1/4	45,081	1/4	55,400	1/4	65,718	1/4	76,037	1/4	86,355	1/4	96,674
1/2	4,033	1/2	14,355	1/2	24,672	1/2	34,978	1/2	45,296	1/2	55,615	1/2	65,933	1/2	76,252	1/2	86,570	1/2	96,889
3/4	4,247	3/4	14,570	3/4	24,887	3/4	35,193	3/4	45,511	3/4	55,830	3/4	66,148	3/4	76,467	3/4	86,785	3/4	97,104
5	4,462	5	14,785	5	25,102	5	35,408	5	45,726	5	56,045	5	66,363	5	76,682	5	87,000	5	97,319
1/4	4,677	1/4	15,001	1/4	25,316	1/4	35,623	1/4	45,941	1/4	56,260	1/4	66,578	1/4	76,897	1/4	87,215	1/4	97,534
1/2	4,892	1/2	15,216	1/2	25,531	1/2	35,838	1/2	46,156	1/2	56,475	1/2	66,793	1/2	77,112	1/2	87,430	1/2	97,749
3/4	5,107	3/4	15,431	3/4	25,745	3/4	36,053	3/4	46,371	3/4	56,690	3/4	67,008	3/4	77,327	3/4	87,645	3/4	97,964
6	5,322	6	15,646	6	25,960	6	36,268	6	46,586	6	56,905	6	67,223	6	77,542	6	87,860	6	98,178
1/4	5,537	1/4	15,861	1/4	26,175	1/4	36,483	1/4	46,801	1/4	57,120	1/4	67,438	1/4	77,757	1/4	88,075	1/4	98,393
1/2	5,752	1/2	16,076	1/2	26,389	1/2	36,698	1/2	47,016	1/2	57,335	1/2	67,653	1/2	77,971	1/2	88,290	1/2	98,608
3/4	5,967	3/4	16,290	3/4	26,604	3/4	36,913	3/4	47,231	3/4	57,550	3/4	67,868	3/4	78,186	3/4	88,505	3/4	98,823
7	6,183	7	16,505	7	26,819	7	37,128	7	47,446	7	57,764	7	68,083	7	78,401	7	88,720	7	99,038
1/4	6,398	1/4	16,720	1/4	27,033	1/4	37,343	1/4	47,661	1/4	57,979	1/4	68,298	1/4	78,616	1/4	88,935	1/4	99,253
1/2	6,613	1/2	16,935	1/2	27,248	1/2	37,557	1/2	47,876	1/2	58,194	1/2	68,513	1/2	78,831	1/2	89,150	1/2	99,468
3/4	6,828	3/4	17,150	3/4	27,463	3/4	37,772	3/4	48,091	3/4	58,409	3/4	68,728	3/4	79,046	3/4	89,365	3/4	99,683
8	7,043	8	17,365	8	27,677	8	37,987	8	48,306	8	58,624	8	68,943	8	79,261	8	89,580	8	99,898
1/4	7,258	1/4	17,580	1/4	27,892	1/4	38,202	1/4	48,521	1/4	58,839	1/4	69,158	1/4	79,476	1/4	89,795	1/4	100,113
1/2	7,473	1/2	17,795	1/2	28,107	1/2	38,417	1/2	48,736	1/2	59,054	1/2	69,373	1/2	79,691	1/2	90,010	1/2	100,328
3/4	7,688	3/4	18,010	3/4	28,321	3/4	38,632	3/4	48,951	3/4	59,269	3/4	69,588	3/4	79,906	3/4	90,225	3/4	100,543
9	7,903	9	18,225	9	28,536	9	38,847	9	49,166	9	59,484	9	69,803	9	80,121	9	90,440	9	100,758
1/4	8,118	1/4	18,440	1/4	28,750	1/4	39,062	1/4	49,381	1/4	59,699	1/4	70,018	1/4	80,336	1/4	90,655	1/4	100,973
1/2	8,333	1/2	18,655	1/2	28,965	1/2	39,277	1/2	49,596	1/2	59,914	1/2	70,233	1/2	80,551	1/2	90,870	1/2	101,188
3/4	8,548	3/4	18,870	3/4	29,180	3/4	39,492	3/4	49,811	3/4	60,129	3/4	70,448	3/4	80,766	3/4	91,085	3/4	101,403
10	8,763	10	19,085	10	29,394	10	39,707	10	50,026	10	60,344	10	70,663	10	80,981	10	91,300	10	101,618
1/4	8,979	1/4	19,300	1/4	29,609	1/4	39,922	1/4	50,241	1/4	60,559	1/4	70,878	1/4	81,196	1/4	91,514	1/4	101,833
1/2	9,194	1/2	19,515	1/2	29,824	1/2	40,137	1/2	50,456	1/2	60,774	1/2	71,093	1/2	81,411	1/2	91,729	1/2	102,048
3/4	9,409	3/4	19,729	3/4	30,038	3/4	40,352	3/4	50,671	3/4	60,989	3/4	71,307	3/4	81,626	3/4	91,944	3/4	102,263
11	9,624	11	19,944	11	30,253	11	40,567	11	50,885	11	61,204	11	71,522	11	81,841	11	92,159	11	102,478
1/4	9,839	1/4	20,159	1/4	30,468	1/4	40,782	1/4	51,100	1/4	61,419	1/4	71,737	1/4	82,056	1/4	92,374	1/4	102,693
1/2	10,054	1/2	20,374	1/2	30,682	1/2	40,997	1/2	51,315	1/2	61,634	1/2	71,952	1/2	82,271	1/2	92,589	1/2	102,908
3/4	10,269	3/4	20,589	3/4	30,897	3/4	41,212	3/4	51,530	3/4	61,849	3/4	72,167	3/4	82,486	3/4	92,804	3/4	103,123

NOTE: BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.  
 NOTE: GAUGE POINT: TO TOP LIP OF 2" DIAMETER MMC BALL VALVE, LOCATED NEAR GEOMETRIC CENTER OF TANK 26' 03" AFT OF FORWARD BULKHEAD; NO TRIM CORRECTION REQUIRED  
 NOTE: CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK AT CENTERLINE.  
 NOTE: CAPACITY TABLE REFLECTS GAUGING ON ZERO DATUM LOCATED 1/4" ABOVE TANK BOTTOM.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED 5/12/05 BY: WHF/DJS  
 DATE COMPUTED: 5/31/05 BY: WHF  
 DATE ISSUED: 8/25/05 Corrected Tank 3

**INTERTEK - CALEB BRETT**



**BARGE "CCL 18"**  
**HULL NO. 023**

**TANK NO. 3**  
**INNAGE TABLE**

CAPACITIES GIVEN IN WHOLE GALLONS

OFFICIAL NUMBER 1168981

GAUGE HEIGHT 16' 02 1/4"

IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	103,338	0	113,656	0	123,975	0	134,293	0	144,612	0		0		0		0		0	
1/4	103,553	1/4	113,871	1/4	124,190	1/4	134,508	1/4	144,827	1/4		1/4		1/4		1/4		1/4	
1/2	103,768	1/2	114,086	1/2	124,405	1/2	134,723	1/2	145,042	1/2		1/2		1/2		1/2		1/2	
3/4	103,983	3/4	114,301	3/4	124,620	3/4	134,938	3/4	145,257	3/4		3/4		3/4		3/4		3/4	
1	104,198	1	114,516	1	124,835	1	135,153	1	145,471	1		1		1		1		1	
1/4	104,413	1/4	114,731	1/4	125,050	1/4	135,368	1/4	145,686	1/4		1/4		1/4		1/4		1/4	
1/2	104,628	1/2	114,946	1/2	125,264	1/2	135,583	1/2	145,901	1/2		1/2		1/2		1/2		1/2	
3/4	104,843	3/4	115,161	3/4	125,479	3/4	135,798	3/4	146,116	3/4		3/4		3/4		3/4		3/4	
2	105,057	2	115,376	2	125,694	2	136,013	2	146,331	2		2		2		2		2	
1/4	105,272	1/4	115,591	1/4	125,909	1/4	136,228	1/4	146,546	1/4		1/4		1/4		1/4		1/4	
1/2	105,487	1/2	115,806	1/2	126,124	1/2	136,443	1/2	146,761	1/2		1/2		1/2		1/2		1/2	
3/4	105,702	3/4	116,021	3/4	126,339	3/4	136,658	3/4	146,976	3/4		3/4		3/4		3/4		3/4	
3	105,917	3	116,236	3	126,554	3	136,873	3	147,191	3		3		3		3		3	
1/4	106,132	1/4	116,451	1/4	126,769	1/4	137,088	1/4	147,406	1/4		1/4		1/4		1/4		1/4	
1/2	106,347	1/2	116,666	1/2	126,984	1/2	137,303	1/2	147,621	1/2		1/2		1/2		1/2		1/2	
3/4	106,562	3/4	116,881	3/4	127,199	3/4	137,518	3/4	147,836	3/4		3/4		3/4		3/4		3/4	
4	106,777	4	117,096	4	127,414	4	137,733	4	148,051	4		4		4		4		4	
1/4	106,992	1/4	117,311	1/4	127,629	1/4	137,948	1/4	148,266	1/4		1/4		1/4		1/4		1/4	
1/2	107,207	1/2	117,526	1/2	127,844	1/2	138,163	1/2	148,481	1/2		1/2		1/2		1/2		1/2	
3/4	107,422	3/4	117,741	3/4	128,059	3/4	138,378	3/4	148,696	3/4		3/4		3/4		3/4		3/4	
5	107,637	5	117,956	5	128,274	5	138,593	5	148,911	5		5		5		5		5	
1/4	107,852	1/4	118,171	1/4	128,489	1/4	138,807	1/4	149,126	1/4		1/4		1/4		1/4		1/4	
1/2	108,067	1/2	118,386	1/2	128,704	1/2	139,022	1/2	149,341	1/2		1/2		1/2		1/2		1/2	
3/4	108,282	3/4	118,600	3/4	128,919	3/4	139,237	3/4	149,556	3/4		3/4		3/4		3/4		3/4	
6	108,497	6	118,815	6	129,134	6	139,452	6	149,771	6		6		6		6		6	
1/4	108,712	1/4	119,030	1/4	129,349	1/4	139,667	1/4	149,986	1/4		1/4		1/4		1/4		1/4	
1/2	108,927	1/2	119,245	1/2	129,564	1/2	139,882	1/2	150,201	1/2		1/2		1/2		1/2		1/2	
3/4	109,142	3/4	119,460	3/4	129,779	3/4	140,097	3/4	150,416	3/4		3/4		3/4		3/4		3/4	
7	109,357	7	119,675	7	129,994	7	140,312	7	150,588	7		7		7		7		7	
1/4	109,572	1/4	119,890	1/4	130,209	1/4	140,527	1/4	150,760	1/4		1/4		1/4		1/4		1/4	
1/2	109,787	1/2	120,105	1/2	130,424	1/2	140,742	1/2	150,932	1/2		1/2		1/2		1/2		1/2	
3/4	110,002	3/4	120,320	3/4	130,639	3/4	140,957	3/4	151,103	3/4		3/4		3/4		3/4		3/4	
8	110,217	8	120,535	8	130,854	8	141,172	8	151,232	8		8		8		8		8	
1/4	110,432	1/4	120,750	1/4	131,069	1/4	141,387	1/4	151,361	1/4		1/4		1/4		1/4		1/4	
1/2	110,647	1/2	120,965	1/2	131,284	1/2	141,602	1/2	151,490	1/2		1/2		1/2		1/2		1/2	
3/4	110,862	3/4	121,180	3/4	131,499	3/4	141,817	3/4	151,619	3/4		3/4		3/4		3/4		3/4	
9	111,077	9	121,395	9	131,714	9	142,032	9	151,705	9		9		9		9		9	
1/4	111,292	1/4	121,610	1/4	131,929	1/4	142,247	1/4	151,791	1/4		1/4		1/4		1/4		1/4	
1/2	111,507	1/2	121,825	1/2	132,143	1/2	142,462	1/2	151,877	1/2		1/2		1/2		1/2		1/2	
3/4	111,721	3/4	122,040	3/4	132,358	3/4	142,677	3/4	151,963	3/4		3/4		3/4		3/4		3/4	
10	111,936	10	122,255	10	132,573	10	142,892	10	152,005	10		10		10		10		10	
1/4	112,151	1/4	122,470	1/4	132,788	1/4	143,107	1/4	152,048	1/4		1/4		1/4		1/4		1/4	
1/2	112,366	1/2	122,685	1/2	133,003	1/2	143,322	1/2	152,091	1/2		1/2		1/2		1/2		1/2	
3/4	112,581	3/4	122,900	3/4	133,218	3/4	143,537	3/4	152,134	3/4		3/4		3/4		3/4		3/4	
11	112,796	11	123,115	11	133,433	11	143,752	11	152,155	11		11		11		11		11	
1/4	113,011	1/4	123,330	1/4	133,648	1/4	143,967	1/4	152,177	1/4		1/4		1/4		1/4		1/4	
1/2	113,226	1/2	123,545	1/2	133,863	1/2	144,182	1/2	152,198	1/2		1/2		1/2		1/2		1/2	
3/4	113,441	3/4	123,760	3/4	134,078	3/4	144,397	3/4	152,220	3/4		3/4		3/4		3/4		3/4	

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

DATE STRAPPED 5/12/05 BY: WHF/DJS  
DATE COMPUTED: 5/31/05 BY: WHF  
DATE ISSUED: 8/25/05 Corrected Tank 3

**INTERTEK - CALEB BRETT**

