



United States of America
Department of Homeland Security
United States Coast Guard

Certification Date: 07 Aug 2024
Expiration Date: 07 Aug 2029

Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name	Official Number	IMO Number	Call Sign	Service		
CCL 403	1231311			Tank Barge		
Hailing Port	Hull Material	Horsepower	Propulsion			
NEW ORLEANS, LA	Steel					
UNITED STATES						
Place Built	Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
ASHLAND CITY, TN	22Feb2011	28Jan2011	R-1619	R-1619		R-297.5
UNITED STATES			I-	I-		I-0
Owner	Operator					
CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES	CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES					

This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.

0 Masters	0 Licensed Mates	0 Chief Engineers	0 Oilers
0 Chief Mates	0 First Class Pilots	0 First Assistant Engineers	
0 Second Mates	0 Radio Officers	0 Second Assistant Engineers	
0 Third Mates	0 Able Seamen	0 Third Assistant Engineers	
0 Master First Class Pilot	0 Ordinary Seamen	0 Licensed Engineers	
0 Mate First Class Pilots	0 Deckhands	0 Qualified Member Engineer	

In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0

Route Permitted And Conditions Of Operation:

---Lakes, Bays, and Sounds---

Also, in fair weather only, coastwise, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.

This vessel has been granted fresh water hull examination intervals in accordance with 46 CFR table 31.10-21(b). If this vessel has been operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.

SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION

With this Inspection for Certification having been completed at New Orleans, LA, UNITED STATES, the Officer in Charge, Marine Inspection, Sector New Orleans certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.

Annual/Periodic/Re-Inspection				This certificate issued by D. VELEZ COMMANDER , By direction Officer in Charge, Marine Inspection Sector New Orleans Inspection Zone
Date	Zone	A/P/R	Signature	
16 SEP 2025	SEC. HOU/GAL	A	<i>[Signature]</i>	



United States of America
Department of Homeland Security
United States Coast Guard

Certification Date: 07 Aug 2024
Expiration Date: 07 Aug 2029

Certificate of Inspection

For ships on international voyages this certificate fulfills the requirements of SOLAS 74 as amended, regulation V/14, for a SAFE MANNING DOCUMENT.

Vessel Name	Official Number	IMO Number	Call Sign	Service		
CCL 403	1231311			Tank Barge		
Hailing Port	Hull Material	Horsepower	Propulsion			
NEW ORLEANS, LA	Steel					
UNITED STATES						
Place Built	Delivery Date	Keel Laid Date	Gross Tons	Net Tons	DWT	Length
ASHLAND CITY, TN	22Feb2011	28Jan2011	R-1619	R-1619		R-297.5
UNITED STATES			I-	I-		I-0
Owner	Operator					
CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES	CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE, LA 70780 UNITED STATES					
This vessel must be manned with the following licensed and unlicensed Personnel. Included in which there must be 0 Certified Lifeboatmen, 0 Certified Tankermen, 0 HSC Type Rating, and 0 GMDSS Operators.						
0 Masters	0 Licensed Mates	0 Chief Engineers	0 Oilers			
0 Chief Mates	0 First Class Pilots	0 First Assistant Engineers				
0 Second Mates	0 Radio Officers	0 Second Assistant Engineers				
0 Third Mates	0 Able Seamen	0 Third Assistant Engineers				
0 Master First Class Pilot	0 Ordinary Seamen	0 Licensed Engineers				
0 Mate First Class Pilots	0 Deckhands	0 Qualified Member Engineer				
In addition, this vessel may carry 0 Passengers, 0 Other Persons in crew, 0 Persons in addition to crew, and no Others. Total Persons allowed: 0						
Route Permitted And Conditions Of Operation: ---Lakes, Bays, and Sounds---						
Also, in fair weather only, coastwise, not more than twelve (12) miles from shore between St. Marks and Carrabelle, Florida.						
This vessel has been granted fresh water hull examination intervals in accordance with 46 CFR table 31.10-21(b). If this vessel has been operated in salt water more than six (6) months in any twelve (12) month period, the vessel must be inspected using salt water intervals and the cognizant OCMI notified in writing as soon as this change in status occurs.						
SEE NEXT PAGE FOR ADDITIONAL CERTIFICATE INFORMATION						
With this Inspection for Certification having been completed at New Orleans, LA, UNITED STATES, the Officer in Charge, Marine Inspection, Sector New Orleans certified the vessel, in all respects, is in conformity with the applicable vessel inspection laws and the rules and regulations prescribed thereunder.						
Annual/Periodic/Re-Inspection				This certificate issued by:		
Date	Zone	A/P/R	Signature	D. VELEZ COMMANDER, By direction		
				Officer in Charge, Marine Inspection		
				Sector New Orleans		
				Inspection Zone		



Certificate of Inspection

Vessel Name: CCL 403

---Hull Exams---

Exam Type	Next Exam	Last Exam	Prior Exam
DryDock	30Nov2029	19Nov2019	22Feb2011
Internal Structure	25Jul2029	25Jul2024	19Nov2019

--- Liquid/Gas/Solid Cargo Authority/Conditions ---

Authorization: GRADE "A" AND LOWER AND SPECIFIED HAZARDOUS CARGOES.

Total Capacity	Units	Highest Grade Type	Part151 Regulated	Part153 Regulated	Part154 Regulated
29700	Barrels	A	Yes	No	No

Hazardous Bulk Solids Authority

Not Authorized

Loading Constraints - Structural

Tank Number	Max Cargo Weight per Tank (short tons)	Maximum Density (lbs/gal)
1 P/S	816	13.60
2 P/S	828	13.60
3 P/S	764	13.60

Loading Constraints - Stability

Hull Type	Maximum Load (short tons)	Maximum Draft (ft/in)	Max Density (lbs/gal)	Route Description
II	3840	10ft 3in	13.60	R, LBS, LC 0-12
III	4588	11ft 9in	13.60	R, LBS, LC 0-12

Conditions Of Carriage

Only those cargoes named in the vessel's Cargo Authority Attachment, serial #C1-1100183, dated 21-Jan-11 and Grade "A" and lower cargoes may be carried, and then only in the tanks indicated.

Per 46 CFR 150.130, the Person in Charge of the vessel is responsible for ensuring the compatibility requirements of 46 CFR 150 are met. Cargoes must be checked for compatibility using figures, tables, and appendices of 46 CFR 150 in conjunction with the reactive group numbers from the "COMPAT GRP" column listed in the vessel's CAA.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the Person in Charge is responsible for ensuring the provisions of 46 CFR Part 197, Subpart C are applied.

Stability and Trim

Cargo tanks must be loaded uniformly whenever a 46 CFR Subchapter "O" cargo is carried; for trim purposes, the weight of cargo in each tank may exceed the uniformly loaded tank cargo weight by at most 5 percent.

The maximum design density of cargo which may be filled to the tank top is 8.74 lbs/gal. Cargoes with higher densities, up to 13.6 lbs/gal, may be carried as slack loads, but shall not exceed the tank weight limits as listed above.

Vapor Control Authorization

In accordance with 46 CFR part 39, excluding part 39.4000, this vessel's vapor control system has been inspected to the plans approved by Marine Safety Center letter serial #C1-1100183, dated 21-Jan-11, and found acceptable for collection of bulk liquid cargo vapors annotated with "Yes" in the VCS column of the vessel's Cargo Authority Attachment.



Certificate of Inspection

Vessel Name: CCL 403

--- Inspection Status ---

Fuel Tanks

Tank ID	Internal Examinations		
	Previous	Last	Next
Aft Machinery Deck	-	22Feb2011	-

Cargo Tanks

Tank Id	Internal Exam			External Exam		
	Previous	Last	Next	Previous	Last	Next
1 P/S	22Feb2011	19Nov2019	30Nov2029	-	-	-
2 P/S	22Feb2011	19Nov2019	30Nov2029	-	-	-
3 P/S	22Feb2011	19Nov2019	30Nov2029	-	-	-

Hydro Test

Tank Id	Safety Valves	Previous	Last	Next
1 P/S	-	-	22Feb2011	-
2 P/S	-	-	22Feb2011	-
3 P/S	-	-	22Feb2011	-

---Conditional Portable Fire Extinguisher Requirements---

Required Only During Transfer of Cargo or Operation of Barge Machinery

--- Fire Fighting Equipment ---

Fire Extinguishers - Hand portable and semi-portable

Quantity	Class Type
2	40-B

END



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Shipyard: Trinity Ashland City

Hull #: 4772

46 CFR 151 Tank Group Characteristics

Tank Group Information		Cargo Identification			Hull Type	Cargo Seg Tank	Tanks			Cargo Transfer		Environmental Control		Fire Protection Provided	Special Requirements			Elec Haz	Temp Cont
Tnk Grp	Tanks in Group	Density	Press.	Temp.			Type	Vent	Gauge	Pipe Class	Cont	Tanks	Handling Space		General	Materials of Construction			
A	#1P/S, #2P/S, #3P/S	13.6	Atmos.	Elev	II	1ii 2ii	Integral Gravity	PV	Closed	II	G-1	NR	NA	Portable	40-1(f)(1), .50-60, .50-70(a), .50-70(b), .50-73, .50-81(a), .50-81(b),	55-1(b), (c), (e), (f), (j), 56-1(a), (b), (c), (d), (e), (f), (g),	NR	Yes	

- Notes: 1. Under Environmental Control, Tanks, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo tanks.
2. Under Environmental Control, Handling Space, NR means that the tank group is suitable only for those cargoes which require no environmental control in the cargo handling space. NA means that the vessel does not have a cargo control space, and this requirement is not applied.
3. Under Electrical Hazard Class, NA means that the tank group is suitable only for those cargoes which have no electrical hazard class requirement. NR means that the vessel has no electrical equipment located in a hazardous location.

List of Authorized Cargoes

Cargo Identification						Conditions of Carriage					
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of		Insp. Period
							App'd (Y or N)	VCS Category			

Authorized Subchapter O Cargoes

Acetonitrile	ATN	37	O	C	III	A	Yes	3	No		G
Acrylonitrile	ACN	15 ²	O	C	II	A	Yes	4	.50-70(a), .55-1(e)		G
Adiponitrile	ADN	37	O	E	II	A	Yes	1	No		G
Alkyl(C7-C9) nitrates	AKN	34 ²	O	NA	III	A	No	N/A	.50-81, .50-86		G
Aminoethylethanolamine	AEE	8	O	E	III	A	Yes	1	.55-1(b)		G
Ammonium bisulfite solution (70% or less)	ABX	43 ²	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)		G
Ammonium hydroxide (28% or less NH3)	AMH	6	O	NA	III	A	No	N/A	.56-1(a), (b), (c), (f), (g)		G
Anthracene oil (Coal tar fraction)	AHO	33	O	NA	II	A	No	N/A	No		G
Benzene	BNZ	32	O	C	III	A	Yes	1	.50-60		G
Benzene or hydrocarbon mixtures (having 10% Benzene or more)	BHB	32 ²	O	C	III	A	Yes	1	.50-60		G
Benzene or hydrocarbon mixtures (containing Acetylene and 10% Benzene or more)	BHA	32 ²	O	C	III	A	Yes	1	.50-60, .56-1(b), (d), (f), (g)		G
Benzene, Toluene, Xylene mixtures (10% Benzene or more)	BTX	32	O	B/C	III	A	Yes	1	.50-60		G
Butyl acrylate (all isomers)	BAR	14	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)		G
Butyl methacrylate	BMH	14	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)		G
Butyraldehyde (all isomers)	BAE	19	O	C	III	A	Yes	1	.55-1(h)		G
Camphor oil (light)	CPO	18	O	D	II	A	No	N/A	No		G
Carbon tetrachloride	CBT	36	O	NA	III	A	No	N/A	No		G
Caustic potash solution	CPS	5 ²	O	NA	III	A	No	N/A	.50-73, .55-1(j)		G
Caustic soda solution	CSS	5 ²	O	NA	III	A	No	N/A	.50-73, .55-1(j)		G
Chemical Oil (refined, containing phenolics)	COD	21	O	E	II	A	No	N/A	.50-73		G
Chlorobenzene	CRB	36	O	D	III	A	Yes	1	No		G
Chloroform	CRF	36	O	NA	III	A	Yes	3	No		G
Coal tar naphtha solvent	NCT	33	O	D	III	A	Yes	1	.50-73		G
Coal tar pitch (molten)	CTP	33	O	E	III	A	No	N/A	.50-73		G
Creosote	CCW	21 ²	O	E	III	A	Yes	1	No		G
Cresols (all isomers)	CRS	21	O	E	III	A	Yes	1	No		G
Cresylate spent caustic	CSC	5	O	NA	III	A	No	N/A	.50-73, .55-1(b)		G
Cresylic acid tar	CRX		O	E	III	A	Yes	1	.55-1(f)		G
Crotonaldehyde	CTA	19 ²	O	C	II	A	Yes	4	.55-1(h)		G
Crude hydrocarbon feedstock (containing Butyraldehydes and Ethylpropyl acrolein)	CHG		O	C	III	A	No	N/A	No		G
Cyclohexanone	CCH	18	O	D	III	A	Yes	1	.56-1(a), (b)		G
Cyclohexanone, Cyclohexanol mixture	CYX	18 ²	O	E	III	A	Yes	1	.56-1 (b)		G



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Page 2 of 8

Shipyard: Trinity Ashland City

Hull #: 4772

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
Cyclohexylamine	CHA	7	O	D	III	A	Yes	1	.56-1(a), (b), (c), (g)	G
Cyclopentadiene, Styrene, Benzene mixture	CSB	30	O	D	III	A	Yes	1	.50-60, .56-1(b)	G
iso-Decyl acrylate	IAI	14	O	E	III	A	Yes	2	.50-70(a), .50-81(a), (b), .55-1(c)	G
Dichlorobenzene (all isomers)	DBX	36	O	E	III	A	Yes	3	.56-1(a), (b)	G
1,1-Dichloroethane	DCH	36	O	C	III	A	Yes	1	No	G
2,2'-Dichloroethyl ether	DEE	41	O	D	II	A	Yes	1	.55-1(f)	G
Dichloromethane	DCM	36	O	NA	III	A	Yes	5	No	G
2,4-Dichlorophenoxyacetic acid, diethanolamine salt solution	DDE	43	O	E	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, dimethylamine salt solution	DAD	0 1,2	O	A	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
2,4-Dichlorophenoxyacetic acid, triisopropanolamine salt solution	DTI	43 2	O	E	III	A	No	N/A	.56-1(a), (b), (c), (g)	G
1,1-Dichloropropane	DPB	36	O	C	III	A	Yes	3	No	G
1,2-Dichloropropane	DPP	36	O	C	III	A	Yes	3	No	G
1,3-Dichloropropane	DPC	36	O	C	III	A	Yes	3	No	G
1,3-Dichloropropene	DPU	15	O	D	II	A	Yes	4	No	G
Dichloropropene, Dichloropropane mixtures	DMX	15	O	C	II	A	Yes	1	No	G
Diethanolamine	DEA	8	O	E	III	A	Yes	1	.55-1(c)	G
Diethylamine	DEN	7	O	C	III	A	Yes	3	.55-1(c)	G
Diethylenetriamine	DET	7 2	O	E	III	A	Yes	1	.55-1(c)	G
Diisobutylamine	DBU	7	O	D	III	A	Yes	3	.55-1(c)	G
Diisopropanolamine	DIP	8	O	E	III	A	Yes	1	.55-1(c)	G
Diisopropylamine	DIA	7	O	C	II	A	Yes	3	.55-1(c)	G
N,N-Dimethylacetamide	DAC	10	O	E	III	A	Yes	3	.56-1(b)	G
Dimethylethanolamine	DMB	8	O	D	III	A	Yes	1	.56-1(b), (c)	G
Dimethylformamide	DMF	10	O	D	III	A	Yes	1	.55-1(e)	G
Di-n-propylamine	DNA	7	O	C	II	A	Yes	3	.55-1(c)	G
Dodecyldimethylamine, Tetradecyldimethylamine mixture	DOT	7	O	E	III	A	No	N/A	.56-1(b)	G
Dodecyl diphenyl ether disulfonate solution	DOS	43	O	#	II	A	No	N/A	No	G
EE Glycol Ether Mixture	EEG	40	O	D	III	A	No	N/A	No	G
Ethanolamine	MEA	8	O	E	III	A	Yes	1	.55-1(c)	G
Ethyl acrylate	EAC	14	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethylamine solution (72% or less)	EAN	7	O	A	II	A	Yes	6	.55-1(b)	G
N-Ethylbutylamine	EBA	7	O	D	III	A	Yes	3	.55-1(b)	G
N-Ethylcyclohexylamine	ECC	7	O	D	III	A	Yes	1	.55-1(b)	G
Ethylene cyanohydrin	ETC	20	O	E	III	A	Yes	1	No	G
Ethylenediamine	EDA	7 2	O	D	III	A	Yes	1	.55-1(c)	G
Ethylene dichloride	EDC	36 2	O	C	III	A	Yes	1	No	G
Ethylene glycol hexyl ether	EGH	40	O	E	III	A	No	N/A	No	G
Ethylene glycol monoalkyl ethers	EGC	40	O	D/E	III	A	Yes	1	No	G
Ethylene glycol propyl ether	EGP	40	O	E	III	A	Yes	1	No	G
2-Ethylhexyl acrylate	EAI	14	O	E	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Ethyl methacrylate	ETM	14	O	D/E	III	A	Yes	2	.50-70(a)	G
2-Ethyl-3-propylacrolein	EPA	19 2	O	E	III	A	Yes	1	No	G
Formaldehyde solution (37% to 50%)	FMS	19 2	O	D/E	III	A	Yes	1	.55-1(h)	G
Furfural	FFA	19	O	D	III	A	Yes	1	.55-1(h)	G
Glutaraldehyde solution (50% or less)	GTA	19	O	NA	III	A	No	N/A	No	G
Hexamethylenediamine solution	HMC	7	O	E	III	A	Yes	1	.55-1(c)	G
Hexamethyleneimine	HMI	7	O	C	II	A	Yes	1	.56-1(b), (c)	G
Hydrocarbon 5-9	HFN		O	C	III	A	Yes	1	.50-70(a), .50-81(a), (b)	G



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Page 3 of 8

Shipyard: Trinity Ashland City

Hull #: 4772

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat's of	Insp. Period
							App'd (Y or N)	VCS Category		
Isoprene	IPR	30	O	A	III	A	Yes	7	.50-70(a), .50-81(a), (b)	G
Isoprene, Pentadiene mixture	IPN		O	B	III	A	No	N/A	.50-70(a), .55-1(c)	G
Kraft pulping liquors (free alkali content 3% or more)(including: Black, Green, or White liquor)	KPL	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (g)	G
Mesityl oxide	MSO	18 ²	O	D	III	A	Yes	1	No	G
Methyl acrylate	MAM	14	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Methylcyclopentadiene dimer	MCK	30	O	C	III	A	Yes	1	No	G
Methyl diethanolamine	MDE	8	O	E	III	A	Yes	1	.56-1(b), (c)	G
2-Methyl-5-ethylpyridine	MEP	9	O	E	III	A	Yes	1	.55-1(e)	G
Methyl methacrylate	MMM	14	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
2-Methylpyridine	MPR	9	O	D	III	A	Yes	3	.55-1(c)	G
alpha-Methylstyrene	MSR	30	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Morpholine	MPL	7 ²	O	D	III	A	Yes	1	.55-1(c)	G
Nitroethane	NTE	42	O	D	II	A	No	N/A	.50-81, .56-1(b)	G
1- or 2-Nitropropane	NPM	42	O	D	III	A	Yes	1	.50-81	G
1,3-Pentadiene	PDE	30	O	A	III	A	Yes	7	.50-70(a), .50-81	G
Perchloroethylene	PER	36	O	NA	III	A	No	N/A	No	G
Phthalic anhydride (molten)	PAN	11	O	E	III	A	Yes	1	No	G
Polyethylene polyamines	PEB	7 ²	O	E	III	A	Yes	1	.55-1(e)	G
iso-Propanolamine	MPA	8	O	E	III	A	Yes	1	.55-1(c)	G
Propanolamine (iso-, n-)	PAX	8	O	E	III	A	Yes	1	.56-1(b), (c)	G
iso-Propylamine	IPP	7	O	A	II	A	Yes	5	.55-1(c)	G
Pyridine	PRD	9	O	C	III	A	Yes	1	.55-1(e)	G
Sodium acetate, Glycol, Water mixture (3% or more Sodium Hydroxide)	SAP		O		III	A	No	N/A	.50-73, .55-1(j)	G
Sodium aluminate solution (45% or less)	SAU	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b), (c)	G
Sodium chlorate solution (50% or less)	SDD	0 ^{1,2}	O	NA	III	A	No	N/A	.50-73	G
Sodium hypochlorite solution (20% or less)	SHQ	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (b)	G
Sodium sulfide, hydrosulfide solution (H2S 15 ppm or less)	SSH	0 ^{1,2}	O	NA	III	A	Yes	1	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 15 ppm but less than 200 ppm)	SSI	0 ^{1,2}	O	NA	III	A	No	N/A	.50-73, .55-1(b)	G
Sodium sulfide, hydrosulfide solution (H2S greater than 200 ppm)	SSJ	0 ^{1,2}	O	NA	II	A	No	N/A	.50-73, .55-1(b)	G
Styrene (crude)	STX		O	D	III	A	Yes	2	No	G
Styrene monomer	STY	30	O	D	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
1,1,2,2-Tetrachloroethane	TEC	36	O	NA	III	A	No	N/A	No	G
Tetraethylenepentamine	TTP	7	O	E	III	A	Yes	1	.55-1(c)	G
Tetrahydrofuran	THF	41	O	C	III	A	Yes	1	.50-70(b)	G
Toluenediamine	TDA	9	O	E	II	A	No	N/A	.50-73, .56-1(a), (b), (c), (g)	G
1,2,4-Trichlorobenzene	TCB	36	O	E	III	A	Yes	1	No	G
1,1,2-Trichloroethane	TCM	36	O	NA	III	A	Yes	1	.50-73, .56-1(a)	G
Trichloroethylene	TCL	36 ²	O	NA	III	A	Yes	1	No	G
1,2,3-Trichloropropane	TCN	36	O	E	II	A	Yes	3	.50-73, .56-1(a)	G
Triethanolamine	TEA	8 ²	O	E	III	A	Yes	1	.55-1(b)	G
Triethylamine	TEN	7	O	C	II	A	Yes	3	.55-1(e)	G
Triethylenetetramine	TET	7 ²	O	E	III	A	Yes	1	.55-1(b)	G
Triphenylborane (10% or less), caustic soda solution	TPB	5	O	NA	III	A	No	N/A	.56-1(a), (b), (c)	G
Trisodium phosphate solution	TSP	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c)	G
Urea, Ammonium nitrate solution (containing more than 2% NH3)	UAS	6	O	NA	III	A	No	N/A	.56-1(b)	G
Vanillin black liquor (free alkali content, 3% or more),	VLB	5	O	NA	III	A	No	N/A	.50-73, .56-1(a), (c), (g)	G



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Page 4 of 8

Shipyard: Trinity Ashland City

Hull #: 4772

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
Vinyl acetate	VAM	13	O	C	III	A	Yes	2	.50-70(a), .50-81(a), (b)	G
Vinyl neodecanate	VND	13	O	E	III	A	No	N/A	.50-70(a), .50-81(a), (b)	G
Vinyltoluene	VNT	13	O	D	III	A	Yes	2	.50-70(a), .50-81, .56-1(a), (b), (c), (	G

Subchapter D Cargoes Authorized for Vapor Control

Acetone	ACT	18 ²	D	C		A	Yes	1
Acetophenone	ACP	18	D	E		A	Yes	1
Alcohol(C12-C16) poly(1-6)ethoxylates	APU	20	D	E		A	Yes	1
Alcohol(C6-C17)(secondary) poly(7-12)ethoxylates	AEB	20	D	E		A	Yes	1
Amyl acetate (all isomers)	AEC	34	D	D		A	Yes	1
Amyl alcohol (iso-, n-, sec-, primary)	AAI	20	D	D		A	Yes	1
Benzyl alcohol	BAL	21	D	E		A	Yes	1
Brake fluid base mixtures (containing Poly(2-8)alkylene(C2-C3) glycols, Polyalkylene(C2-C10) glycol monoalkyl(C1-C4) ethers, and their borate esters)	BFX	20	D	E		A	Yes	1
Butyl acetate (all isomers)	BAX	34	D	D		A	Yes	1
Butyl alcohol (iso-)	IAL	20 ²	D	D		A	Yes	1
Butyl alcohol (n-)	BAN	20 ²	D	D		A	Yes	1
Butyl alcohol (sec-)	BAS	20 ²	D	C		A	Yes	1
Butyl alcohol (tert-)	BAT		D	C		A	Yes	1
Butyl benzyl phthalate	BPH	34	D	E		A	Yes	1
Butyl toluene	BUE	32	D	D		A	Yes	1
Caprolactam solutions	CLS	22	D	E		A	Yes	1
Cyclohexane	CHX	31	D	C		A	Yes	1
Cyclohexanol	CHN	20	D	E		A	Yes	1
1,3-Cyclopentadiene dimer (molten)	CPD	30	D	D/E		A	Yes	2
p-Cymene	CMP	32	D	D		A	Yes	1
iso-Decaldehyde	IDA	19	D	E		A	Yes	1
n-Decaldehyde	DAL	19	D	E		A	Yes	1
Decene	DCE	30	D	D		A	Yes	1
Decyl alcohol (all isomers)	DAX	20 ²	D	E		A	Yes	1
n-Decylbenzene, see Alkyl(C9+)benzenes	DBZ	32	D	E		A	Yes	1
Diacetone alcohol	DAA	20 ²	D	D		A	Yes	1
ortho-Dibutyl phthalate	DPA	34	D	E		A	Yes	1
Diethylbenzene	DEB	32	D	D		A	Yes	1
Diethylene glycol	DEG	40 ²	D	E		A	Yes	1
Diisobutylene	DBL	30	D	C		A	Yes	1
Diisobutyl ketone	DIK	18	D	D		A	Yes	1
Diisopropylbenzene (all isomers)	DIX	32	D	E		A	Yes	1
Dimethyl phthalate	DTL	34	D	E		A	Yes	1
Diethyl phthalate	DOP	34	D	E		A	Yes	1
Dipentene	DPN	30	D	D		A	Yes	1
Diphenyl	DIL	32	D	D/E		A	Yes	1
Diphenyl, Diphenyl ether mixtures	DDO	33	D	E		A	Yes	1
Diphenyl ether	DPE	41	D	{E}		A	Yes	1
Dipropylene glycol	DPG	40	D	E		A	Yes	1
Distillates: Flashed feed stocks	DFF	33	D	E		A	Yes	1
Distillates: Straight run	DSR	33	D	E		A	Yes	1
Dodecene (all isomers)	DOZ	30	D	D		A	Yes	1



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Page 5 of 8

Shipyard: Trinity Ashland City

Hull #: 4772

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ts of	Insp. Period
							App'd (Y or N)	VCS Category		
Dodecylbenzene, see Alkyl(C9+)benzenes	DDB	32	D	E		A	Yes	1		
2-Ethoxyethyl acetate	EEA	34	D	D		A	Yes	1		
Ethoxy triglycol (crude)	ETG	40	D	E		A	Yes	1		
Ethyl acetate	ETA	34	D	C		A	Yes	1		
Ethyl acetoacetate	EAA	34	D	E		A	Yes	1		
Ethyl alcohol	EAL	20 ²	D	C		A	Yes	1		
Ethylbenzene	ETB	32	D	C		A	Yes	1		
Ethyl butanol	EBT	20	D	D		A	Yes	1		
Ethyl tert-butyl ether	EBE	41	D	C		A	Yes	1		
Ethyl butyrate	EBR	34	D	D		A	Yes	1		
Ethyl cyclohexane	ECY	31	D	D		A	Yes	1		
Ethylene glycol	EGL	20 ²	D	E		A	Yes	1		
Ethylene glycol butyl ether acetate	EMA	34	D	E		A	Yes	1		
Ethylene glycol diacetate	EGY	34	D	E		A	Yes	1		
Ethylene glycol phenyl ether	EPE	40	D	E		A	Yes	1		
Ethyl-3-ethoxypropionate	EEP	34	D	D		A	Yes	1		
2-Ethylhexanol	EHX	20	D	E		A	Yes	1		
Ethyl propionate	EPR	34	D	C		A	Yes	1		
Ethyl toluene	ETE	32	D	D		A	Yes	1		
Formamide	FAM	10	D	E		A	Yes	1		
Furfuryl alcohol	FAL	20 ²	D	E		A	Yes	1		
Gasoline blending stocks: Alkylates	GAK	33	D	A/C		A	Yes	1		
Gasoline blending stocks: Reformates	GRF	33	D	A/C		A	Yes	1		
Gasolines: Automotive (containing not over 4.23 grams lead per gallon)	GAT	33	D	C		A	Yes	1		
Gasolines: Aviation (containing not over 4.86 grams of lead per gallon)	GAV	33	D	C		A	Yes	1		
Gasolines: Casinghead (natural)	GCS	33	D	A/C		A	Yes	1		
Gasolines: Polymer	GPL	33	D	A/C		A	Yes	1		
Gasolines: Straight run	GSR	33	D	A/C		A	Yes	1		
Glycerine	GCR	20 ²	D	E		A	Yes	1		
Heptane (all isomers), see Alkanes (C6-C9) (all isomers)	HMX	31	D	C		A	Yes	1		
Heptanoic acid	HEP	4	D	E		A	Yes	1		
Heptanol (all isomers)	HTX	20	D	D/E		A	Yes	1		
Heptene (all isomers)	HPX	30	D	C		A	Yes	2		
Heptyl acetate	HPE	34	D	E		A	Yes	1		
Hexane (all isomers), see Alkanes (C6-C9)	HXS	31 ²	D	B/C		A	Yes	1		
Hexanoic acid	HXO	4	D	E		A	Yes	1		
Hexanol	HXN	20	D	D		A	Yes	1		
Hexene (all isomers)	HEX	30	D	C		A	Yes	2		
Hexylene glycol	HXG	20	D	E		A	Yes	1		
Isophorone	IPH	18 ²	D	E		A	Yes	1		
Jet fuel: JP-4	JPF	33	D	E		A	Yes	1		
Jet fuel: JP-5 (kerosene, heavy)	JPV	33	D	D		A	Yes	1		
Kerosene	KRS	33	D	D		A	Yes	1		
Methyl acetate	MTT	34	D	D		A	Yes	1		
Methyl alcohol	MAL	20 ²	D	C		A	Yes	1		
Methylamyl acetate	MAC	34	D	D		A	Yes	1		
Methylamyl alcohol	MAA	20	D	D		A	Yes	1		

*** This document is only valid when attached to, and referenced by a current, valid Certificate of Inspection. ***



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: **CCL 403**

Official #: 1231311

Page 6 of 8

Shipyard: Trinity Ashland City

Hull #: 4772

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'l's of	Insp. Period
							App'd (Y or N)	VCS Category		
Methyl amyl ketone	MAK	18	D	D		A	Yes	1		
Methyl tert-butyl ether	MBE	41 ²	D	C		A	Yes	1		
Methyl butyl ketone	MBK	18	D	C		A	Yes	1		
Methyl butyrate	MBU	34	D	C		A	Yes	1		
Methyl ethyl ketone	MEK	18 ²	D	C		A	Yes	1		
Methyl heptyl ketone	MHK	18	D	D		A	Yes	1		
Methyl isobutyl ketone	MIK	18 ²	D	C		A	Yes	1		
Methyl naphthalene (molten)	MNA	32	D	E		A	Yes	1		
Mineral spirits	MNS	33	D	D		A	Yes	1		
Myrcene	MRE	30	D	D		A	Yes	1		
Naphtha: Heavy	NAG	33	D	#		A	Yes	1		
Naphtha: Petroleum	PTN	33	D	#		A	Yes	1		
Naphtha: Solvent	NSV	33	D	D		A	Yes	1		
Naphtha: Stoddard solvent	NSS	33	D	D		A	Yes	1		
Naphtha: Varnish makers and painters (75%)	NVM	33	D	C		A	Yes	1		
Nonane (all isomers), see Alkanes (C6-C9)	NAX	31	D	D		A	Yes	1		
Nonene (all isomers)	NON	30	D	D		A	Yes	2		
Nonyl alcohol (all isomers)	NNS	20 ²	D	E		A	Yes	1		
Nonyl phenol	NNP	21	D	E		A	Yes	1		
Nonyl phenol poly(4+)ethoxylates	NPE	40	D	E		A	Yes	1		
Octane (all isomers), see Alkanes (C6-C9)	OAX	31	D	C		A	Yes	1		
Octanoic acid (all isomers)	OAY	4	D	E		A	Yes	1		
Octanol (all isomers)	OCX	20 ²	D	E		A	Yes	1		
Octene (all isomers)	OTX	30	D	C		A	Yes	2		
Oil, fuel: No. 2	OTW	33	D	D/E		A	Yes	1		
Oil, fuel: No. 2-D	OTD	33	D	D		A	Yes	1		
Oil, fuel: No. 4	OFR	33	D	D/E		A	Yes	1		
Oil, fuel: No. 5	OFV	33	D	D/E		A	Yes	1		
Oil, fuel: No. 6	OSX	33	D	E		A	Yes	1		
Oil, misc: Crude	OIL	33	D	C/D		A	Yes	1		
Oil, misc: Diesel	ODS	33	D	D/E		A	Yes	1		
Oil, misc: Gas, high pour	OGP	33	D	E		A	Yes	1		
Oil, misc: Lubricating	OLB	33	D	E		A	Yes	1		
Oil, misc: Residual	ORL	33	D	E		A	Yes	1		
Oil, misc: Turbine	OTB	33	D	E		A	Yes	1		
Pentane (all isomers)	PTY	31	D	A		A	Yes	5		
Pentene (all isomers)	PTX	30	D	A		A	Yes	5		
n-Pentyl propionate	PPE	34	D	D		A	Yes	1		
alpha-Pinene	PIO	30	D	D		A	Yes	1		
beta-Pinene	PIP	30	D	D		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether	PAG	40	D	E		A	Yes	1		
Poly(2-8)alkylene glycol monoalkyl(C1-C6) ether acetate	PAF	34	D	E		A	Yes	1		
Polybutene	PLB	30	D	E		A	Yes	1		
Polypropylene glycol	PGC	40	D	E		A	Yes	1		
iso-Propyl acetate	IAC	34	D	C		A	Yes	1		
n-Propyl acetate	PAT	34	D	C		A	Yes	1		
iso-Propyl alcohol	IPA	20 ²	D	C		A	Yes	1		
n-Propyl alcohol	PAL	20 ²	D	C		A	Yes	1		



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Page 7 of 8

Shipyard: Trinity Ashland City

Hull #: 4772

Cargo Identification						Conditions of Carriage				
Name	Chem Code	Compat Group No	Sub Chapter	Grade	Hull Type	Tank Group	Vapor Recovery		Special Requirements in 46 CFR 151 General and Mat'ls of	Insp. Period
							App'd (Y or N)	VCS Category		
Propylbenzene (all isomers)	PBY	32	D	D		A	Yes	1		
iso-Propylcyclohexane	IPX	31	D	D		A	Yes	1		
Propylene glycol	PPG	20 ²	D	E		A	Yes	1		
Propylene glycol methyl ether acetate	PGN	34	D	D		A	Yes	1		
Propylene tetramer	PTT	30	D	D		A	Yes	1		
Sulfolane	SFL	39	D	E		A	Yes	1		
Tetraethylene glycol	TTG	40	D	E		A	Yes	1		
Tetrahydronaphthalene	THN	32	D	E		A	Yes	1		
Toluene	TOL	32	D	C		A	Yes	1		
Tricresyl phosphate (less than 1% of the ortho isomer)	TCP	34	D	E		A	Yes	1		
Triethylbenzene	TEB	32	D	E		A	Yes	1		
Triethylene glycol	TEG	40	D	E		A	Yes	1		
Triethyl phosphate	TPS	34	D	E		A	Yes	1		
Trimethylbenzene (all isomers)	TRE	32	D	{D}		A	Yes	1		
Trixylenyl phosphate	TRP	34	D	E		A	Yes	1		
Undecene	UDC	30	D	D/E		A	Yes	1		
1-Undecyl alcohol	UND	20	D	E		A	Yes	1		
Xylenes (ortho-, meta-, para-)	XLX	32	D	D		A	Yes	1		



Certificate of Inspection

Cargo Authority Attachment

Vessel Name: CCL 403

Official #: 1231311

Page 8 of 8

Shipyard: Trinity Ashland

Hull #: 4772

Explanation of terms & symbols used in the Table:

Cargo Identification

Name	The proper shipping name as listed in 46 CFR Table 30.25-1, 46 CFR Table 151.05, and 46 CFR Part 153 Table 2.
Chem Code none	The three letter designation assigned to the cargo in the Chemical Hazards Response Information System (CHRIS) Manual. Certain mixtures of cargoes may not have a CHRIS Code assigned.
Compatability Group No.	The cargo reactive group number assigned for compatibility determinations in 46 CFR Part 150 Tables I and II. In accordance with 46 CFR 150.130, the Person-in-Charge of the barge is responsible for ensuring that the compatibility requirements of 46 CFR Part 150 are met. Cargoes must be checked for compatibility using the figures, tables, and appendices of 46 CFR 150 in conjunction with the assigned reactive group number.
Note 1	Because of the very high reactivity or unusual conditions of carriage or potential compatibility problems, this product is not assigned to a specific group in the Compatibility Chart. For additional compatibility information, contact Commandant (CG-3PSO-3), U.S. Coast Guard, 2100 Second Street, SW, Washington, DC 20593-0001. Telephone (202) 372-1425.
Note 2	See Appendix I to 46 CFR Part 150 - exceptions to the compatibility chart.
Subchapter Subchapter D Subchapter O Note 3	The subchapter in Title 46 Code of Federal Regulations under which the cargo has been classified. Those flammable and combustible liquids listed in 46 CFR Table 30.25-1. Those hazardous cargoes listed in 46 CFR Table 151.05 and 46 CFR Part 153 Table 2. Those cargoes listed in 46 CFR Part 153 Table 2 are non-regulated cargoes when carried in bulk on non-oceangoing barges.
Grade	The cargo classification assigned to each flammable or combustible liquid. Grades inside of "{ }" indicate a provisional assignment based upon literature sources which were not verified by manufacturers data. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
A, B, C	Flammable liquid cargoes, as defined in 46 CFR 30-10.22.
D, E	Combustible liquid cargoes, as defined in 46 CFR 30-10.15.
Note 4	The flammability/combustibility grade of these cargoes may vary depending upon the flashpoint and Reid vapor pressure. The Person-in-Charge shall verify the cargo grade based on Manufacturers data and ensure that the barge is authorized for carriage of that grade of cargo.
NA	Those subchapter O cargoes which are not classified as a flammable or combustible liquid.
#	No flammability/combustibility grade has been assigned yet, as the necessary flash point/vapor pressure data for such assignments are presently not available.
Hull Type I II III NA	The required barge hull classification for carriage of the specified Subchapter O hazardous material cargo, see 46 CFR 151.10-1. Designed to carry products which require the maximum preventive measures to preclude the uncontrolled release of the cargo. See 46 CFR 151.10-1(b)(1). Designed to carry products which require significant preventive measures to preclude the uncontrolled release of cargo. See 46 CFR 151.10-1(b)(3). Designed to carry products of sufficient hazard to require a moderate degree of control. See 46 CFR 151.10-1(b)(4). Not applicable to barges certificated under Subchapter D.

Conditions of Carriage

Tank Group	The vessel's tank group (as defined in Section 4) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.

Conditions of Carriage

Tank Group	The vessel's tank group (as defined under the "46 CFR Tank Group Characteristics" listed on page 1) which is authorized for carriage of the named cargo.
Vapor Recovery Approved (Y or N)	Yes: The vessel's VCS has been reviewed and approved by the MSC to control vapors of the specified cargo. No: The vessel's VCS has been reviewed and is not approved by the MSC to control vapors of the specified cargo.
VCS Category:	The specified cargo's provisional classification for vapor control systems.
Category 1	(No additional VCS requirements above those for benzene, gasolines and crude oil) All requirements applying to the handling of oil and hazardous materials in Titles 33 and 46 Code of Federal Regulations (CFR) apply to these cargoes. Those specifically dealing with vapor control systems are in 33 CFR 155.750, 33 CFR 156.120, 33 CFR 156.170, 46 CFR 35.35 and 46 CFR 39. The cargo tank venting system calculations (46 CFR 39.20-11) and the pressure drop calculations (46 CFR 39.30-1(b)) must use appropriate friction factors, vapor densities and vapor growth rates.
Category 2	(Polymerizes) Polymerization and residue build-up of these cargoes can adversely affect the vessel by fouling safety components and restricting vapor flow which could lead to cargo tank overpressurization. The vessel's owner must develop a method of ensuring all VCS safety components are functional and polymer build-up is not causing an unsafe condition due to increased pressure in the vapor control piping and cargo tanks. The method shall be acceptable to the local Officer in Charge, Marine Inspection. This is in addition to the requirements of Category 1. Please note that a material not normally considered a monomer can be a problem in detonation arrester.
Category 3	(Highly toxic) VCSs for these toxic cargoes cannot use a spill valve or rupture disk as the primary means to meet the overfill protection requirement of 46 CFR 39.20-9. This requirement is in addition to the requirements of Category 1.
Category 4	(Polymerizes and highly toxic) Must comply with requirements of Categories 1, 2 and 3.
Category 5	(High vapor pressure) VCS pressure drop calculations for cargoes with a vapor pressure greater than 14.7 psia at 115 F must take into account increased vapor-air mixture densities and vapor growth rates as compared to Category 1 cargoes. Consult the Marine Safety Center's VCS Guidelines for further information. This requirement is in addition to the requirements of Category 1.
Category 6	(High vapor pressure and highly toxic) Must comply with requirements of Categories 1, 3 and 5.
Category 7	(High vapor pressure and polymerizes) Must comply with requirements of Categories 1, 2 and 5.
none	The cargo has not been evaluated/classified for use in vapor control systems.



UNITED STATES OF AMERICA

DEPARTMENT OF HOMELAND SECURITY
UNITED STATES COAST GUARD

NATIONAL VESSEL DOCUMENTATION CENTER

CERTIFICATE OF DOCUMENTATION


VESSEL NAME CCL 403		OFFICIAL NUMBER 1231311	IMO OR OTHER NUMBER 4772	YEAR COMPLETED 2011	
HAILING PORT NEW ORLEANS LA		HULL MATERIAL STEEL		MECHANICAL PROPULSION NO	
GROSS TONNAGE 1619 GRT	NET TONNAGE 1619 NRT	LENGTH 297.5	BREADTH 54.0	DEPTH 12.0	
PLACE BUILT ASHLAND CITY TN					
OWNERS CHEM CARRIERS LLC COMPRISED OF ONE MEMBER			OPERATIONAL ENDORSEMENTS COASTWISE		
MANAGING OWNER CHEM CARRIERS LLC 1237 HIGHWAY 75 SUNSHINE LA 70780					
RESTRICTIONS NONE					
ENTITLEMENTS NONE					
REMARKS NONE					
ISSUE DATE NOVEMBER 18, 2025		THIS CERTIFICATE EXPIRES DECEMBER 31, 2026			
		 DIRECTOR, NATIONAL VESSEL DOCUMENTATION CENTER			



Certificate of Financial Responsibility (COFR)<https://www.uscg.mil/Mariners/National-Pollution-Funds-Center/COFRs/ECOFR-Active-Vessel-Status/>

Updated: 04/15/2026 1145

Vessel Name	Vin	Vst Vessel Type Desc	Vessel Type Code	Gross Tonnage	Case Control ID	Examiner ID	Operator Name	Effective Date	Expiration Date
CCL 1	D518612	TANKBARGE	50	812	841310	22	CHEM CARRIERS, L.L.C	9/2/2025	9/2/2028
CCL 2	D510107	TANKBARGE	50	855	841310	22	CHEM CARRIERS, L.L.C	6/23/2023	6/23/2026
CCL 3	D296363	TANKBARGE	50	822	841310	22	CHEM CARRIERS, L.L.C	10/3/2023	10/3/2026
CCL 4	D512519	TANKBARGE	50	860	841310	22	CHEM CARRIERS, L.L.C	4/7/2025	4/7/2028
CCL 6	D530996	TANKBARGE	50	798	841310	22	CHEM CARRIERS, L.L.C	1/26/2025	1/26/2028
CCL 7	D551980	TANKBARGE	50	773	841310	22	CHEM CARRIERS, L.L.C	11/27/2023	11/27/2026
CCL 8	D551982	TANKBARGE	50	773	841310	22	CHEM CARRIERS, L.L.C	9/27/2025	9/27/2028
CCL 9	D551983	TANKBARGE	50	773	841310	22	CHEM CARRIERS, L.L.C	2/19/2026	2/19/2029
CCL 10	D551979	TANKBARGE	50	773	841310	22	CHEM CARRIERS, L.L.C	12/12/2023	12/12/2026
CCL 11	D551976	TANKBARGE	50	773	841310	22	CHEM CARRIERS, L.L.C	9/29/2025	9/29/2028
CCL 14	D4497784	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	9/22/2025	9/22/2028
CCL 15	D1164452	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	3/1/2024	3/1/2027
CCL 16	D1164666	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	9/14/2024	9/14/2027
CCL 17	D1166179	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	12/19/2025	12/19/2028
CCL 18	D1168981	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	7/1/2023	7/1/2026
CCL 19	D1168980	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	8/24/2023	8/24/2026
CCL 20	D1191598	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	2/27/2025	2/27/2028
CCL 21	D1191599	TANKBARGE	50	793	841310	22	CHEM CARRIERS, L.L.C	2/26/2025	2/26/2028
CCL 22	D1191600	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	1/13/2025	1/13/2028
CCL 23	D1191601	TANKBARGE	50	793	841310	22	CHEM CARRIERS, L.L.C	4/20/2025	4/20/2028
CCL 24	D1196547	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	8/11/2023	8/11/2026
CCL 25	D1196548	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	8/11/2023	8/11/2026
CCL 26	D1203816	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	2/11/2025	2/11/2028
CCL 27	D1203817	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	5/3/2024	5/3/2027
CCL 28	D1212828	TANKBARGE	50	793	841310	22	CHEM CARRIERS, L.L.C	9/9/2023	9/9/2026
CCL 29	D1212829	TANKBARGE	50	793	841310	22	CHEM CARRIERS, L.L.C	9/22/2023	9/22/2026
CCL 30	D1305871	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	10/1/2023	10/1/2026
CCL 31	D1305870	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	10/1/2023	10/1/2026
CCL 32	D1305869	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	11/13/2023	11/13/2026
CCL 33	D1305868	TANKBARGE	50	735	841310	22	CHEM CARRIERS, L.L.C	11/13/2023	11/13/2026
CCL 401	D1216671	TANKBARGE	50	2001	841310	22	CHEM CARRIERS, L.L.C	4/13/2024	4/13/2027
CCL 402	D1219910	TANKBARGE	50	1754	841310	22	CHEM CARRIERS, L.L.C	4/29/2024	4/29/2027
CCL 403	D1231311	TANKBARGE	50	1691	841310	22	CHEM CARRIERS, L.L.C	2/8/2026	2/8/2029
CCL 404	D1231312	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	2/23/2026	2/23/2029
CCL 405	D1236867	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	1/1/2024	1/1/2027
CCL 406	D1236866	TANKBARGE	50	1691	841310	22	CHEM CARRIERS, L.L.C	1/27/2024	1/27/2027
CCL 407	D1246320	TANKBARGE	50	1754	841310	22	CHEM CARRIERS, L.L.C	8/22/2025	8/22/2028
CCL 408	D1246097	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	8/7/2025	8/7/2028
CCL 409	D1246098	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	10/2/2025	10/2/2028
CCL 410	D1255906	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	9/3/2023	9/3/2026
CCL 411	D1255907	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	9/25/2023	9/25/2026
CCL 414-L	D1262941	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	9/23/2024	9/23/2027
CCL 415-T	D1262942	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	9/28/2024	9/28/2027
CCL 416-T	D1264691	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	1/20/2025	1/20/2028
CCL 417-T	D1298307	TANKBARGE	50	1769	841310	22	CHEM CARRIERS, L.L.C	12/19/2025	12/19/2028
CCL 418-L	D1306896	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	11/13/2023	11/13/2026
CCL 419-L	D1306897	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	1/5/2024	1/5/2027
CCL 420-T	D1348560	TANKBARGE	50	1619	841310	22	CHEM CARRIERS, L.L.C	2/12/2025	2/12/2028
CCL 421-T	D1352615	TANKBARGE	50	1616	841310	22	CHEM CARRIERS, L.L.C	8/28/2025	8/28/2028
CCL 424-T	D1359105	TANKBARGE	50	1616	841310	22	CHEM CARRIERS, L.L.C	3/12/2026	3/12/2029
AX 3202	D1089031	TANKBARGE	50	1754	841310	22	CHEM CARRIERS, L.L.C	6/11/2024	6/11/2027
MERLIN BANTA	D249614	TUG AND TOWBOAT	51	384	841310	22	CHEM CARRIERS, L.L.C	11/24/2024	11/24/2027



LYNCHBURG SHIPYARD
999 Independence Pkwy N.
Baytown, TX 77520

BARGE VAPOR TIGHTNESS TEST SHEET

THE FOLLOWING BARGE WAS TESTED IN ACCORDING WITH THE NATIONAL EMISSION STANDARD FOR BENZENE EMISSIONS FROM TRANSFER OPERATIONS, SECTION 40 CFR, 61.304 (F), AND NATION EMISSIONS STANDARDS FOR HAZARDOUS AIR POLLUTANTS SECTION 40 CFR 63.565 (C).

Barge Name: CCL - 403 Official# 1231311

Barge Owner: chem carriers LLC

Owner Address: 1237 Highway 75 Sunshine LA 70780

Date of Test: 7 - 29 - 26 Name of Tester: Karim Mendez

Witnessing Inspector: ☒ Juan Serrano ☐ Juan Maldonado ☐ Angel Arredondo

Inspector Signature: [Signature]

TEST RESULTS

This barge has been tested at this facility in accordance to Section 61.304 (f), and section 63.565 (c) and is considered to be vapor-tight.

Signature of Tester: [Signature]

Time Started: 13:00 Time Completed: 13:30

Starting Pressure: 27.7 Ending Pressure: 27.7

Allowable Pressure Loss: 1.0

TRANSFER SYSTEM TESTING DATA

The Pipeline System was hydro tested at 187.50 P.S.I. 7 - 29 - 26

The Pressure Relief Valve was hydro tested at 125 P.S.I. 7 - 29 - 26


The Load Line was hydro tested at 187.50 P.S.I. 7 - 29 - 26

The Steam Line was hydro tested at 125 P.S.I. N/A

Lynchburg Shipyard Supervisor

[Signature]
SIGNATURE

7 - 29 - 26
DATE



DECK PLAN

CARGO SYSTEM

- V01 CARGO PUMP SUCTION VALVE
- V02 CARGO PUMP DISCHARGE VALVE
- V03 CARGO PUMP RELIEF VALVE
- V04 CARGO PUMP BYPASS VALVE
- V05 PORT TRANS CARGO HDR BLOCK VALVE
- V06 STBD TRANS CARGO HDR BLOCK VALVE
- V07 CARGO LOADING VALVE
- V08 CARGO SUCTION VALVE-TANK #1S
- V09 CARGO SUCTION VALVE-TANK #1P
- V10 CARGO SUCTION VALVE-TANK #2S
- V11 CARGO SUCTION VALVE-TANK #2P
- V12 CARGO SUCTION VALVE-TANK #3S
- V13 CARGO SUCTION VALVE-TANK #3P
- V14 CARGO SUCTION VALVE-TANK #3P


VAPOR SYSTEM

- V15 STBD TRANS VAPOR HDR BLOCK VALVE
- V16 PORT TRANS VAPOR HDR BLOCK VALVE
- V17 VAPOR P/V VALVE
- V18 VAPOR P/V VALVE

STRIPPING SYSTEM

- V19 STRIPPING VALVE-CARGO HEADER
- V20 STRIPPING VALVE-TANK #1P
- V21 STRIPPING VALVE-TANK #1S
- V22 STRIPPING VALVE-TANK #2P
- V23 STRIPPING VALVE-TANK #2S
- V24 STRIPPING VALVE-TANK #3P
- V25 STRIPPING VALVE-TANK #3S
- V26 STRIPPING VALVE-CARGO PUMPWELL

REV	AS-BUILT	DESCRIPTION	DATE	BY
1	AS-BUILT	DESCRIPTION	DATE	BY
2	AS-BUILT	DESCRIPTION	DATE	BY
3	AS-BUILT	DESCRIPTION	DATE	BY
4	AS-BUILT	DESCRIPTION	DATE	BY
5	AS-BUILT	DESCRIPTION	DATE	BY
6	AS-BUILT	DESCRIPTION	DATE	BY
7	AS-BUILT	DESCRIPTION	DATE	BY
8	AS-BUILT	DESCRIPTION	DATE	BY
9	AS-BUILT	DESCRIPTION	DATE	BY
10	AS-BUILT	DESCRIPTION	DATE	BY
11	AS-BUILT	DESCRIPTION	DATE	BY
12	AS-BUILT	DESCRIPTION	DATE	BY
13	AS-BUILT	DESCRIPTION	DATE	BY
14	AS-BUILT	DESCRIPTION	DATE	BY
15	AS-BUILT	DESCRIPTION	DATE	BY
16	AS-BUILT	DESCRIPTION	DATE	BY
17	AS-BUILT	DESCRIPTION	DATE	BY
18	AS-BUILT	DESCRIPTION	DATE	BY
19	AS-BUILT	DESCRIPTION	DATE	BY
20	AS-BUILT	DESCRIPTION	DATE	BY
21	AS-BUILT	DESCRIPTION	DATE	BY
22	AS-BUILT	DESCRIPTION	DATE	BY
23	AS-BUILT	DESCRIPTION	DATE	BY
24	AS-BUILT	DESCRIPTION	DATE	BY
25	AS-BUILT	DESCRIPTION	DATE	BY
26	AS-BUILT	DESCRIPTION	DATE	BY
27	AS-BUILT	DESCRIPTION	DATE	BY
28	AS-BUILT	DESCRIPTION	DATE	BY
29	AS-BUILT	DESCRIPTION	DATE	BY
30	AS-BUILT	DESCRIPTION	DATE	BY
31	AS-BUILT	DESCRIPTION	DATE	BY
32	AS-BUILT	DESCRIPTION	DATE	BY
33	AS-BUILT	DESCRIPTION	DATE	BY
34	AS-BUILT	DESCRIPTION	DATE	BY
35	AS-BUILT	DESCRIPTION	DATE	BY
36	AS-BUILT	DESCRIPTION	DATE	BY
37	AS-BUILT	DESCRIPTION	DATE	BY
38	AS-BUILT	DESCRIPTION	DATE	BY
39	AS-BUILT	DESCRIPTION	DATE	BY
40	AS-BUILT	DESCRIPTION	DATE	BY
41	AS-BUILT	DESCRIPTION	DATE	BY
42	AS-BUILT	DESCRIPTION	DATE	BY
43	AS-BUILT	DESCRIPTION	DATE	BY
44	AS-BUILT	DESCRIPTION	DATE	BY
45	AS-BUILT	DESCRIPTION	DATE	BY
46	AS-BUILT	DESCRIPTION	DATE	BY
47	AS-BUILT	DESCRIPTION	DATE	BY
48	AS-BUILT	DESCRIPTION	DATE	BY
49	AS-BUILT	DESCRIPTION	DATE	BY
50	AS-BUILT	DESCRIPTION	DATE	BY
51	AS-BUILT	DESCRIPTION	DATE	BY
52	AS-BUILT	DESCRIPTION	DATE	BY
53	AS-BUILT	DESCRIPTION	DATE	BY
54	AS-BUILT	DESCRIPTION	DATE	BY
55	AS-BUILT	DESCRIPTION	DATE	BY
56	AS-BUILT	DESCRIPTION	DATE	BY
57	AS-BUILT	DESCRIPTION	DATE	BY
58	AS-BUILT	DESCRIPTION	DATE	BY
59	AS-BUILT	DESCRIPTION	DATE	BY
60	AS-BUILT	DESCRIPTION	DATE	BY
61	AS-BUILT	DESCRIPTION	DATE	BY
62	AS-BUILT	DESCRIPTION	DATE	BY
63	AS-BUILT	DESCRIPTION	DATE	BY
64	AS-BUILT	DESCRIPTION	DATE	BY
65	AS-BUILT	DESCRIPTION	DATE	BY
66	AS-BUILT	DESCRIPTION	DATE	BY
67	AS-BUILT	DESCRIPTION	DATE	BY
68	AS-BUILT	DESCRIPTION	DATE	BY
69	AS-BUILT	DESCRIPTION	DATE	BY
70	AS-BUILT	DESCRIPTION	DATE	BY
71	AS-BUILT	DESCRIPTION	DATE	BY
72	AS-BUILT	DESCRIPTION	DATE	BY
73	AS-BUILT	DESCRIPTION	DATE	BY
74	AS-BUILT	DESCRIPTION	DATE	BY
75	AS-BUILT	DESCRIPTION	DATE	BY
76	AS-BUILT	DESCRIPTION	DATE	BY
77	AS-BUILT	DESCRIPTION	DATE	BY
78	AS-BUILT	DESCRIPTION	DATE	BY
79	AS-BUILT	DESCRIPTION	DATE	BY
80	AS-BUILT	DESCRIPTION	DATE	BY
81	AS-BUILT	DESCRIPTION	DATE	BY
82	AS-BUILT	DESCRIPTION	DATE	BY
83	AS-BUILT	DESCRIPTION	DATE	BY
84	AS-BUILT	DESCRIPTION	DATE	BY
85	AS-BUILT	DESCRIPTION	DATE	BY
86	AS-BUILT	DESCRIPTION	DATE	BY
87	AS-BUILT	DESCRIPTION	DATE	BY
88	AS-BUILT	DESCRIPTION	DATE	BY
89	AS-BUILT	DESCRIPTION	DATE	BY
90	AS-BUILT	DESCRIPTION	DATE	BY
91	AS-BUILT	DESCRIPTION	DATE	BY
92	AS-BUILT	DESCRIPTION	DATE	BY
93	AS-BUILT	DESCRIPTION	DATE	BY
94	AS-BUILT	DESCRIPTION	DATE	BY
95	AS-BUILT	DESCRIPTION	DATE	BY
96	AS-BUILT	DESCRIPTION	DATE	BY
97	AS-BUILT	DESCRIPTION	DATE	BY
98	AS-BUILT	DESCRIPTION	DATE	BY
99	AS-BUILT	DESCRIPTION	DATE	BY
100	AS-BUILT	DESCRIPTION	DATE	BY





Marine Safety Center Vapor Control System (VCS) Plan Review Information Sheet (PRIS)



Vessel Name CCL 403 & CCL 404

Shipyard Trinity Ashland City

Official Number Pending

Hull Number 4772 & 4773

1. This sheet consolidates critical VCS parameters for MSC Staff Engineers and CG Field Inspectors dealing with Vapor Control Systems. CG Inspectors should verify the vessel's VCS design is consistent with the information listed in boxes 2, 6, 7 & 8 prior to updating the vapor control endorsement on the vessel's Certificate of Inspection. For cases where the information in the VCS PRIS does not reflect the vessel's design the CG Inspector should contact the MSC's Cargo Authority branch.

2. Tank Maximum Design Working Pressure 6.50 psig Raised Trunk ☒
Flush Deck ☐

3. Authorized Maximum Cargo Transfer Rate(s) 5000 bbl/hr loading
5000 bbl/hr discharging

4. Authorized Maximum Cargo Density 0.443 lbm/ft³

5. Authorized VCS Categories 1 through 7

6. Cargoes with the highest vapor density and/or pressure drop:

a. Cargo Name PENTANE

b. Cargo Name PENTANE

7. Pressure Vacuum Valve:

Manufacturer ERL
Size Superac Model II, 6 Inch
CG Approval 162.017/167/3

Settings in psig:

Pressure-side 6
Vacuum-side 3

8. VCS Pipe Sizes:

Approx. Inside Diameter
Longitudinal Header (inches) 8
Transverse Header (Inches) 8

Required Venting Capacity of Pressure-Side of P/V valve 16434 bbl/hr (air)

Required Venting Capacity of Vacuum-Side of P/V valve 5000 bbl/hr (air)

9. Tank Overfill Protection System (check appropriate box or boxes)

a. High Level/Tank Overfill Alarm ☒

Type ERL Level Alert II

b. Overfill Control Shutdown ☒

Type ERL Level Alert II

c. Spill Valve ☐

Type N/A

d. Rupture Disk ☐

Type N/A

Meets ASTM F1271 Setting in psig N/A

10. Closed Gauging Verify the vessel has closed gauging that satisfies 46 CFR 39.20-3 and 151.15-10(c).

11. Instructions/Guidelines for the OCMI:

11a. The following is the Marine Safety Center's recommended COI endorsement:

In accordance with 46 CFR Part 39, excluding part 39.40, this vessel's vapor collection system has been inspected to the plans approved by Marine Safety Center letter Serial # C1-110183 dated 21 January 2011, and has been found acceptable for the collection of bulk liquid cargo vapors annotated with "Yes" in the VCS column of the vessel's Cargo Authority Attachment, Serial # C1-1100183 dated 21 January 2011.

When the vessel is carrying cargoes containing greater than 0.5% benzene, the person in charge is responsible for ensuring the provisions of 46 US Code of Federal Regulations Part 197, Subpart C are applied.

11b. The MSC approval letter/s must be available at the OCMI's request.


11c. Verify isolation valve at the vapor connection flange is manually operable and designed in a way it is "clearly" open or closed.

11d. Previous applicable approval letters: None

VCS Approval Letter C1-1100183

MSC Plan Reviewer Mr. Marcus Ewardo

CCL 403 & CCL 404
 LIQUID TRANSFER RATE vs PRESSURE DROP
 BASED ON PRESSURE DROP FROM
 CARGO TANK #1 TO FACILITY CONNECTION



CARGO TRANSFER PROCEDURES

CHEM CARRIERS L.L.C.

TRANSFER FROM BARGE TO DOCK

PARTS

1. **PRODUCTS TRANSFERRED**
 2. **DESCRIPTION OF SYSTEM**
 3. **PERSONS ON DUTY**
 4. **PERSONS IN CHARGE**
 5. **EMERGENCY SHUTDOWN**
 6. **TOPPING OFF PROCEDURE**
 7. **COMPLETION OF TRANSFER**
 8. **REPORTING CARGO SPILLS**
 9. **VESSEL CLOSURES**
 10. **PRODUCT DATA**
 11. **Vapor Control Procedures**
- Barge CCL 403**

PARTS 1. PRODUCTS TRANSFERRED

33 CFR 155.750 (a) (1) (i)

This vessel is certificated for the carriage of grades "A" and lower Sub-Chapter (D) and (O) Products. It has also been certified to carry vapor products. Reference Certificate of Inspection.

PARTS 2. DESCRIPTION OF CARGO TRANSFER SYSTEM

33 CFR 155.750 (a) (2) (i) (ii)

The cargo transfer procedures apply to all Chem Carrier L.L.C. owned or leased tank barges. In most cases other than series built barges, the cargo piping arrangement is usually slightly different on every barge, and for this reason, the piping diagram must be studied before loading or discharging a barge. The basic concept for loading and discharging is fairly standard depending on the location of the pump.

A. (Reference the piping diagram for transfer system arrangement.)

B. PROCEDURES FOR THE CONTAINMENT SYSTEM

33 CFR 155.310 (a) (1) (iv)

33 CFR 155.750 (a) (2) (iii)

- 1). The containment pans are equipped with a drain for the removal of slops to shore facilities:

NEVER DRAIN THE CONTAINMENT TANKS ONTO THE DECK.

- 2). CCL 403 is equipped with a separate containment area for the cargo trunk top and the aft deck area. Each containment area

is equipped with drains and scupper plugs. Plugs should be installed prior to cargo transfer and removed after the cargo transfer is complete. PIC should notify Chem Carriers when containment areas need cleaning or if scupper plugs need replacing. **Never Drain Product captured in containment area overboard.**

PARTS 3. PERSONS ON DUTY DURING TRANSFER

33 CFR 155.750 (a) (3)

Number of persons required on duty during transfer operations:

- A. At no time during the transfer operation will be less than one responsible person on duty. The certified tankerman assigned shall be in charge and responsible for the safe transfer of cargo.

PARTS 4. PERSONS IN CHARGE

The tankerman (person in charge) is responsible for transferring cargo and carrying out related operations on board in an efficient, safe, and pollution free manner. The tankerman whether employed by the towboat, owner, operator, a shore tankerman service, or Chem Carriers L.L.C., shall comply with all Coast Guard, State and local regulations. Tankerman's responsibility shall include but not be limited to the following:

- A. To have on his/her person a valid merchant marine document endorsed as tankerman, certified to handle the grade of cargo to be transferred.
- B. Make a thorough inspection of the barge prior to the start of transfer operation.
- C. To have proper connection of the grounding cable.
- D. The vessel's moorings are adequate to hold during all expected conditions of surge, current, wind, tide, ect., and lines are long enough to allow for surge, tide, wind, changes in draft ect.
- E. Proper hose sizes, lengths, support, and connections.
- F. The condition of fire extinguishers and required number.
- G. The person in charge of transfer operations on the transferring vessel or facility and the person in charge of transferring operations on the receiving vessel or facility agree to begin the transfer operations.
- H. The transfer operation between tank barges and dock facilities should be lighted between sunset and sunrise to comply with the U. S. Coast Guard regulation pertaining to the displaying of lights on barges as required by Title 33.
- I. The PIC (PERSON IN CHARGE) will be responsible for the DOI (declaration of inspection) and DOS (declaration of security).
- J. Always maintain communications with dock or shore personnel with an agreed upon approved system.

PARTS 5: EMERGENCY SHUTDOWN

33 CFR 155.750 (a) (6)

THE EMERGENCY SHUTDOWN IS LOCATED NEAR THE CENTER OF THE BARGE.

- A. In the event of an emergency, transfer operations can be stopped by pulling the remote shutdown cable.
- B. Familiarize yourself with its location and operation prior to transfer.

PARTS 6; TOPPING OFF PROCEDURES

33 CFR 155.750 (a) (7)

In the process of topping off, tanks should be loaded at different levels to top off one at a time. Extra care should be taken to avoid over pressuring the connections, and hoses by closing valves against the receiving line. Since barges and facilities vary in their systems, no standard for topping off exist, but the following should be considered:

- A. The closing of one tank increases the rate of flow to other tanks on the same line.
- B. Always consider temperature and cargo in accordance with the amount of expansion that should be allowed.
- C. Always maintain communications with dock or shore personnel.
- D. A set of dipstick overfill devices have been installed on the CCL 403. Dipsticks can be made operational by releasing the covers or caps. Dipsticks should be used as a visual aid for overfill protection.

PARTS 7: COMPLETION OF TRANSFER

33 CFR 155.750 (a) (8)

Upon the completion of the transfer all pipelines should be drained into cargo tanks. The header valve used during the operation should then be closed, sealed off with a blind flange and shore personnel should seal lines and hatches on vessel.

PARTS 8: REPORTING CARGO SPILLS

33 CFR 155.750 (a) (9)

Should an accidental discharge of product occur, you should consider the following:

- A. Locate the source of the spill and try to stop it, if possible, and safe to do so.

- B. Make an attempt to contain the product if possible.
- C. Notify the Coast Guard. The national Response Center at 1-800-424-8802.
- E. Notify Chem Carriers L.L.C. at (225) 642-0060
- F. If loading, transfer the cargo from the leaking tank to an adjacent tank or back to the dock if safe to do so.
- G. If discharging, pump the product from the leaking tank as quickly as possible if safe to do so.

***When reporting a spill, the tankerman should provide the following information:**

- A. Name (his or her)
- B. Name of Company: (employed by; (contracted by;
- C. Name of Barge.
- D. Spill Location
- E. Specify Product.
- F. Estimate Quantity of Spill
- G. Weather, Tide, Sea and Current Conditions.
- H. Cause of Spill.
- I. Action Being Taken to Contain and Stop Spill

PART 9

CLOSURES ON VESSELS

Upon completion of cargo transfer operations, all tank hatch covers, ullage covers, and gauging device covers shall be dogged down and secured. In addition, the vent drain valves, if installed, should be secured and left in the proper position. All drain valves should be closed, and drip pan covers, if installed, should be made up tight. Covers for void spaces, bow and stern compartments shall be secured at all times and checked for tightness. Closing devices on clean-out hatches and clean-out opening should be checked, especially when the barge is loaded.

PART 10

PRODUCT DATA

See specific MSDS sheets provided with these procedures.

In case of any other emergency, immediately shut down and notify the transferring facility, and Chem Carriers L.L.C. (225) 642-0060 24 Hour Line.

PART 11

VAPOR CONTROL PROCEDURES

This is a guide only and is not intended to replace experience, sound judgment, and a proper assessment of the task at hand.

The tankerman on duty is the acting Designated Person In Charge (PIC) and is responsible for cargo transfer operations and carrying out related operations on barges.

1. Vapor Recovery Transfer Maximum Rate is 4000 BBLS/HR for

subchapter "D" Cargoes and 4000 BBLS/Hr for subchapter "O" Cargoes.

- 1.1 Transfer rates, which exceed these maximums, must be approved by Chem Carriers.
- 1.2 Transfer rates for each cargo tank should not exceed the maximum transfer rate.

2. Pre-transfer Inspection For Vapor Recovery Operations

2.1 Follow the procedures outlined below in addition to the procedures utilized during normal transfers:

2.1.1 Wear personal protective equipment (PPE) as needed for the cargo in the barge when testing P/V and, hooking up hoses, or draining low points.

2.1.2 Ensure that a Certificate of Vapor Tightness is onboard and valid.

2.1.3 Close the low point drain on the port/starboard vapor header, if applicable.

2.1.4 Close the low point drain near the vent stack, if applicable.

2.1.5 Close valve to the vent riser if applicable.

2.1.7 Blinds used for the vapor control manifold should have a hole to accommodate the ½" stud located in the vapor header.

2.1.8 Each cargo tank is fitted with a liquid level gauge stick. Remove the cap, raise the stick, This stick can be monitored visually to avoid overfilling.

2.1.9 Ensure that the last one meter (3.3 feet) of vapor piping before the vapor connection is painted red/yellow/red.

2.1.10 The cross-header should be stenciled with the word "VAPOR" in black letters at least 2" high.

2.1.11 The vapor connection flange should be fixed with a 1" long by 1/2" diameter stud projecting outward from the face of the flange, midway between bolt holes.

2.1.12 The high level alarms/shutdowns are installed near the center of each cargo tank. Dock alarm/shutdown should be connected prior to loading, and plugs located near the forward end of the barge Port and Starboard should be labeled "ALARM/SHUTDOWN SENSOR." High level alarms are set to alarm at 90% of the cargo tanks capacity and Shut downs are set to shut transfer down at 95% of each tanks capacity.

2.1.13 Ensure that the P/V relief valve flame screen, if required, is in place and in good condition prior to testing.

2.1.14 Ensure that the facility has a Letter of Adequacy endorsed as meeting the requirements of 33 CFR Subpart E.

3. Vapor Piping

3.1 The PIC checks the vapor piping diagram.

3.2 Characteristics of a vapor header:

3.2.1 The vapor collection piping system on tank barges is permanently installed and located as close as practical to the loading manifold. The piping system is electrically bonded to the hull and electrically continuous.

3.2.2 The last one meter (3.3 feet) of vapor piping prior to the valve before the vapor connection is painted red/yellow/red. The red bands are 4" wide and the yellow band is 32" wide.

3.2.3 The vapor header is stenciled with the word "VAPOR" in black letters at least 2" high.

3.2.4 The vapor connection flange is to be fixed with a 1" by 1/2" diameter stud projecting outward from the face of the flange. This stud is located at the top of the flange, midway between bolt holes.

3.2.5 When not in use, blank off the vapor headers using a blind flange with a bolt in every hole. Each blind flange used on the vapor piping has a hole drilled to accommodate the pin.

4. Inspection And Verification Of Vent Lines

4.1 The Person in Charge performs the following steps:

4.1.1 Checks the Certificate of Inspection on board the barge;

4.1.2 Locates polymerizing or inhibited cargoes in the section of the COI marked *Specific Hazardous Cargo Authority*;

4.1.3 Refers to the MSDS or Chemical Data Guide on board the vessel to determine what cargoes are subject to polymerization, or what cargoes are inhibited;

4.1.4 Locates the MSDS for the cargo and determines its toxicity and whether or not it is a polymerizing or inhibited cargo; and,

4.1.5 Notifies the Dispatcher and Field Supervisor when polymerization is suspected.

5. Any problems with the Vapor Control system must be reported immediately to the person in charge and Chem Carriers.

U.S. Department of
Homeland Security

United States
Coast Guard



Commandant
United States Coast Guard

2703 Martin Luther King Jr. Ave SE
Stop 7516
Washington, DC 20593-7516
Staff Symbol: CG-MER-4 (VRP)
Phone: (202) 372-1005
Fax: (202) 372-8376
Email: vrp@uscg.mil

16460
March 12, 2025

Chem Carriers, L.L.C.
C/O: FOREFRONT EMERGENCY MANAGEMENT, LP
ATTN: ALLIE MARTIN
1730 COTEAU ROAD
HOUMA, LA 70364

Dear Sir or Madam:

Your Vessel Response Plan (Control Number 56041), submitted to meet the requirements of Title 33, Code of Federal Regulations (CFR), Part 155, Subparts D and I, is **approved**. Approval will remain valid until **March 21, 2030**.

The CCL 403 (1231311) is authorized to operate only in the ports or geographic areas indicated in the Captain of the Port zones listed below. If carrying oil as cargo, the vessel is prohibited from handling, storing, transporting, transferring, or lightering oil unless it is operating in full compliance with this plan. Compliance includes ensuring that required resources have been identified and planned for or are in place and available through contract or other approved means. If applicable to your routes, this includes the dispersant and aerial observation requirements of 33 CFR 155.1050.

You are reminded that your chosen salvage and marine firefighting resource provider may have submitted waivers from meeting one or more of the specified response times in accordance with 33 CFR 155.4055. If so, this may be rescinded by the U.S. Coast Guard if the appropriate response resources are not available when the approved waiver expires. You shall continue to assess the adequacy of your chosen salvors and firefighters as required by 33 CFR 155.4050.

The vessel must keep a copy of this approval letter onboard in addition to the minimum sections of the plan as required by 33 CFR 155.1030. In accordance with 33 CFR 155.1070, you are required to review your plan annually and submit plan amendments for approval. As per 33 CFR 155.1070(b), the entire plan must be resubmitted for a comprehensive review and approval six (6) months prior to the expiration date.

APPROVED CAPTAIN OF THE PORT ZONES

CORPUS CHRISTI
HOUMA
HOUSTON-GALVESTON

LOWER MISSISSIPPI RIVER OHIO VALLEY
(MEMPHIS) PORT ARTHUR AND LAKE
MOBILE CHARLES
NEW ORLEANS

UPPER MISSISSIPPI RIVER
(ST. LOUIS)

Sincerely,



CHARRON MCCOMBS

Lieutenant Commander

Acting Chief, Domestic Preparedness & Planning Division

U.S. Coast Guard

By direction

U.S. Department of
Homeland Security

United States
Coast Guard



Commanding Officer
United States Coast Guard
Marine Safety Center

US Coast Guard Stop 7430
2703 Martin Luther King Jr. Ave. SE
Washington, DC 20593-7430
Staff Symbol: MSC-5
Phone: (202) 795-6729
Email: securityplaninfo@uscg.mil

16710
VS-326893
December 3, 2024

Chem Carriers, LLC
Attn: Robert Banta
1237 Hwy 75
Sunshine, LA 70780
robert@chemcarriers.com

Subj: CHEM CARRIERS, LLC VESSELS
VESSEL SECURITY PLAN APPROVAL WITH AMENDMENTS

Ref: (a) Your correspondence dated November 6, 2024
(b) Title 33 Code of Federal Regulations (CFR) Part 104
(c) MSC Vessel Security Plan Approval letter dated October 16, 2024

Dear Mr. Banta:

We have conducted a review of the Vessel Security Plan (VSP) submitted with reference (a) in accordance with reference (b) and it is **"Approved."**

Your vessel must operate in compliance with this approved VSP and the requirements contained in reference (b). You are reminded to immediately report any deviation from this approved plan to the local Captain of the Port (COTP)/Officer in Charge, Marine Inspection (OCMI).

This approval will remain valid until five years from the date of reference (c) unless rescinded in writing by the local COTP/OCMI. You must review your plan annually and submit any amendments to this office for approval. Please ensure that a copy of the VSP is maintained on board the vessel if manned, or, if unmanned, at a suitable secure location so that it is readily available during an emergency or security incident. You shall make available to the Coast Guard, upon request, this letter, the VSP and any information related to the implementation of the VSP. Our Case Number for this plan is 326893. Please ensure that all future correspondence includes this Case Number.

Sincerely,

K. C. WILLIAMS
Lieutenant Commander, U.S. Coast Guard
Chief, Vessel Security Division
By direction

Enclosures: (1) List of Vessel Security Plan Amendments
(2) List of Vessels Covered


List of Vessels Covered

<u>Vessel Name</u>	<u>Official Number (O.N.)</u>
CCL-1	518612
CCL 2	510107
CCL-3	296363
CCL 4	512519
CCL-5	512520
CCL-6	530996
CCL7	551980
CCL 8	551982
CCL 9	551983
CCL 10	551979
CCL 11	551976
CCL 14	1164451
CCL 15	1164452
CCL 16	1164666
CCL 17	1166179
CCL 18	1168981
CCL 19	1168980
CCL 20	1191598
CCL 21	1191599
CCL 22	1191600
CCL 23	1191601
CCL 24	1196547
CCL 25	1196548
CCL 26	1203816
CCL 27	1203817
CCL 28	1212828
CCL 29	1212829
CCL 30	1305871
CCL 31	1305870
CCL 32	1305869
CCL 33	1305868
CCL 401	1216671
CCL 402	1219910
CCL 403	1231311
CCL 404	1231312
CCL 405	1236867
CCL 406	1236866
CCL 407	1246320
CCL 408	1246097
CCL 409	1246098
CCL 410	1255906
CCL 411	1255907
CCL 414-L	1262941
CCL 415-T	1262942

<u>Vessel Name</u>	<u>Official Number (O.N.)</u>
CCL 416-T	1264691
CCL 417 T	1298307
CCL 418-L	1306896
CCL 419-L	1306897
CCL 420-T	1348560
CCL 421-T	CG1843359
CCL 3202	1089031
HFL 413	1237482
HFL 415	1237483
HFL 435	1236563
HFL 605	1237484


VESSEL INCIDENT / ACCIDENT NOTIFICATION CHART

Incidents that involve injury or illness, spill / pollution or a probable discharge, significant equipment failure, property damage, cargo related issues, service delays or any accident involving a Chem Carriers Towing, LLC vessel or crewmember shall be immediately called into the Chem Carriers Towing, LLC 24-hour Emergency Hotline at **225-642-0060**



Master Standing the Watch

Once the situation has been stabilized and all safety issues have been addressed, immediately contact the Chem Carriers Towing, LLC Emergency Hotline (225-642-0060)
Any serious marine incident, or any incident that has the potential to become a serious marine incident, alcohol testing shall be conducted on all involved crewmembers within 2 hours, whether onboard the vessel or at a testing facility.



NATIONAL Response Center

1-800-424-8802

or

1-202-267-2675

MADANTORY for all pollution incidents on CCT equipment

Chem Carriers Towing, LLC Emergency Hotline



Qualified Individual (QI)

225-642-0060

State Notifications




Louisiana 225-925-6595
Mississippi 601-987-1212
Texas 409-924-5400

Oil Spill Removal Organization Customer Internal

Reference Emergency Response Guidelines for
a Complete List of Required Notifications

USCG COTP ZONES

Baton Rouge 225-298-5400
New Orleans 504-365-2200
Morgan City 985-380-5320
Lake Charles 337-721-5741





BARGE "CCL 403" INNAGE TRIM TABLE

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
2 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8
3 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
3 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 5'-00"
 DIFF. = 3'-00" (DOWN BY STERN)

THE CORRECTION FOR 3'-00" TRIM DOWN BY STERN FOR 1 PORT IS 00-1/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 1 PORT, THE TRIM CORRECTED INNAGE IS 4'-00 1/8"

LENGTH BETWEEN DRAFT MARKS: 237'-06"

January 14, 2011

PRECISION MEASUREMENT

& ANALYSIS, INC.

P.O. Box 2092

Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "CCL 403"

1 PORT INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/2"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	789	0	13,128	0	27,877	0	42,830	0	57,835	0	72,867	0	87,899	0	102,930	0	117,962	0	132,987
1/4	950	1/4	13,420	1/4	28,191	1/4	43,141	1/4	58,149	1/4	73,180	1/4	88,212	1/4	103,244	1/4	118,275	1/4	133,300
1/2	1,111	1/2	13,711	1/2	28,504	1/2	43,452	1/2	58,462	1/2	73,493	1/2	88,525	1/2	103,557	1/2	118,588	1/2	133,613
3/4	1,272	3/4	14,003	3/4	28,817	3/4	43,763	3/4	58,775	3/4	73,807	3/4	88,838	3/4	103,870	3/4	118,902	3/4	133,926
1	1,432	1	14,295	1	29,130	1	44,074	1	59,088	1	74,120	1	89,151	1	104,183	1	119,215	1	134,240
1/4	1,652	1/4	14,591	1/4	29,443	1/4	44,385	1/4	59,401	1/4	74,433	1/4	89,465	1/4	104,496	1/4	119,528	1/4	134,553
1/2	1,872	1/2	14,887	1/2	29,756	1/2	44,697	1/2	59,714	1/2	74,746	1/2	89,778	1/2	104,809	1/2	119,841	1/2	134,866
3/4	2,091	3/4	15,182	3/4	30,070	3/4	45,008	3/4	60,027	3/4	75,059	3/4	90,091	3/4	105,123	3/4	120,154	3/4	135,179
2	2,311	2	15,478	2	30,383	2	45,319	2	60,341	2	75,372	2	90,404	2	105,436	2	120,467	2	135,492
1/4	2,563	1/4	15,778	1/4	30,696	1/4	45,631	1/4	60,654	1/4	75,685	1/4	90,717	1/4	105,749	1/4	120,780	1/4	135,805
1/2	2,814	1/2	16,077	1/2	31,009	1/2	45,942	1/2	60,967	1/2	75,999	1/2	91,030	1/2	106,062	1/2	121,093	1/2	136,118
3/4	3,066	3/4	16,377	3/4	31,322	3/4	46,254	3/4	61,280	3/4	76,312	3/4	91,344	3/4	106,375	3/4	121,406	3/4	136,431
3	3,318	3	16,677	3	31,635	3	46,566	3	61,593	3	76,625	3	91,657	3	106,688	3	121,719	3	136,744
1/4	3,575	1/4	16,980	1/4	31,948	1/4	46,878	1/4	61,906	1/4	76,938	1/4	91,970	1/4	107,002	1/4	122,032	1/4	137,057
1/2	3,832	1/2	17,284	1/2	32,260	1/2	47,190	1/2	62,220	1/2	77,251	1/2	92,283	1/2	107,315	1/2	122,345	1/2	137,370
3/4	4,088	3/4	17,587	3/4	32,573	3/4	47,502	3/4	62,533	3/4	77,564	3/4	92,596	3/4	107,628	3/4	122,658	3/4	137,683
4	4,345	4	17,891	4	32,886	4	47,814	4	62,846	4	77,878	4	92,909	4	107,941	4	122,971	4	137,996
1/4	4,606	1/4	18,198	1/4	33,196	1/4	48,127	1/4	63,159	1/4	78,191	1/4	93,222	1/4	108,254	1/4	123,284	1/4	138,309
1/2	4,867	1/2	18,505	1/2	33,507	1/2	48,441	1/2	63,472	1/2	78,504	1/2	93,536	1/2	108,567	1/2	123,597	1/2	138,622
3/4	5,128	3/4	18,813	3/4	33,818	3/4	48,754	3/4	63,785	3/4	78,817	3/4	93,849	3/4	108,881	3/4	123,910	3/4	138,935
5	5,389	5	19,120	5	34,129	5	49,067	5	64,099	5	79,130	5	94,162	5	109,194	5	124,223	5	139,248
1/4	5,653	1/4	19,431	1/4	34,439	1/4	49,380	1/4	64,412	1/4	79,443	1/4	94,475	1/4	109,507	1/4	124,536	1/4	139,561
1/2	5,918	1/2	19,742	1/2	34,750	1/2	49,693	1/2	64,725	1/2	79,757	1/2	94,788	1/2	109,820	1/2	124,849	1/2	139,874
3/4	6,183	3/4	20,052	3/4	35,061	3/4	50,006	3/4	65,038	3/4	80,070	3/4	95,101	3/4	110,133	3/4	125,162	3/4	140,187
6	6,448	6	20,363	6	35,372	6	50,320	6	65,351	6	80,383	6	95,415	6	110,446	6	125,475	6	140,500
1/4	6,716	1/4	20,676	1/4	35,682	1/4	50,633	1/4	65,664	1/4	80,696	1/4	95,728	1/4	110,759	1/4	125,788	1/4	140,813
1/2	6,985	1/2	20,989	1/2	35,993	1/2	50,946	1/2	65,978	1/2	81,009	1/2	96,041	1/2	111,073	1/2	126,101	1/2	141,126
3/4	7,254	3/4	21,302	3/4	36,304	3/4	51,259	3/4	66,291	3/4	81,322	3/4	96,354	3/4	111,386	3/4	126,414	3/4	141,439
7	7,522	7	21,614	7	36,615	7	51,572	7	66,604	7	81,636	7	96,667	7	111,699	7	126,727	7	141,752
1/4	7,795	1/4	21,928	1/4	36,926	1/4	51,885	1/4	66,917	1/4	81,949	1/4	96,980	1/4	112,012	1/4	127,040	1/4	142,065
1/2	8,067	1/2	22,241	1/2	37,236	1/2	52,198	1/2	67,230	1/2	82,262	1/2	97,294	1/2	112,325	1/2	127,353	1/2	142,378
3/4	8,340	3/4	22,554	3/4	37,547	3/4	52,512	3/4	67,543	3/4	82,575	3/4	97,607	3/4	112,638	3/4	127,666	3/4	142,691
8	8,613	8	22,867	8	37,858	8	52,825	8	67,856	8	82,888	8	97,920	8	112,952	8	127,979	8	143,004
1/4	8,889	1/4	23,180	1/4	38,169	1/4	53,138	1/4	68,170	1/4	83,201	1/4	98,233	1/4	113,265	1/4	128,292	1/4	143,317
1/2	9,165	1/2	23,493	1/2	38,479	1/2	53,451	1/2	68,483	1/2	83,515	1/2	98,546	1/2	113,578	1/2	128,605	1/2	143,630
3/4	9,442	3/4	23,807	3/4	38,790	3/4	53,764	3/4	68,796	3/4	83,828	3/4	98,859	3/4	113,891	3/4	128,918	3/4	143,943
9	9,718	9	24,120	9	39,101	9	54,077	9	69,109	9	84,141	9	99,173	9	114,204	9	129,231	9	144,256
1/4	9,998	1/4	24,433	1/4	39,412	1/4	54,391	1/4	69,422	1/4	84,454	1/4	99,486	1/4	114,517	1/4	129,544	1/4	144,569
1/2	10,279	1/2	24,746	1/2	39,722	1/2	54,704	1/2	69,735	1/2	84,767	1/2	99,799	1/2	114,831	1/2	129,857	1/2	144,882
3/4	10,559	3/4	25,059	3/4	40,033	3/4	55,017	3/4	70,049	3/4	85,080	3/4	100,112	3/4	115,144	3/4	130,170	3/4	145,195
10	10,839	10	25,372	10	40,344	10	55,330	10	70,362	10	85,393	10	100,425	10	115,457	10	130,483	10	145,508
1/4	11,123	1/4	25,685	1/4	40,655	1/4	55,643	1/4	70,675	1/4	85,707	1/4	100,738	1/4	115,770	1/4	130,796	1/4	145,821
1/2	11,407	1/2	25,999	1/2	40,965	1/2	55,956	1/2	70,988	1/2	86,020	1/2	101,051	1/2	116,083	1/2	131,109	1/2	146,134
3/4	11,692	3/4	26,312	3/4	41,276	3/4	56,270	3/4	71,301	3/4	86,333	3/4	101,365	3/4	116,396	3/4	131,422	3/4	146,447
11	11,976	11	26,625	11	41,587	11	56,583	11	71,614	11	86,646	11	101,678	11	116,710	11	131,735	11	146,760
1/4	12,264	1/4	26,938	1/4	41,898	1/4	56,896	1/4	71,928	1/4	86,959	1/4	101,991	1/4	117,023	1/4	132,048	1/4	147,073
1/2	12,552	1/2	27,251	1/2	42,209	1/2	57,209	1/2	72,241	1/2	87,272	1/2	102,304	1/2	117,336	1/2	132,361	1/2	147,386
3/4	12,840	3/4	27,564	3/4	42,519	3/4	57,522	3/4	72,554	3/4	87,586	3/4	102,617	3/4	117,649	3/4	132,674	3/4	147,699

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.

CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.

CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE.

GAUGE POINT: (HERMETIC) LOCATED 12'-09" OFF CENTERLINE AND 43'-06" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

1 PORT INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/2"

CAPACITIES GIVEN IN WHOLE GALLONS																			
IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	148,012	0	163,036	0	177,993	0	192,929	0	207,801	0		0		0		0		0	
1/4	148,325	1/4	163,349	1/4	178,304	1/4	193,241	1/4	208,092	1/4		1/4		1/4		1/4		1/4	
1/2	148,638	1/2	163,662	1/2	178,615	1/2	193,552	1/2	208,383	1/2		1/2		1/2		1/2		1/2	
3/4	148,951	3/4	163,975	3/4	178,926	3/4	193,863	3/4	208,675	3/4		3/4		3/4		3/4		3/4	
1	149,264	1	164,288	1	179,237	1	194,174	1	208,966	1		1		1		1		1	
1/4	149,577	1/4	164,601	1/4	179,549	1/4	194,485	1/4	209,225	1/4		1/4		1/4		1/4		1/4	
1/2	149,890	1/2	164,914	1/2	179,860	1/2	194,796	1/2	209,485	1/2		1/2		1/2		1/2		1/2	
3/4	150,203	3/4	165,227	3/4	180,171	3/4	195,108	3/4	209,745	3/4		3/4		3/4		3/4		3/4	
2	150,516	2	165,540	2	180,482	2	195,419	2	210,005	2		2		2		2		2	
1/4	150,829	1/4	165,853	1/4	180,793	1/4	195,730	1/4	210,212	1/4		1/4		1/4		1/4		1/4	
1/2	151,142	1/2	166,165	1/2	181,104	1/2	196,041	1/2	210,420	1/2		1/2		1/2		1/2		1/2	
3/4	151,455	3/4	166,478	3/4	181,416	3/4	196,352	3/4	210,627	3/4		3/4		3/4		3/4		3/4	
3	151,768	3	166,790	3	181,727	3	196,663	3	210,835	3		3		3		3		3	
1/4	152,081	1/4	167,101	1/4	182,038	1/4	196,975	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	152,394	1/2	167,413	1/2	182,349	1/2	197,286	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	152,707	3/4	167,724	3/4	182,660	3/4	197,597	3/4		3/4		3/4		3/4		3/4		3/4	
4	153,020	4	168,035	4	182,972	4	197,908	4		4		4		4		4		4	
1/4	153,333	1/4	168,346	1/4	183,283	1/4	198,219	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	153,646	1/2	168,657	1/2	183,594	1/2	198,531	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	153,959	3/4	168,968	3/4	183,905	3/4	198,842	3/4		3/4		3/4		3/4		3/4		3/4	
5	154,272	5	169,280	5	184,216	5	199,153	5		5		5		5		5		5	
1/4	154,585	1/4	169,591	1/4	184,527	1/4	199,464	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	154,898	1/2	169,902	1/2	184,839	1/2	199,775	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	155,211	3/4	170,213	3/4	185,150	3/4	200,086	3/4		3/4		3/4		3/4		3/4		3/4	
6	155,524	6	170,524	6	185,461	6	200,398	6		6		6		6		6		6	
1/4	155,837	1/4	170,836	1/4	185,772	1/4	200,709	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	156,150	1/2	171,147	1/2	186,083	1/2	201,020	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	156,463	3/4	171,458	3/4	186,395	3/4	201,331	3/4		3/4		3/4		3/4		3/4		3/4	
7	156,776	7	171,769	7	186,706	7	201,642	7		7		7		7		7		7	
1/4	157,089	1/4	172,080	1/4	187,017	1/4	201,954	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	157,402	1/2	172,391	1/2	187,328	1/2	202,265	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	157,715	3/4	172,703	3/4	187,639	3/4	202,576	3/4		3/4		3/4		3/4		3/4		3/4	
8	158,028	8	173,014	8	187,950	8	202,887	8		8		8		8		8		8	
1/4	158,341	1/4	173,325	1/4	188,262	1/4	203,198	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	158,654	1/2	173,636	1/2	188,573	1/2	203,509	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	158,967	3/4	173,947	3/4	188,884	3/4	203,821	3/4		3/4		3/4		3/4		3/4		3/4	
9	159,280	9	174,259	9	189,195	9	204,132	9		9		9		9		9		9	
1/4	159,593	1/4	174,570	1/4	189,506	1/4	204,443	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	159,906	1/2	174,881	1/2	189,818	1/2	204,754	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	160,219	3/4	175,192	3/4	190,129	3/4	205,065	3/4		3/4		3/4		3/4		3/4		3/4	
10	160,532	10	175,503	10	190,440	10	205,376	10		10		10		10		10		10	
1/4	160,845	1/4	175,814	1/4	190,751	1/4	205,684	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	161,158	1/2	176,126	1/2	191,062	1/2	205,992	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	161,471	3/4	176,437	3/4	191,373	3/4	206,300	3/4		3/4		3/4		3/4		3/4		3/4	
11	161,784	11	176,748	11	191,685	11	206,608	11		11		11		11		11		11	
1/4	162,097	1/4	177,059	1/4	191,996	1/4	206,906	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	162,410	1/2	177,370	1/2	192,307	1/2	207,204	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	162,723	3/4	177,681	3/4	192,618	3/4	207,503	3/4		3/4		3/4		3/4		3/4		3/4	

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 01/13/2011 CL - SW
CALCULATED: 01/14/2011 CL
PRINTED: 01/14/2011 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 01/2011

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

1 STBD
INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	789	0	13,128	0	27,877	0	42,866	0	57,890	0	72,921	0	87,953	0	102,985	0	118,017	0	133,042
1/4	950	1/4	13,420	1/4	28,191	1/4	43,178	1/4	58,203	1/4	73,235	1/4	88,266	1/4	103,298	1/4	118,330	1/4	133,355
1/2	1,111	1/2	13,711	1/2	28,504	1/2	43,490	1/2	58,516	1/2	73,548	1/2	88,579	1/2	103,611	1/2	118,643	1/2	133,668
3/4	1,272	3/4	14,003	3/4	28,817	3/4	43,802	3/4	58,829	3/4	73,861	3/4	88,893	3/4	103,924	3/4	118,956	3/4	133,981
1	1,432	1	14,295	1	29,130	1	44,114	1	59,142	1	74,174	1	89,206	1	104,237	1	119,269	1	134,294
1/4	1,652	1/4	14,591	1/4	29,443	1/4	44,426	1/4	59,456	1/4	74,487	1/4	89,519	1/4	104,551	1/4	119,582	1/4	134,607
1/2	1,872	1/2	14,887	1/2	29,756	1/2	44,739	1/2	59,769	1/2	74,800	1/2	89,832	1/2	104,864	1/2	119,895	1/2	134,920
3/4	2,091	3/4	15,182	3/4	30,070	3/4	45,051	3/4	60,082	3/4	75,114	3/4	90,145	3/4	105,177	3/4	120,209	3/4	135,233
2	2,311	2	15,478	2	30,383	2	45,363	2	60,395	2	75,427	2	90,458	2	105,490	2	120,522	2	135,546
1/4	2,563	1/4	15,778	1/4	30,696	1/4	45,676	1/4	60,708	1/4	75,740	1/4	90,772	1/4	105,803	1/4	120,835	1/4	135,859
1/2	2,814	1/2	16,077	1/2	31,009	1/2	45,990	1/2	61,021	1/2	76,053	1/2	91,085	1/2	106,116	1/2	121,148	1/2	136,172
3/4	3,066	3/4	16,377	3/4	31,322	3/4	46,303	3/4	61,335	3/4	76,366	3/4	91,398	3/4	106,430	3/4	121,461	3/4	136,485
3	3,318	3	16,677	3	31,635	3	46,616	3	61,648	3	76,679	3	91,711	3	106,743	3	121,774	3	136,798
1/4	3,575	1/4	16,980	1/4	31,948	1/4	46,929	1/4	61,961	1/4	76,993	1/4	92,024	1/4	107,056	1/4	122,087	1/4	137,111
1/2	3,832	1/2	17,284	1/2	32,261	1/2	47,242	1/2	62,274	1/2	77,306	1/2	92,337	1/2	107,369	1/2	122,400	1/2	137,424
3/4	4,088	3/4	17,587	3/4	32,574	3/4	47,555	3/4	62,587	3/4	77,619	3/4	92,651	3/4	107,682	3/4	122,713	3/4	137,737
4	4,345	4	17,891	4	32,887	4	47,869	4	62,900	4	77,932	4	92,964	4	107,995	4	123,026	4	138,050
1/4	4,606	1/4	18,198	1/4	33,198	1/4	48,182	1/4	63,213	1/4	78,245	1/4	93,277	1/4	108,309	1/4	123,339	1/4	138,363
1/2	4,867	1/2	18,505	1/2	33,510	1/2	48,495	1/2	63,527	1/2	78,558	1/2	93,590	1/2	108,622	1/2	123,652	1/2	138,676
3/4	5,128	3/4	18,813	3/4	33,822	3/4	48,808	3/4	63,840	3/4	78,871	3/4	93,903	3/4	108,935	3/4	123,965	3/4	138,989
5	5,389	5	19,120	5	34,134	5	49,121	5	64,153	5	79,185	5	94,216	5	109,248	5	124,278	5	139,302
1/4	5,653	1/4	19,431	1/4	34,446	1/4	49,434	1/4	64,466	1/4	79,498	1/4	94,530	1/4	109,561	1/4	124,591	1/4	139,615
1/2	5,918	1/2	19,742	1/2	34,758	1/2	49,748	1/2	64,779	1/2	79,811	1/2	94,843	1/2	109,874	1/2	124,904	1/2	139,928
3/4	6,183	3/4	20,052	3/4	35,069	3/4	50,061	3/4	65,092	3/4	80,124	3/4	95,156	3/4	110,188	3/4	125,217	3/4	140,241
6	6,448	6	20,363	6	35,381	6	50,374	6	65,406	6	80,437	6	95,469	6	110,501	6	125,530	6	140,554
1/4	6,716	1/4	20,676	1/4	35,693	1/4	50,687	1/4	65,719	1/4	80,750	1/4	95,782	1/4	110,814	1/4	125,843	1/4	140,867
1/2	6,985	1/2	20,989	1/2	36,005	1/2	51,000	1/2	66,032	1/2	81,064	1/2	96,095	1/2	111,127	1/2	126,156	1/2	141,180
3/4	7,254	3/4	21,302	3/4	36,317	3/4	51,313	3/4	66,345	3/4	81,377	3/4	96,408	3/4	111,440	3/4	126,469	3/4	141,493
7	7,522	7	21,614	7	36,629	7	51,627	7	66,658	7	81,690	7	96,722	7	111,753	7	126,782	7	141,806
1/4	7,795	1/4	21,928	1/4	36,941	1/4	51,940	1/4	66,971	1/4	82,003	1/4	97,035	1/4	112,066	1/4	127,095	1/4	142,119
1/2	8,067	1/2	22,241	1/2	37,252	1/2	52,253	1/2	67,285	1/2	82,316	1/2	97,348	1/2	112,380	1/2	127,408	1/2	142,432
3/4	8,340	3/4	22,554	3/4	37,564	3/4	52,566	3/4	67,598	3/4	82,629	3/4	97,661	3/4	112,693	3/4	127,721	3/4	142,745
8	8,613	8	22,867	8	37,876	8	52,879	8	67,911	8	82,943	8	97,974	8	113,006	8	128,034	8	143,058
1/4	8,889	1/4	23,180	1/4	38,188	1/4	53,192	1/4	68,224	1/4	83,256	1/4	98,287	1/4	113,319	1/4	128,347	1/4	143,371
1/2	9,165	1/2	23,493	1/2	38,500	1/2	53,506	1/2	68,537	1/2	83,569	1/2	98,601	1/2	113,632	1/2	128,660	1/2	143,684
3/4	9,442	3/4	23,807	3/4	38,812	3/4	53,819	3/4	68,850	3/4	83,882	3/4	98,914	3/4	113,945	3/4	128,973	3/4	143,997
9	9,718	9	24,120	9	39,123	9	54,132	9	69,164	9	84,195	9	99,227	9	114,259	9	129,286	9	144,310
1/4	9,998	1/4	24,433	1/4	39,435	1/4	54,445	1/4	69,477	1/4	84,508	1/4	99,540	1/4	114,572	1/4	129,599	1/4	144,623
1/2	10,279	1/2	24,746	1/2	39,747	1/2	54,758	1/2	69,790	1/2	84,822	1/2	99,853	1/2	114,885	1/2	129,912	1/2	144,936
3/4	10,559	3/4	25,059	3/4	40,059	3/4	55,071	3/4	70,103	3/4	85,135	3/4	100,166	3/4	115,198	3/4	130,225	3/4	145,249
10	10,839	10	25,372	10	40,371	10	55,384	10	70,416	10	85,448	10	100,480	10	115,511	10	130,538	10	145,562
1/4	11,123	1/4	25,685	1/4	40,683	1/4	55,698	1/4	70,729	1/4	85,761	1/4	100,793	1/4	115,824	1/4	130,851	1/4	145,875
1/2	11,407	1/2	25,999	1/2	40,994	1/2	56,011	1/2	71,042	1/2	86,074	1/2	101,106	1/2	116,138	1/2	131,164	1/2	146,188
3/4	11,692	3/4	26,312	3/4	41,306	3/4	56,324	3/4	71,356	3/4	86,387	3/4	101,419	3/4	116,451	3/4	131,477	3/4	146,501
11	11,976	11	26,625	11	41,618	11	56,637	11	71,669	11	86,701	11	101,732	11	116,764	11	131,790	11	146,814
1/4	12,264	1/4	26,938	1/4	41,930	1/4	56,950	1/4	71,982	1/4	87,014	1/4	102,045	1/4	117,077	1/4	132,103	1/4	147,127
1/2	12,552	1/2	27,251	1/2	42,242	1/2	57,263	1/2	72,295	1/2	87,327	1/2	102,359	1/2	117,390	1/2	132,416	1/2	147,440
3/4	12,840	3/4	27,564	3/4	42,554	3/4	57,577	3/4	72,608	3/4	87,640	3/4	102,672	3/4	117,703	3/4	132,729	3/4	147,753

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.

CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.

CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE.

GAUGE POINT: (HERMETIC) LOCATED 12'-09" OFF CENTERLINE AND 43'-06" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

1 STBD
INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/4"

IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	148,066	0	163,090	0	178,047	0	192,984	0	207,855	0		0		0		0		0	
1/4	148,379	1/4	163,403	1/4	178,358	1/4	193,295	1/4	208,146	1/4		1/4		1/4		1/4		1/4	
1/2	148,692	1/2	163,716	1/2	178,669	1/2	193,606	1/2	208,438	1/2		1/2		1/2		1/2		1/2	
3/4	149,005	3/4	164,029	3/4	178,981	3/4	193,917	3/4	208,729	3/4		3/4		3/4		3/4		3/4	
1	149,318	1	164,342	1	179,292	1	194,228	1	209,020	1		1		1		1		1	
1/4	149,631	1/4	164,655	1/4	179,603	1/4	194,540	1/4	209,280	1/4		1/4		1/4		1/4		1/4	
1/2	149,944	1/2	164,968	1/2	179,914	1/2	194,851	1/2	209,540	1/2		1/2		1/2		1/2		1/2	
3/4	150,257	3/4	165,281	3/4	180,225	3/4	195,162	3/4	209,799	3/4		3/4		3/4		3/4		3/4	
2	150,570	2	165,594	2	180,537	2	195,473	2	210,059	2		2		2		2		2	
1/4	150,883	1/4	165,907	1/4	180,848	1/4	195,784	1/4	210,266	1/4		1/4		1/4		1/4		1/4	
1/2	151,196	1/2	166,219	1/2	181,159	1/2	196,096	1/2	210,474	1/2		1/2		1/2		1/2		1/2	
3/4	151,509	3/4	166,532	3/4	181,470	3/4	196,407	3/4	210,682	3/4		3/4		3/4		3/4		3/4	
3	151,822	3	166,845	3	181,781	3	196,718	3	210,889	3		3		3		3		3	
1/4	152,135	1/4	167,156	1/4	182,092	1/4	197,029	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	152,448	1/2	167,467	1/2	182,404	1/2	197,340	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	152,761	3/4	167,778	3/4	182,715	3/4	197,651	3/4		3/4		3/4		3/4		3/4		3/4	
4	153,074	4	168,089	4	183,026	4	197,963	4		4		4		4		4		4	
1/4	153,387	1/4	168,400	1/4	183,337	1/4	198,274	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	153,700	1/2	168,712	1/2	183,648	1/2	198,585	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	154,013	3/4	169,023	3/4	183,959	3/4	198,896	3/4		3/4		3/4		3/4		3/4		3/4	
5	154,326	5	169,334	5	184,271	5	199,207	5		5		5		5		5		5	
1/4	154,639	1/4	169,645	1/4	184,582	1/4	199,518	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	154,952	1/2	169,956	1/2	184,893	1/2	199,830	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	155,265	3/4	170,268	3/4	185,204	3/4	200,141	3/4		3/4		3/4		3/4		3/4		3/4	
6	155,578	6	170,579	6	185,515	6	200,452	6		6		6		6		6		6	
1/4	155,891	1/4	170,890	1/4	185,827	1/4	200,763	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	156,204	1/2	171,201	1/2	186,138	1/2	201,074	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	156,517	3/4	171,512	3/4	186,449	3/4	201,386	3/4		3/4		3/4		3/4		3/4		3/4	
7	156,830	7	171,823	7	186,760	7	201,697	7		7		7		7		7		7	
1/4	157,143	1/4	172,135	1/4	187,071	1/4	202,008	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	157,456	1/2	172,446	1/2	187,382	1/2	202,319	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	157,769	3/4	172,757	3/4	187,694	3/4	202,630	3/4		3/4		3/4		3/4		3/4		3/4	
8	158,082	8	173,068	8	188,005	8	202,941	8		8		8		8		8		8	
1/4	158,395	1/4	173,379	1/4	188,316	1/4	203,253	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	158,708	1/2	173,691	1/2	188,627	1/2	203,564	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	159,021	3/4	174,002	3/4	188,938	3/4	203,875	3/4		3/4		3/4		3/4		3/4		3/4	
9	159,334	9	174,313	9	189,250	9	204,186	9		9		9		9		9		9	
1/4	159,647	1/4	174,624	1/4	189,561	1/4	204,497	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	159,960	1/2	174,935	1/2	189,872	1/2	204,808	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	160,273	3/4	175,246	3/4	190,183	3/4	205,120	3/4		3/4		3/4		3/4		3/4		3/4	
10	160,586	10	175,558	10	190,494	10	205,431	10		10		10		10		10		10	
1/4	160,899	1/4	175,869	1/4	190,805	1/4	205,739	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	161,212	1/2	176,180	1/2	191,117	1/2	206,047	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	161,525	3/4	176,491	3/4	191,428	3/4	206,354	3/4		3/4		3/4		3/4		3/4		3/4	
11	161,838	11	176,802	11	191,739	11	206,662	11		11		11		11		11		11	
1/4	162,151	1/4	177,114	1/4	192,050	1/4	206,961	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	162,464	1/2	177,425	1/2	192,361	1/2	207,259	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	162,777	3/4	177,736	3/4	192,673	3/4	207,557	3/4		3/4		3/4		3/4		3/4		3/4	

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 01/13/2011 CL - SW
CALCULATED: 01/14/2011 CL
PRINTED: 01/14/2011 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 01/2011

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

2 PORT INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 3/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	842	0	15,394	0	30,466	0	45,114	0	60,002	0	75,074	0	90,146	0	105,217	0	120,289	0	135,355
1/4	1,057	1/4	15,708	1/4	30,780	1/4	45,415	1/4	60,316	1/4	75,388	1/4	90,460	1/4	105,531	1/4	120,603	1/4	135,668
1/2	1,273	1/2	16,022	1/2	31,094	1/2	45,716	1/2	60,630	1/2	75,702	1/2	90,773	1/2	105,845	1/2	120,917	1/2	135,982
3/4	1,489	3/4	16,336	3/4	31,408	3/4	46,018	3/4	60,944	3/4	76,016	3/4	91,087	3/4	106,159	3/4	121,231	3/4	136,296
1	1,705	1	16,650	1	31,722	1	46,319	1	61,258	1	76,330	1	91,401	1	106,473	1	121,545	1	136,610
1/4	1,989	1/4	16,964	1/4	32,036	1/4	46,621	1/4	61,572	1/4	76,644	1/4	91,715	1/4	106,787	1/4	121,859	1/4	136,924
1/2	2,273	1/2	17,278	1/2	32,350	1/2	46,922	1/2	61,886	1/2	76,958	1/2	92,029	1/2	107,101	1/2	122,173	1/2	137,238
3/4	2,557	3/4	17,592	3/4	32,664	3/4	47,224	3/4	62,200	3/4	77,272	3/4	92,343	3/4	107,415	3/4	122,487	3/4	137,551
2	2,841	2	17,906	2	32,978	2	47,525	2	62,514	2	77,586	2	92,657	2	107,729	2	122,801	2	137,865
1/4	3,154	1/4	18,220	1/4	33,292	1/4	47,827	1/4	62,828	1/4	77,900	1/4	92,971	1/4	108,043	1/4	123,115	1/4	138,179
1/2	3,467	1/2	18,534	1/2	33,606	1/2	48,129	1/2	63,142	1/2	78,214	1/2	93,285	1/2	108,357	1/2	123,429	1/2	138,493
3/4	3,780	3/4	18,848	3/4	33,920	3/4	48,432	3/4	63,456	3/4	78,528	3/4	93,599	3/4	108,671	3/4	123,742	3/4	138,807
3	4,092	3	19,162	3	34,234	3	48,734	3	63,770	3	78,842	3	93,913	3	108,985	3	124,056	3	139,121
1/4	4,406	1/4	19,476	1/4	34,544	1/4	49,039	1/4	64,084	1/4	79,156	1/4	94,227	1/4	109,299	1/4	124,370	1/4	139,435
1/2	4,720	1/2	19,790	1/2	34,855	1/2	49,344	1/2	64,398	1/2	79,470	1/2	94,541	1/2	109,613	1/2	124,684	1/2	139,748
3/4	5,033	3/4	20,104	3/4	35,166	3/4	49,649	3/4	64,712	3/4	79,784	3/4	94,855	3/4	109,927	3/4	124,998	3/4	140,062
4	5,347	4	20,418	4	35,477	4	49,954	4	65,026	4	80,098	4	95,169	4	110,241	4	125,312	4	140,376
1/4	5,661	1/4	20,732	1/4	35,778	1/4	50,268	1/4	65,340	1/4	80,412	1/4	95,483	1/4	110,555	1/4	125,626	1/4	140,690
1/2	5,975	1/2	21,046	1/2	36,079	1/2	50,582	1/2	65,654	1/2	80,726	1/2	95,797	1/2	110,869	1/2	125,939	1/2	141,004
3/4	6,289	3/4	21,360	3/4	36,380	3/4	50,896	3/4	65,968	3/4	81,040	3/4	96,111	3/4	111,183	3/4	126,253	3/4	141,318
5	6,603	5	21,674	5	36,681	5	51,210	5	66,282	5	81,354	5	96,425	5	111,497	5	126,567	5	141,631
1/4	6,917	1/4	21,988	1/4	36,982	1/4	51,524	1/4	66,596	1/4	81,668	1/4	96,739	1/4	111,811	1/4	126,881	1/4	141,945
1/2	7,231	1/2	22,302	1/2	37,283	1/2	51,838	1/2	66,910	1/2	81,982	1/2	97,053	1/2	112,125	1/2	127,195	1/2	142,259
3/4	7,545	3/4	22,616	3/4	37,585	3/4	52,152	3/4	67,224	3/4	82,296	3/4	97,367	3/4	112,439	3/4	127,509	3/4	142,573
6	7,859	6	22,930	6	37,886	6	52,466	6	67,538	6	82,610	6	97,681	6	112,753	6	127,822	6	142,887
1/4	8,173	1/4	23,244	1/4	38,187	1/4	52,780	1/4	67,852	1/4	82,924	1/4	97,995	1/4	113,067	1/4	128,136	1/4	143,201
1/2	8,487	1/2	23,558	1/2	38,488	1/2	53,094	1/2	68,166	1/2	83,238	1/2	98,309	1/2	113,381	1/2	128,450	1/2	143,514
3/4	8,801	3/4	23,872	3/4	38,789	3/4	53,408	3/4	68,480	3/4	83,552	3/4	98,623	3/4	113,695	3/4	128,764	3/4	143,828
7	9,115	7	24,186	7	39,090	7	53,722	7	68,794	7	83,866	7	98,937	7	114,009	7	129,078	7	144,142
1/4	9,429	1/4	24,500	1/4	39,392	1/4	54,036	1/4	69,108	1/4	84,180	1/4	99,251	1/4	114,323	1/4	129,392	1/4	144,456
1/2	9,743	1/2	24,814	1/2	39,693	1/2	54,350	1/2	69,422	1/2	84,494	1/2	99,565	1/2	114,637	1/2	129,705	1/2	144,770
3/4	10,057	3/4	25,128	3/4	39,994	3/4	54,664	3/4	69,736	3/4	84,808	3/4	99,879	3/4	114,951	3/4	130,019	3/4	145,084
8	10,371	8	25,442	8	40,295	8	54,978	8	70,050	8	85,122	8	100,193	8	115,265	8	130,333	8	145,397
1/4	10,684	1/4	25,756	1/4	40,596	1/4	55,292	1/4	70,364	1/4	85,436	1/4	100,507	1/4	115,579	1/4	130,647	1/4	145,711
1/2	10,998	1/2	26,070	1/2	40,897	1/2	55,606	1/2	70,678	1/2	85,750	1/2	100,821	1/2	115,893	1/2	130,961	1/2	146,025
3/4	11,312	3/4	26,384	3/4	41,198	3/4	55,920	3/4	70,992	3/4	86,064	3/4	101,135	3/4	116,207	3/4	131,275	3/4	146,339
9	11,626	9	26,698	9	41,500	9	56,234	9	71,306	9	86,378	9	101,449	9	116,521	9	131,588	9	146,653
1/4	11,940	1/4	27,012	1/4	41,801	1/4	56,548	1/4	71,620	1/4	86,692	1/4	101,763	1/4	116,835	1/4	131,902	1/4	146,967
1/2	12,254	1/2	27,326	1/2	42,102	1/2	56,862	1/2	71,934	1/2	87,006	1/2	102,077	1/2	117,149	1/2	132,216	1/2	147,281
3/4	12,568	3/4	27,640	3/4	42,403	3/4	57,176	3/4	72,248	3/4	87,320	3/4	102,391	3/4	117,463	3/4	132,530	3/4	147,594
10	12,882	10	27,954	10	42,704	10	57,490	10	72,562	10	87,634	10	102,705	10	117,777	10	132,844	10	147,908
1/4	13,196	1/4	28,268	1/4	43,005	1/4	57,804	1/4	72,876	1/4	87,948	1/4	103,019	1/4	118,091	1/4	133,158	1/4	148,222
1/2	13,510	1/2	28,582	1/2	43,306	1/2	58,118	1/2	73,190	1/2	88,262	1/2	103,333	1/2	118,405	1/2	133,472	1/2	148,536
3/4	13,824	3/4	28,896	3/4	43,608	3/4	58,432	3/4	73,504	3/4	88,576	3/4	103,647	3/4	118,719	3/4	133,785	3/4	148,850
11	14,138	11	29,210	11	43,909	11	58,746	11	73,818	11	88,890	11	103,961	11	119,033	11	134,099	11	149,164
1/4	14,452	1/4	29,524	1/4	44,210	1/4	59,060	1/4	74,132	1/4	89,204	1/4	104,275	1/4	119,347	1/4	134,413	1/4	149,477
1/2	14,766	1/2	29,838	1/2	44,511	1/2	59,374	1/2	74,446	1/2	89,518	1/2	104,589	1/2	119,661	1/2	134,727	1/2	149,791
3/4	15,080	3/4	30,152	3/4	44,812	3/4	59,688	3/4	74,760	3/4	89,832	3/4	104,903	3/4	119,975	3/4	135,041	3/4	150,105

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.

CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.

CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE.

GAUGE POINT: (HERMETIC) LOCATED 12'-09" OFF CENTERLINE AND 43'-00" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT
& ANALYSIS, INC.

P.O. Box 2092

Pearland, Texas 77588

<http://www.pmacorp.net>



BARGE "CCL 403"

2 PORT INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 3/4"

IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	150,419	0	165,483	0	180,480	0	195,457	0	210,369	0		0		0		0		0	
1/4	150,733	1/4	165,797	1/4	180,792	1/4	195,769	1/4	210,661	1/4		1/4	1/4		1/4	1/4		1/4	
1/2	151,047	1/2	166,111	1/2	181,104	1/2	196,081	1/2	210,953	1/2		1/2	1/2		1/2	1/2		1/2	
3/4	151,360	3/4	166,425	3/4	181,416	3/4	196,393	3/4	211,245	3/4		3/4	3/4		3/4	3/4		3/4	
1	151,674	1	166,739	1	181,728	1	196,705	1	211,537	1		1	1		1		1		1
1/4	151,988	1/4	167,053	1/4	182,040	1/4	197,017	1/4	211,797	1/4		1/4	1/4		1/4	1/4		1/4	
1/2	152,302	1/2	167,366	1/2	182,352	1/2	197,329	1/2	212,058	1/2		1/2	1/2		1/2	1/2		1/2	
3/4	152,616	3/4	167,680	3/4	182,664	3/4	197,641	3/4	212,318	3/4		3/4	3/4		3/4	3/4		3/4	
2	152,930	2	167,994	2	182,976	2	197,953	2	212,579	2		2	2		2		2		2
1/4	153,244	1/4	168,307	1/4	183,288	1/4	198,265	1/4	212,787	1/4		1/4	1/4		1/4	1/4		1/4	
1/2	153,557	1/2	168,621	1/2	183,600	1/2	198,577	1/2	212,995	1/2		1/2	1/2		1/2	1/2		1/2	
3/4	153,871	3/4	168,934	3/4	183,912	3/4	198,889	3/4	213,203	3/4		3/4	3/4		3/4	3/4		3/4	
3	154,185	3	169,248	3	184,224	3	199,201	3	213,411	3		3	3		3		3		3
1/4	154,499	1/4	169,560	1/4	184,536	1/4	199,513	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	154,813	1/2	169,872	1/2	184,848	1/2	199,825	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	155,127	3/4	170,184	3/4	185,160	3/4	200,137	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
4	155,440	4	170,496	4	185,472	4	200,449	4		4		4	4		4		4		4
1/4	155,754	1/4	170,808	1/4	185,784	1/4	200,761	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	156,068	1/2	171,120	1/2	186,096	1/2	201,073	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	156,382	3/4	171,432	3/4	186,408	3/4	201,385	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
5	156,696	5	171,744	5	186,720	5	201,697	5		5		5	5		5		5		5
1/4	157,010	1/4	172,056	1/4	187,032	1/4	202,009	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	157,323	1/2	172,368	1/2	187,344	1/2	202,321	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	157,637	3/4	172,680	3/4	187,657	3/4	202,633	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
6	157,951	6	172,992	6	187,969	6	202,945	6		6		6	6		6		6		6
1/4	158,265	1/4	173,304	1/4	188,281	1/4	203,257	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	158,579	1/2	173,616	1/2	188,593	1/2	203,569	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	158,893	3/4	173,928	3/4	188,905	3/4	203,881	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
7	159,206	7	174,240	7	189,217	7	204,193	7		7		7	7		7		7		7
1/4	159,520	1/4	174,552	1/4	189,529	1/4	204,505	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	159,834	1/2	174,864	1/2	189,841	1/2	204,817	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	160,148	3/4	175,176	3/4	190,153	3/4	205,129	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
8	160,462	8	175,488	8	190,465	8	205,441	8		8		8	8		8		8		8
1/4	160,776	1/4	175,800	1/4	190,777	1/4	205,753	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	161,090	1/2	176,112	1/2	191,089	1/2	206,065	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	161,403	3/4	176,424	3/4	191,401	3/4	206,377	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
9	161,717	9	176,736	9	191,713	9	206,689	9		9		9	9		9		9		9
1/4	162,031	1/4	177,048	1/4	192,025	1/4	207,001	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	162,345	1/2	177,360	1/2	192,337	1/2	207,313	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	162,659	3/4	177,672	3/4	192,649	3/4	207,625	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
10	162,973	10	177,984	10	192,961	10	207,937	10		10		10	10		10		10		10
1/4	163,286	1/4	178,296	1/4	193,273	1/4	208,246	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	163,600	1/2	178,608	1/2	193,585	1/2	208,555	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	163,914	3/4	178,920	3/4	193,897	3/4	208,864	3/4		3/4		3/4	3/4		3/4	3/4		3/4	
11	164,228	11	179,232	11	194,209	11	209,173	11		11		11	11		11		11		11
1/4	164,542	1/4	179,544	1/4	194,521	1/4	209,472	1/4		1/4		1/4	1/4		1/4	1/4		1/4	
1/2	164,856	1/2	179,856	1/2	194,833	1/2	209,771	1/2		1/2		1/2	1/2		1/2	1/2		1/2	
3/4	165,169	3/4	180,168	3/4	195,145	3/4	210,070	3/4		3/4		3/4	3/4		3/4	3/4		3/4	

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 01/13/2011 CL - SW
CALCULATED: 01/14/2011 CL
PRINTED: 01/14/2011 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 01/2011

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

2 STBD INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 3/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	842	0	15,394	0	30,466	0	45,494	0	60,558	0	75,630	0	90,702	0	105,774	0	120,845	0	135,911
1/4	1,057	1/4	15,708	1/4	30,780	1/4	45,807	1/4	60,872	1/4	75,944	1/4	91,016	1/4	106,088	1/4	121,159	1/4	136,225
1/2	1,273	1/2	16,022	1/2	31,094	1/2	46,120	1/2	61,186	1/2	76,258	1/2	91,330	1/2	106,402	1/2	121,473	1/2	136,539
3/4	1,489	3/4	16,336	3/4	31,408	3/4	46,433	3/4	61,500	3/4	76,572	3/4	91,644	3/4	106,716	3/4	121,787	3/4	136,852
1	1,705	1	16,650	1	31,722	1	46,746	1	61,814	1	76,886	1	91,958	1	107,030	1	122,101	1	137,166
1/4	1,989	1/4	16,964	1/4	32,036	1/4	47,059	1/4	62,128	1/4	77,200	1/4	92,272	1/4	107,344	1/4	122,415	1/4	137,480
1/2	2,273	1/2	17,278	1/2	32,350	1/2	47,372	1/2	62,442	1/2	77,514	1/2	92,586	1/2	107,658	1/2	122,729	1/2	137,794
3/4	2,557	3/4	17,592	3/4	32,664	3/4	47,685	3/4	62,756	3/4	77,828	3/4	92,900	3/4	107,972	3/4	123,043	3/4	138,108
2	2,841	2	17,906	2	32,978	2	47,998	2	63,070	2	78,142	2	93,214	2	108,286	2	123,357	2	138,422
1/4	3,154	1/4	18,220	1/4	33,292	1/4	48,312	1/4	63,384	1/4	78,456	1/4	93,528	1/4	108,600	1/4	123,671	1/4	138,735
1/2	3,467	1/2	18,534	1/2	33,606	1/2	48,626	1/2	63,698	1/2	78,770	1/2	93,842	1/2	108,914	1/2	123,985	1/2	139,049
3/4	3,780	3/4	18,848	3/4	33,920	3/4	48,940	3/4	64,012	3/4	79,084	3/4	94,156	3/4	109,228	3/4	124,299	3/4	139,363
3	4,092	3	19,162	3	34,234	3	49,254	3	64,326	3	79,398	3	94,470	3	109,542	3	124,613	3	139,677
1/4	4,406	1/4	19,476	1/4	34,547	1/4	49,568	1/4	64,640	1/4	79,712	1/4	94,784	1/4	109,856	1/4	124,926	1/4	139,991
1/2	4,720	1/2	19,790	1/2	34,861	1/2	49,882	1/2	64,954	1/2	80,026	1/2	95,098	1/2	110,170	1/2	125,240	1/2	140,305
3/4	5,033	3/4	20,104	3/4	35,174	3/4	50,196	3/4	65,268	3/4	80,340	3/4	95,412	3/4	110,484	3/4	125,554	3/4	140,618
4	5,347	4	20,418	4	35,488	4	50,510	4	65,582	4	80,654	4	95,726	4	110,798	4	125,868	4	140,932
1/4	5,661	1/4	20,732	1/4	35,801	1/4	50,824	1/4	65,896	1/4	80,968	1/4	96,040	1/4	111,112	1/4	126,182	1/4	141,246
1/2	5,975	1/2	21,046	1/2	36,113	1/2	51,138	1/2	66,210	1/2	81,282	1/2	96,354	1/2	111,426	1/2	126,496	1/2	141,560
3/4	6,289	3/4	21,360	3/4	36,426	3/4	51,452	3/4	66,524	3/4	81,596	3/4	96,668	3/4	111,740	3/4	126,809	3/4	141,874
5	6,603	5	21,674	5	36,739	5	51,766	5	66,838	5	81,910	5	96,982	5	112,054	5	127,123	5	142,188
1/4	6,917	1/4	21,988	1/4	37,052	1/4	52,080	1/4	67,152	1/4	82,224	1/4	97,296	1/4	112,368	1/4	127,437	1/4	142,502
1/2	7,231	1/2	22,302	1/2	37,364	1/2	52,394	1/2	67,466	1/2	82,538	1/2	97,610	1/2	112,682	1/2	127,751	1/2	142,815
3/4	7,545	3/4	22,616	3/4	37,677	3/4	52,708	3/4	67,780	3/4	82,852	3/4	97,924	3/4	112,996	3/4	128,065	3/4	143,129
6	7,859	6	22,930	6	37,990	6	53,022	6	68,094	6	83,166	6	98,238	6	113,310	6	128,379	6	143,443
1/4	8,173	1/4	23,244	1/4	38,302	1/4	53,336	1/4	68,408	1/4	83,480	1/4	98,552	1/4	113,624	1/4	128,693	1/4	143,757
1/2	8,487	1/2	23,558	1/2	38,615	1/2	53,650	1/2	68,722	1/2	83,794	1/2	98,866	1/2	113,937	1/2	129,006	1/2	144,071
3/4	8,801	3/4	23,872	3/4	38,928	3/4	53,964	3/4	69,036	3/4	84,108	3/4	99,180	3/4	114,251	3/4	129,320	3/4	144,385
7	9,115	7	24,186	7	39,240	7	54,278	7	69,350	7	84,422	7	99,494	7	114,565	7	129,634	7	144,698
1/4	9,429	1/4	24,500	1/4	39,553	1/4	54,592	1/4	69,664	1/4	84,736	1/4	99,808	1/4	114,879	1/4	129,948	1/4	145,012
1/2	9,743	1/2	24,814	1/2	39,866	1/2	54,906	1/2	69,978	1/2	85,050	1/2	100,122	1/2	115,193	1/2	130,262	1/2	145,326
3/4	10,057	3/4	25,128	3/4	40,178	3/4	55,220	3/4	70,292	3/4	85,364	3/4	100,436	3/4	115,507	3/4	130,576	3/4	145,640
8	10,371	8	25,442	8	40,491	8	55,534	8	70,606	8	85,678	8	100,750	8	115,821	8	130,889	8	145,954
1/4	10,684	1/4	25,756	1/4	40,804	1/4	55,848	1/4	70,920	1/4	85,992	1/4	101,064	1/4	116,135	1/4	131,203	1/4	146,268
1/2	10,998	1/2	26,070	1/2	41,116	1/2	56,162	1/2	71,234	1/2	86,306	1/2	101,378	1/2	116,449	1/2	131,517	1/2	146,581
3/4	11,312	3/4	26,384	3/4	41,429	3/4	56,476	3/4	71,548	3/4	86,620	3/4	101,692	3/4	116,763	3/4	131,831	3/4	146,895
9	11,626	9	26,698	9	41,742	9	56,790	9	71,862	9	86,934	9	102,006	9	117,077	9	132,145	9	147,209
1/4	11,940	1/4	27,012	1/4	42,054	1/4	57,104	1/4	72,176	1/4	87,248	1/4	102,320	1/4	117,391	1/4	132,459	1/4	147,523
1/2	12,254	1/2	27,326	1/2	42,367	1/2	57,418	1/2	72,490	1/2	87,562	1/2	102,634	1/2	117,705	1/2	132,772	1/2	147,837
3/4	12,568	3/4	27,640	3/4	42,680	3/4	57,732	3/4	72,804	3/4	87,876	3/4	102,948	3/4	118,019	3/4	133,086	3/4	148,151
10	12,882	10	27,954	10	42,992	10	58,046	10	73,118	10	88,190	10	103,262	10	118,333	10	133,400	10	148,464
1/4	13,196	1/4	28,268	1/4	43,305	1/4	58,360	1/4	73,432	1/4	88,504	1/4	103,576	1/4	118,647	1/4	133,714	1/4	148,778
1/2	13,510	1/2	28,582	1/2	43,618	1/2	58,674	1/2	73,746	1/2	88,818	1/2	103,890	1/2	118,961	1/2	134,028	1/2	149,092
3/4	13,824	3/4	28,896	3/4	43,930	3/4	58,988	3/4	74,060	3/4	89,132	3/4	104,204	3/4	119,275	3/4	134,342	3/4	149,406
11	14,138	11	29,210	11	44,243	11	59,302	11	74,374	11	89,446	11	104,518	11	119,589	11	134,655	11	149,720
1/4	14,452	1/4	29,524	1/4	44,556	1/4	59,616	1/4	74,688	1/4	89,760	1/4	104,832	1/4	119,903	1/4	134,969	1/4	150,034
1/2	14,766	1/2	29,838	1/2	44,869	1/2	59,930	1/2	75,002	1/2	90,074	1/2	105,146	1/2	120,217	1/2	135,283	1/2	150,348
3/4	15,080	3/4	30,152	3/4	45,181	3/4	60,244	3/4	75,316	3/4	90,388	3/4	105,460	3/4	120,531	3/4	135,597	3/4	150,661

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.

CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.

CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE.

GAUGE POINT: (HERMETIC) LOCATED 12'-09" OFF CENTERLINE AND 43'-00" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

2 STBD INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 3/4"

CAPACITIES GIVEN IN WHOLE GALLONS																			
IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	150,975	0	166,040	0	181,036	0	196,013	0	210,925	0		0		0		0		0	
1/4	151,289	1/4	166,353	1/4	181,348	1/4	196,325	1/4	211,217	1/4		1/4		1/4		1/4		1/4	
1/2	151,603	1/2	166,667	1/2	181,660	1/2	196,637	1/2	211,509	1/2		1/2		1/2		1/2		1/2	
3/4	151,917	3/4	166,981	3/4	181,972	3/4	196,949	3/4	211,801	3/4		3/4		3/4		3/4		3/4	
1	152,231	1	167,295	1	182,284	1	197,261	1	212,093	1		1		1		1		1	
1/4	152,544	1/4	167,609	1/4	182,596	1/4	197,573	1/4	212,354	1/4		1/4		1/4		1/4		1/4	
1/2	152,858	1/2	167,923	1/2	182,909	1/2	197,885	1/2	212,614	1/2		1/2		1/2		1/2		1/2	
3/4	153,172	3/4	168,236	3/4	183,221	3/4	198,197	3/4	212,875	3/4		3/4		3/4		3/4		3/4	
2	153,486	2	168,550	2	183,533	2	198,509	2	213,135	2		2		2		2		2	
1/4	153,800	1/4	168,864	1/4	183,845	1/4	198,821	1/4	213,343	1/4		1/4		1/4		1/4		1/4	
1/2	154,114	1/2	169,177	1/2	184,157	1/2	199,133	1/2	213,551	1/2		1/2		1/2		1/2		1/2	
3/4	154,427	3/4	169,490	3/4	184,469	3/4	199,445	3/4	213,759	3/4		3/4		3/4		3/4		3/4	
3	154,741	3	169,804	3	184,781	3	199,757	3	213,968	3		3		3		3		3	
1/4	155,055	1/4	170,116	1/4	185,093	1/4	200,069	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	155,369	1/2	170,428	1/2	185,405	1/2	200,381	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	155,683	3/4	170,740	3/4	185,717	3/4	200,693	3/4		3/4		3/4		3/4		3/4		3/4	
4	155,997	4	171,052	4	186,029	4	201,005	4		4		4		4		4		4	
1/4	156,311	1/4	171,364	1/4	186,341	1/4	201,317	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	156,624	1/2	171,676	1/2	186,653	1/2	201,629	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	156,938	3/4	171,988	3/4	186,965	3/4	201,941	3/4		3/4		3/4		3/4		3/4		3/4	
5	157,252	5	172,300	5	187,277	5	202,253	5		5		5		5		5		5	
1/4	157,566	1/4	172,612	1/4	187,589	1/4	202,566	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	157,880	1/2	172,924	1/2	187,901	1/2	202,878	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	158,194	3/4	173,236	3/4	188,213	3/4	203,190	3/4		3/4		3/4		3/4		3/4		3/4	
6	158,507	6	173,548	6	188,525	6	203,502	6		6		6		6		6		6	
1/4	158,821	1/4	173,860	1/4	188,837	1/4	203,814	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	159,135	1/2	174,172	1/2	189,149	1/2	204,126	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	159,449	3/4	174,484	3/4	189,461	3/4	204,438	3/4		3/4		3/4		3/4		3/4		3/4	
7	159,763	7	174,796	7	189,773	7	204,750	7		7		7		7		7		7	
1/4	160,077	1/4	175,108	1/4	190,085	1/4	205,062	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	160,390	1/2	175,420	1/2	190,397	1/2	205,374	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	160,704	3/4	175,732	3/4	190,709	3/4	205,686	3/4		3/4		3/4		3/4		3/4		3/4	
8	161,018	8	176,044	8	191,021	8	205,998	8		8		8		8		8		8	
1/4	161,332	1/4	176,356	1/4	191,333	1/4	206,310	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	161,646	1/2	176,668	1/2	191,645	1/2	206,622	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	161,960	3/4	176,980	3/4	191,957	3/4	206,934	3/4		3/4		3/4		3/4		3/4		3/4	
9	162,273	9	177,292	9	192,269	9	207,246	9		9		9		9		9		9	
1/4	162,587	1/4	177,604	1/4	192,581	1/4	207,558	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	162,901	1/2	177,916	1/2	192,893	1/2	207,870	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	163,215	3/4	178,228	3/4	193,205	3/4	208,182	3/4		3/4		3/4		3/4		3/4		3/4	
10	163,529	10	178,540	10	193,517	10	208,494	10		10		10		10		10		10	
1/4	163,843	1/4	178,852	1/4	193,829	1/4	208,803	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	164,157	1/2	179,164	1/2	194,141	1/2	209,111	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	164,470	3/4	179,476	3/4	194,453	3/4	209,420	3/4		3/4		3/4		3/4		3/4		3/4	
11	164,784	11	179,788	11	194,765	11	209,729	11		11		11		11		11		11	
1/4	165,098	1/4	180,100	1/4	195,077	1/4	210,028	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	165,412	1/2	180,412	1/2	195,389	1/2	210,327	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	165,726	3/4	180,724	3/4	195,701	3/4	210,626	3/4		3/4		3/4		3/4		3/4		3/4	
SEE OTHER CHART FOR THE ABOVE NAMED TANK ONLY																			

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 01/13/2011 CL - SW
CALCULATED: 01/14/2011 CL
PRINTED: 01/14/2011 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 01/2011

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

3 PORT INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/2"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	838	0	15,310	0	30,292	0	44,885	0	59,727	0	74,697	0	89,636	0	104,582	0	119,540	0	134,467
1/4	1,053	1/4	15,622	1/4	30,604	1/4	45,188	1/4	60,039	1/4	75,009	1/4	89,947	1/4	104,894	1/4	119,851	1/4	134,776
1/2	1,268	1/2	15,934	1/2	30,917	1/2	45,491	1/2	60,351	1/2	75,321	1/2	90,258	1/2	105,205	1/2	120,163	1/2	135,085
3/4	1,483	3/4	16,247	3/4	31,229	3/4	45,794	3/4	60,663	3/4	75,633	3/4	90,569	3/4	105,517	3/4	120,475	3/4	135,393
1	1,698	1	16,559	1	31,541	1	46,097	1	60,975	1	75,945	1	90,880	1	105,829	1	120,786	1	135,702
1/4	1,980	1/4	16,871	1/4	31,853	1/4	46,400	1/4	61,287	1/4	76,256	1/4	91,191	1/4	106,140	1/4	121,098	1/4	136,010
1/2	2,263	1/2	17,183	1/2	32,165	1/2	46,703	1/2	61,599	1/2	76,568	1/2	91,501	1/2	106,452	1/2	121,409	1/2	136,319
3/4	2,546	3/4	17,495	3/4	32,477	3/4	47,006	3/4	61,911	3/4	76,880	3/4	91,812	3/4	106,763	3/4	121,721	3/4	136,628
2	2,829	2	17,807	2	32,789	2	47,310	2	62,222	2	77,192	2	92,123	2	107,075	2	122,033	2	136,936
1/4	3,140	1/4	18,119	1/4	33,101	1/4	47,613	1/4	62,534	1/4	77,504	1/4	92,433	1/4	107,387	1/4	122,344	1/4	137,245
1/2	3,452	1/2	18,431	1/2	33,413	1/2	47,917	1/2	62,846	1/2	77,816	1/2	92,744	1/2	107,698	1/2	122,656	1/2	137,554
3/4	3,763	3/4	18,744	3/4	33,725	3/4	48,221	3/4	63,158	3/4	78,127	3/4	93,055	3/4	108,010	3/4	122,967	3/4	137,862
3	4,074	3	19,056	3	34,037	3	48,525	3	63,470	3	78,439	3	93,365	3	108,321	3	123,279	3	138,171
1/4	4,386	1/4	19,368	1/4	34,345	1/4	48,830	1/4	63,782	1/4	78,750	1/4	93,677	1/4	108,633	1/4	123,590	1/4	138,480
1/2	4,698	1/2	19,680	1/2	34,653	1/2	49,136	1/2	64,094	1/2	79,062	1/2	93,988	1/2	108,945	1/2	123,902	1/2	138,788
3/4	5,010	3/4	19,992	3/4	34,961	3/4	49,442	3/4	64,406	3/4	79,373	3/4	94,299	3/4	109,256	3/4	124,213	3/4	139,097
4	5,322	4	20,304	4	35,269	4	49,748	4	64,717	4	79,684	4	94,610	4	109,568	4	124,525	4	139,406
1/4	5,634	1/4	20,616	1/4	35,570	1/4	50,060	1/4	65,029	1/4	79,995	1/4	94,922	1/4	109,880	1/4	124,836	1/4	139,714
1/2	5,946	1/2	20,928	1/2	35,870	1/2	50,371	1/2	65,341	1/2	80,306	1/2	95,233	1/2	110,191	1/2	125,148	1/2	140,023
3/4	6,258	3/4	21,241	3/4	36,170	3/4	50,683	3/4	65,653	3/4	80,617	3/4	95,545	3/4	110,503	3/4	125,459	3/4	140,332
5	6,571	5	21,553	5	36,470	5	50,995	5	65,965	5	80,928	5	95,857	5	110,814	5	125,771	5	140,640
1/4	6,883	1/4	21,865	1/4	36,770	1/4	51,307	1/4	66,277	1/4	81,239	1/4	96,168	1/4	111,126	1/4	126,082	1/4	140,950
1/2	7,195	1/2	22,177	1/2	37,071	1/2	51,619	1/2	66,589	1/2	81,550	1/2	96,480	1/2	111,438	1/2	126,394	1/2	141,260
3/4	7,507	3/4	22,489	3/4	37,371	3/4	51,931	3/4	66,900	3/4	81,861	3/4	96,792	3/4	111,749	3/4	126,705	3/4	141,569
6	7,819	6	22,801	6	37,671	6	52,243	6	67,212	6	82,172	6	97,103	6	112,061	6	127,017	6	141,879
1/4	8,131	1/4	23,113	1/4	37,971	1/4	52,555	1/4	67,524	1/4	82,483	1/4	97,415	1/4	112,373	1/4	127,328	1/4	142,191
1/2	8,443	1/2	23,426	1/2	38,272	1/2	52,866	1/2	67,836	1/2	82,794	1/2	97,726	1/2	112,684	1/2	127,640	1/2	142,504
3/4	8,755	3/4	23,738	3/4	38,572	3/4	53,178	3/4	68,148	3/4	83,105	3/4	98,038	3/4	112,996	3/4	127,951	3/4	142,816
7	9,068	7	24,050	7	38,872	7	53,490	7	68,460	7	83,416	7	98,350	7	113,307	7	128,263	7	143,129
1/4	9,380	1/4	24,362	1/4	39,172	1/4	53,802	1/4	68,772	1/4	83,727	1/4	98,661	1/4	113,619	1/4	128,574	1/4	143,441
1/2	9,692	1/2	24,674	1/2	39,473	1/2	54,114	1/2	69,084	1/2	84,038	1/2	98,973	1/2	113,931	1/2	128,886	1/2	143,754
3/4	10,004	3/4	24,986	3/4	39,773	3/4	54,426	3/4	69,395	3/4	84,349	3/4	99,285	3/4	114,242	3/4	129,197	3/4	144,066
8	10,316	8	25,298	8	40,073	8	54,738	8	69,707	8	84,660	8	99,596	8	114,554	8	129,509	8	144,379
1/4	10,628	1/4	25,610	1/4	40,373	1/4	55,049	1/4	70,019	1/4	84,971	1/4	99,908	1/4	114,866	1/4	129,820	1/4	144,691
1/2	10,940	1/2	25,923	1/2	40,674	1/2	55,361	1/2	70,331	1/2	85,282	1/2	100,219	1/2	115,177	1/2	130,132	1/2	145,004
3/4	11,252	3/4	26,235	3/4	40,974	3/4	55,673	3/4	70,643	3/4	85,593	3/4	100,531	3/4	115,489	3/4	130,443	3/4	145,316
9	11,565	9	26,547	9	41,274	9	55,985	9	70,955	9	85,904	9	100,843	9	115,800	9	130,755	9	145,629
1/4	11,877	1/4	26,859	1/4	41,574	1/4	56,297	1/4	71,267	1/4	86,215	1/4	101,154	1/4	116,112	1/4	131,066	1/4	145,941
1/2	12,189	1/2	27,171	1/2	41,874	1/2	56,609	1/2	71,578	1/2	86,526	1/2	101,466	1/2	116,424	1/2	131,376	1/2	146,254
3/4	12,501	3/4	27,483	3/4	42,175	3/4	56,921	3/4	71,890	3/4	86,837	3/4	101,777	3/4	116,735	3/4	131,687	3/4	146,567
10	12,813	10	27,795	10	42,475	10	57,233	10	72,202	10	87,148	10	102,089	10	117,047	10	131,998	10	146,879
1/4	13,125	1/4	28,107	1/4	42,775	1/4	57,544	1/4	72,514	1/4	87,459	1/4	102,401	1/4	117,358	1/4	132,307	1/4	147,192
1/2	13,437	1/2	28,420	1/2	43,076	1/2	57,856	1/2	72,826	1/2	87,770	1/2	102,712	1/2	117,670	1/2	132,615	1/2	147,504
3/4	13,750	3/4	28,732	3/4	43,377	3/4	58,168	3/4	73,138	3/4	88,081	3/4	103,024	3/4	117,982	3/4	132,924	3/4	147,817
11	14,062	11	29,044	11	43,677	11	58,480	11	73,450	11	88,392	11	103,336	11	118,293	11	133,233	11	148,129
1/4	14,374	1/4	29,356	1/4	43,979	1/4	58,792	1/4	73,762	1/4	88,703	1/4	103,647	1/4	118,605	1/4	133,541	1/4	148,442
1/2	14,686	1/2	29,668	1/2	44,281	1/2	59,104	1/2	74,073	1/2	89,014	1/2	103,959	1/2	118,917	1/2	133,850	1/2	148,754
3/4	14,998	3/4	29,980	3/4	44,583	3/4	59,416	3/4	74,385	3/4	89,325	3/4	104,270	3/4	119,228	3/4	134,159	3/4	149,067

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.

CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.

CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE.

GAUGE POINT: (HERMETIC) LOCATED 12'-09" OFF CENTERLINE AND 42'-06" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT
& ANALYSIS, INC.

P.O. Box 2092
Pearland, Texas 77568
<http://www.pmacorp.net>



BARGE "CCL 403"

3 PORT INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/2"

CAPACITIES GIVEN IN WHOLE GALLONS																			
IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	149,379	0	161,109	0	172,570	0	184,016	0	195,412	0		0		0		0		0	
1/4	149,673	1/4	161,349	1/4	172,809	1/4	184,255	1/4	195,633	1/4		1/4		1/4		1/4		1/4	
1/2	149,968	1/2	161,589	1/2	173,047	1/2	184,493	1/2	195,854	1/2		1/2		1/2		1/2		1/2	
3/4	150,262	3/4	161,828	3/4	173,285	3/4	184,732	3/4	196,076	3/4		3/4		3/4		3/4		3/4	
1	150,556	1	162,068	1	173,524	1	184,970	1	196,297	1		1		1		1		1	
1/4	150,796	1/4	162,308	1/4	173,762	1/4	185,208	1/4	196,487	1/4		1/4		1/4		1/4		1/4	
1/2	151,036	1/2	162,548	1/2	174,001	1/2	185,447	1/2	196,677	1/2		1/2		1/2		1/2		1/2	
3/4	151,276	3/4	162,788	3/4	174,239	3/4	185,685	3/4	196,867	3/4		3/4		3/4		3/4		3/4	
2	151,516	2	163,028	2	174,478	2	185,924	2	197,057	2		2		2		2		2	
1/4	151,756	1/4	163,267	1/4	174,716	1/4	186,162	1/4	197,195	1/4		1/4		1/4		1/4		1/4	
1/2	151,995	1/2	163,507	1/2	174,955	1/2	186,401	1/2	197,333	1/2		1/2		1/2		1/2		1/2	
3/4	152,235	3/4	163,746	3/4	175,193	3/4	186,639	3/4	197,471	3/4		3/4		3/4		3/4		3/4	
3	152,475	3	163,985	3	175,432	3	186,878	3	197,609	3		3		3		3		3	
1/4	152,715	1/4	164,224	1/4	175,670	1/4	187,116	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	152,955	1/2	164,462	1/2	175,909	1/2	187,355	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	153,195	3/4	164,701	3/4	176,147	3/4	187,593	3/4		3/4		3/4		3/4		3/4		3/4	
4	153,434	4	164,939	4	176,385	4	187,832	4		4		4		4		4		4	
1/4	153,674	1/4	165,178	1/4	176,624	1/4	188,070	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	153,914	1/2	165,416	1/2	176,862	1/2	188,308	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	154,154	3/4	165,655	3/4	177,101	3/4	188,547	3/4		3/4		3/4		3/4		3/4		3/4	
5	154,394	5	165,893	5	177,339	5	188,785	5		5		5		5		5		5	
1/4	154,634	1/4	166,132	1/4	177,578	1/4	189,024	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	154,873	1/2	166,370	1/2	177,816	1/2	189,262	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	155,113	3/4	166,609	3/4	178,055	3/4	189,501	3/4		3/4		3/4		3/4		3/4		3/4	
6	155,353	6	166,847	6	178,293	6	189,739	6		6		6		6		6		6	
1/4	155,593	1/4	167,085	1/4	178,532	1/4	189,978	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	155,833	1/2	167,324	1/2	178,770	1/2	190,216	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	156,073	3/4	167,562	3/4	179,008	3/4	190,455	3/4		3/4		3/4		3/4		3/4		3/4	
7	156,312	7	167,801	7	179,247	7	190,693	7		7		7		7		7		7	
1/4	156,552	1/4	168,039	1/4	179,485	1/4	190,932	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	156,792	1/2	168,278	1/2	179,724	1/2	191,170	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	157,032	3/4	168,516	3/4	179,962	3/4	191,408	3/4		3/4		3/4		3/4		3/4		3/4	
8	157,272	8	168,755	8	180,201	8	191,647	8		8		8		8		8		8	
1/4	157,511	1/4	168,993	1/4	180,439	1/4	191,885	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	157,751	1/2	169,232	1/2	180,678	1/2	192,124	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	157,991	3/4	169,470	3/4	180,916	3/4	192,362	3/4		3/4		3/4		3/4		3/4		3/4	
9	158,231	9	169,709	9	181,155	9	192,601	9		9		9		9		9		9	
1/4	158,471	1/4	169,947	1/4	181,393	1/4	192,839	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	158,711	1/2	170,185	1/2	181,632	1/2	193,078	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	158,950	3/4	170,424	3/4	181,870	3/4	193,316	3/4		3/4		3/4		3/4		3/4		3/4	
10	159,190	10	170,662	10	182,108	10	193,554	10		10		10		10		10		10	
1/4	159,430	1/4	170,901	1/4	182,347	1/4	193,790	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	159,670	1/2	171,139	1/2	182,585	1/2	194,026	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	159,910	3/4	171,378	3/4	182,824	3/4	194,262	3/4		3/4		3/4		3/4		3/4		3/4	
11	160,150	11	171,616	11	183,062	11	194,498	11		11		11		11		11		11	
1/4	160,389	1/4	171,855	1/4	183,301	1/4	194,727	1/4		1/4		1/4		1/4		1/4		1/4	
1/2	160,629	1/2	172,093	1/2	183,539	1/2	194,955	1/2		1/2		1/2		1/2		1/2		1/2	
3/4	160,869	3/4	172,332	3/4	183,778	3/4	195,183	3/4		3/4		3/4		3/4		3/4		3/4	

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 01/13/2011 CL - SW
CALCULATED: 01/14/2011 CL
PRINTED: 01/14/2011 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 01/2011

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

3 STBD INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	838	0	15,327	0	30,333	0	45,296	0	60,294	0	75,300	0	90,306	0	105,313	0	120,319	0	135,325
1/4	1,053	1/4	15,640	1/4	30,646	1/4	45,607	1/4	60,607	1/4	75,613	1/4	90,619	1/4	105,625	1/4	120,631	1/4	135,637
1/2	1,268	1/2	15,953	1/2	30,958	1/2	45,919	1/2	60,919	1/2	75,926	1/2	90,932	1/2	105,938	1/2	120,944	1/2	135,950
3/4	1,483	3/4	16,265	3/4	31,271	3/4	46,230	3/4	61,232	3/4	76,238	3/4	91,244	3/4	106,250	3/4	121,257	3/4	136,263
1	1,698	1	16,578	1	31,583	1	46,542	1	61,545	1	76,551	1	91,557	1	106,563	1	121,569	1	136,575
1/4	1,980	1/4	16,890	1/4	31,896	1/4	46,854	1/4	61,857	1/4	76,863	1/4	91,870	1/4	106,876	1/4	121,882	1/4	136,888
1/2	2,263	1/2	17,203	1/2	32,209	1/2	47,165	1/2	62,170	1/2	77,176	1/2	92,182	1/2	107,188	1/2	122,194	1/2	137,201
3/4	2,546	3/4	17,516	3/4	32,521	3/4	47,477	3/4	62,483	3/4	77,489	3/4	92,495	3/4	107,501	3/4	122,507	3/4	137,513
2	2,829	2	17,828	2	32,834	2	47,789	2	62,795	2	77,801	2	92,807	2	107,814	2	122,820	2	137,826
1/4	3,140	1/4	18,141	1/4	33,147	1/4	48,102	1/4	63,108	1/4	78,114	1/4	93,120	1/4	108,126	1/4	123,132	1/4	138,138
1/2	3,452	1/2	18,453	1/2	33,459	1/2	48,414	1/2	63,420	1/2	78,427	1/2	93,433	1/2	108,439	1/2	123,445	1/2	138,451
3/4	3,763	3/4	18,766	3/4	33,772	3/4	48,727	3/4	63,733	3/4	78,739	3/4	93,745	3/4	108,751	3/4	123,758	3/4	138,764
3	4,075	3	19,079	3	34,084	3	49,040	3	64,046	3	79,052	3	94,058	3	109,064	3	124,070	3	139,076
1/4	4,387	1/4	19,391	1/4	34,397	1/4	49,352	1/4	64,358	1/4	79,364	1/4	94,371	1/4	109,377	1/4	124,383	1/4	139,389
1/2	4,699	1/2	19,704	1/2	34,709	1/2	49,665	1/2	64,671	1/2	79,677	1/2	94,683	1/2	109,689	1/2	124,695	1/2	139,702
3/4	5,011	3/4	20,017	3/4	35,021	3/4	49,977	3/4	64,984	3/4	79,990	3/4	94,996	3/4	110,002	3/4	125,008	3/4	140,014
4	5,324	4	20,329	4	35,334	4	50,290	4	65,296	4	80,302	4	95,308	4	110,315	4	125,321	4	140,327
1/4	5,636	1/4	20,642	1/4	35,645	1/4	50,603	1/4	65,609	1/4	80,615	1/4	95,621	1/4	110,627	1/4	125,633	1/4	140,640
1/2	5,949	1/2	20,954	1/2	35,956	1/2	50,915	1/2	65,921	1/2	80,928	1/2	95,934	1/2	110,940	1/2	125,946	1/2	140,952
3/4	6,261	3/4	21,267	3/4	36,267	3/4	51,228	3/4	66,234	3/4	81,240	3/4	96,246	3/4	111,252	3/4	126,259	3/4	141,265
5	6,574	5	21,580	5	36,579	5	51,541	5	66,547	5	81,553	5	96,559	5	111,565	5	126,571	5	141,577
1/4	6,887	1/4	21,892	1/4	36,890	1/4	51,853	1/4	66,859	1/4	81,865	1/4	96,872	1/4	111,878	1/4	126,884	1/4	141,890
1/2	7,199	1/2	22,205	1/2	37,201	1/2	52,166	1/2	67,172	1/2	82,178	1/2	97,184	1/2	112,190	1/2	127,197	1/2	142,203
3/4	7,512	3/4	22,518	3/4	37,513	3/4	52,478	3/4	67,485	3/4	82,491	3/4	97,497	3/4	112,503	3/4	127,509	3/4	142,515
6	7,824	6	22,830	6	37,824	6	52,791	6	67,797	6	82,803	6	97,809	6	112,816	6	127,822	6	142,828
1/4	8,137	1/4	23,143	1/4	38,135	1/4	53,104	1/4	68,110	1/4	83,116	1/4	98,122	1/4	113,128	1/4	128,134	1/4	143,141
1/2	8,450	1/2	23,455	1/2	38,447	1/2	53,416	1/2	68,422	1/2	83,429	1/2	98,435	1/2	113,441	1/2	128,447	1/2	143,453
3/4	8,762	3/4	23,768	3/4	38,758	3/4	53,729	3/4	68,735	3/4	83,741	3/4	98,747	3/4	113,754	3/4	128,760	3/4	143,766
7	9,075	7	24,081	7	39,069	7	54,042	7	69,048	7	84,054	7	99,060	7	114,066	7	129,072	7	144,078
1/4	9,388	1/4	24,393	1/4	39,381	1/4	54,354	1/4	69,360	1/4	84,366	1/4	99,373	1/4	114,379	1/4	129,385	1/4	144,391
1/2	9,700	1/2	24,706	1/2	39,692	1/2	54,667	1/2	69,673	1/2	84,679	1/2	99,685	1/2	114,691	1/2	129,698	1/2	144,704
3/4	10,013	3/4	25,018	3/4	40,003	3/4	54,979	3/4	69,986	3/4	84,992	3/4	99,998	3/4	115,004	3/4	130,010	3/4	145,016
8	10,325	8	25,331	8	40,315	8	55,292	8	70,298	8	85,304	8	100,311	8	115,317	8	130,323	8	145,329
1/4	10,638	1/4	25,644	1/4	40,626	1/4	55,605	1/4	70,611	1/4	85,617	1/4	100,623	1/4	115,629	1/4	130,635	1/4	145,642
1/2	10,951	1/2	25,956	1/2	40,937	1/2	55,917	1/2	70,923	1/2	85,930	1/2	100,936	1/2	115,942	1/2	130,948	1/2	145,954
3/4	11,263	3/4	26,269	3/4	41,248	3/4	56,230	3/4	71,236	3/4	86,242	3/4	101,248	3/4	116,255	3/4	131,261	3/4	146,267
9	11,576	9	26,582	9	41,560	9	56,543	9	71,549	9	86,555	9	101,561	9	116,567	9	131,573	9	146,579
1/4	11,888	1/4	26,894	1/4	41,871	1/4	56,855	1/4	71,861	1/4	86,867	1/4	101,874	1/4	116,880	1/4	131,886	1/4	146,892
1/2	12,201	1/2	27,207	1/2	42,182	1/2	57,168	1/2	72,174	1/2	87,180	1/2	102,186	1/2	117,192	1/2	132,199	1/2	147,205
3/4	12,514	3/4	27,519	3/4	42,494	3/4	57,480	3/4	72,487	3/4	87,493	3/4	102,499	3/4	117,505	3/4	132,511	3/4	147,517
10	12,826	10	27,832	10	42,805	10	57,793	10	72,799	10	87,805	10	102,812	10	117,818	10	132,824	10	147,830
1/4	13,139	1/4	28,145	1/4	43,116	1/4	58,106	1/4	73,112	1/4	88,118	1/4	103,124	1/4	118,130	1/4	133,136	1/4	148,143
1/2	13,452	1/2	28,457	1/2	43,428	1/2	58,418	1/2	73,424	1/2	88,431	1/2	103,437	1/2	118,443	1/2	133,449	1/2	148,455
3/4	13,764	3/4	28,770	3/4	43,739	3/4	58,731	3/4	73,737	3/4	88,743	3/4	103,749	3/4	118,756	3/4	133,762	3/4	148,768
11	14,077	11	29,083	11	44,050	11	59,044	11	74,050	11	89,056	11	104,062	11	119,068	11	134,074	11	149,080
1/4	14,389	1/4	29,395	1/4	44,362	1/4	59,356	1/4	74,362	1/4	89,369	1/4	104,375	1/4	119,381	1/4	134,387	1/4	149,393
1/2	14,702	1/2	29,708	1/2	44,673	1/2	59,669	1/2	74,675	1/2	89,681	1/2	104,687	1/2	119,693	1/2	134,700	1/2	149,706
3/4	15,015	3/4	30,020	3/4	44,984	3/4	59,981	3/4	74,988	3/4	89,994	3/4	105,000	3/4	120,006	3/4	135,012	3/4	150,018

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.

CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.

CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.

CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN WITH "HERMETIC" CLOSED GAUGING DEVICE.

GAUGE POINT: (HERMETIC) LOCATED 12'-09" OFF CENTERLINE AND 42'-06" FORWARD OF AFT BULKHEAD.

PRECISION MEASUREMENT
& ANALYSIS, INC.

P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

3 STBD INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 16'-02 1/4"

CAPACITIES GIVEN IN WHOLE GALLONS																			
IN	10 FT.	IN	11 FT.	IN	12 FT.	IN	13 FT.	IN	14 FT.	IN	15 FT.	IN	16 FT.	IN	17 FT.	IN	18 FT.	IN	19 FT.
0	150,331	0	162,066	0	173,584	0	185,101	0	196,615	0		0		0		0		0	
1/4	150,625	1/4	162,306	1/4	173,824	1/4	185,341	1/4	196,847	1/4		1/4	1/4	1/4		1/4	1/4		
1/2	150,920	1/2	162,546	1/2	174,064	1/2	185,581	1/2	197,079	1/2		1/2	1/2	1/2		1/2	1/2		
3/4	151,214	3/4	162,786	3/4	174,304	3/4	185,821	3/4	197,312	3/4		3/4	3/4	3/4		3/4	3/4		
1	151,509	1	163,026	1	174,544	1	186,061	1	197,544	1		1	1	1		1	1		
1/4	151,749	1/4	163,266	1/4	174,783	1/4	186,301	1/4	197,745	1/4		1/4	1/4	1/4		1/4	1/4		
1/2	151,989	1/2	163,506	1/2	175,023	1/2	186,541	1/2	197,946	1/2		1/2	1/2	1/2		1/2	1/2		
3/4	152,229	3/4	163,746	3/4	175,263	3/4	186,781	3/4	198,146	3/4		3/4	3/4	3/4		3/4	3/4		
2	152,469	2	163,986	2	175,503	2	187,021	2	198,347	2		2	2	2		2	2		
1/4	152,709	1/4	164,226	1/4	175,743	1/4	187,261	1/4	198,496	1/4		1/4	1/4	1/4		1/4	1/4		
1/2	152,948	1/2	164,466	1/2	175,983	1/2	187,501	1/2	198,645	1/2		1/2	1/2	1/2		1/2	1/2		
3/4	153,188	3/4	164,706	3/4	176,223	3/4	187,741	3/4	198,794	3/4		3/4	3/4	3/4		3/4	3/4		
3	153,428	3	164,946	3	176,463	3	187,980	3	198,942	3		3	3	3		3	3		
1/4	153,668	1/4	165,186	1/4	176,703	1/4	188,220	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	153,908	1/2	165,426	1/2	176,943	1/2	188,460	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	154,148	3/4	165,666	3/4	177,183	3/4	188,700	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
4	154,388	4	165,906	4	177,423	4	188,940	4		4		4	4	4		4	4		
1/4	154,628	1/4	166,145	1/4	177,663	1/4	189,180	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	154,868	1/2	166,385	1/2	177,903	1/2	189,420	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	155,108	3/4	166,625	3/4	178,143	3/4	189,660	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
5	155,348	5	166,865	5	178,383	5	189,900	5		5		5	5	5		5	5		
1/4	155,588	1/4	167,105	1/4	178,623	1/4	190,140	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	155,828	1/2	167,345	1/2	178,863	1/2	190,380	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	156,068	3/4	167,585	3/4	179,102	3/4	190,620	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
6	156,308	6	167,825	6	179,342	6	190,860	6		6		6	6	6		6	6		
1/4	156,548	1/4	168,065	1/4	179,582	1/4	191,100	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	156,788	1/2	168,305	1/2	179,822	1/2	191,340	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	157,028	3/4	168,545	3/4	180,062	3/4	191,580	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
7	157,268	7	168,785	7	180,302	7	191,820	7		7		7	7	7		7	7		
1/4	157,507	1/4	169,025	1/4	180,542	1/4	192,060	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	157,747	1/2	169,265	1/2	180,782	1/2	192,299	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	157,987	3/4	169,505	3/4	181,022	3/4	192,539	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
8	158,227	8	169,745	8	181,262	8	192,779	8		8		8	8	8		8	8		
1/4	158,467	1/4	169,985	1/4	181,502	1/4	193,019	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	158,707	1/2	170,225	1/2	181,742	1/2	193,259	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	158,947	3/4	170,464	3/4	181,982	3/4	193,499	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
9	159,187	9	170,704	9	182,222	9	193,739	9		9		9	9	9		9	9		
1/4	159,427	1/4	170,944	1/4	182,462	1/4	193,979	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	159,667	1/2	171,184	1/2	182,702	1/2	194,219	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	159,907	3/4	171,424	3/4	182,942	3/4	194,459	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
10	160,147	10	171,664	10	183,182	10	194,699	10		10		10	10	10		10	10		
1/4	160,387	1/4	171,904	1/4	183,422	1/4	194,939	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	160,627	1/2	172,144	1/2	183,661	1/2	195,178	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	160,867	3/4	172,384	3/4	183,901	3/4	195,418	3/4		3/4		3/4	3/4	3/4		3/4	3/4		
11	161,107	11	172,624	11	184,141	11	195,658	11		11		11	11	11		11	11		
1/4	161,347	1/4	172,864	1/4	184,381	1/4	195,897	1/4		1/4		1/4	1/4	1/4		1/4	1/4		
1/2	161,587	1/2	173,104	1/2	184,621	1/2	196,136	1/2		1/2		1/2	1/2	1/2		1/2	1/2		
3/4	161,826	3/4	173,344	3/4	184,861	3/4	196,376	3/4		3/4		3/4	3/4	3/4		3/4	3/4		

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

STRAPPED: 01/13/2011 CL - SW
CALCULATED: 01/14/2011 CL
PRINTED: 01/14/2011 CL

CANCELS AND SUPERCEDES
ALL PRIOR TO 01/2011

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>



BARGE "CCL 403"

FUEL TANK INNAGE TABLE

CAPACITIES GIVEN IN WHOLE GALLONS

GAUGE HEIGHT 4'-05 1/4"

IN	0 FT.	IN	1 FT.	IN	2 FT.	IN	3 FT.	IN	4 FT.	IN	5 FT.	IN	6 FT.	IN	7 FT.	IN	8 FT.	IN	9 FT.
0	0	0	101	0	259	0	416	0	517	0									
1/4	1	1/4	104	1/4	262	1/4	419	1/4		1/4									
1/2	1	1/2	107	1/2	265	1/2	422	1/2		1/2									
3/4	2	3/4	110	3/4	269	3/4	425	3/4		3/4									
1	3	1	113	1	272	1	428	1		1									
1/4	4	1/4	116	1/4	276	1/4	430	1/4		1/4									
1/2	5	1/2	119	1/2	279	1/2	433	1/2		1/2									
3/4	6	3/4	122	3/4	282	3/4	436	3/4		3/4									
2	7	2	125	2	286	2	439	2		2									
1/4	9	1/4	129	1/4	289	1/4	442	1/4		1/4									
1/2	10	1/2	132	1/2	293	1/2	444	1/2		1/2									
3/4	12	3/4	135	3/4	296	3/4	447	3/4		3/4									
3	13	3	138	3	300	3	450	3		3									
1/4	15	1/4	141	1/4	303	1/4	453	1/4		1/4									
1/2	17	1/2	144	1/2	306	1/2	455	1/2		1/2									
3/4	19	3/4	148	3/4	310	3/4	458	3/4		3/4									
4	21	4	151	4	313	4	460	4		4									
1/4	23	1/4	154	1/4	316	1/4	463	1/4		1/4									
1/2	25	1/2	157	1/2	320	1/2	465	1/2		1/2									
3/4	27	3/4	161	3/4	323	3/4	468	3/4		3/4									
5	29	5	164	5	327	5	470	5		5									
1/4	31	1/4	167	1/4	330	1/4	473	1/4		1/4									
1/2	33	1/2	170	1/2	333	1/2	475	1/2		1/2									
3/4	35	3/4	174	3/4	337	3/4	477	3/4		3/4									
6	37	6	177	6	340	6	480	6		6									
1/4	40	1/4	180	1/4	343	1/4	482	1/4		1/4									
1/2	42	1/2	184	1/2	347	1/2	484	1/2		1/2									
3/4	44	3/4	187	3/4	350	3/4	486	3/4		3/4									
7	47	7	190	7	353	7	488	7		7									
1/4	49	1/4	194	1/4	356	1/4	490	1/4		1/4									
1/2	52	1/2	197	1/2	360	1/2	492	1/2		1/2									
3/4	54	3/4	201	3/4	363	3/4	494	3/4		3/4									
8	57	8	204	8	366	8	496	8		8									
1/4	59	1/4	207	1/4	369	1/4	498	1/4		1/4									
1/2	62	1/2	211	1/2	373	1/2	500	1/2		1/2									
3/4	64	3/4	214	3/4	376	3/4	502	3/4		3/4									
9	67	9	217	9	379	9	504	9		9									
1/4	70	1/4	221	1/4	382	1/4	505	1/4		1/4									
1/2	73	1/2	224	1/2	385	1/2	507	1/2		1/2									
3/4	75	3/4	228	3/4	388	3/4	508	3/4		3/4									
10	78	10	231	10	392	10	510	10		10									
1/4	81	1/4	235	1/4	395	1/4	511	1/4		1/4									
1/2	84	1/2	238	1/2	398	1/2	512	1/2		1/2									
3/4	87	3/4	241	3/4	401	3/4	513	3/4		3/4									
11	89	11	245	11	404	11	514	11		11									
1/4	92	1/4	248	1/4	407	1/4	515	1/4		1/4									
1/2	95	1/2	252	1/2	410	1/2	516	1/2		1/2									
3/4	98	3/4	255	3/4	413	3/4	516	3/4		3/4									

CERTIFIED CHART FOR THE ABOVE NAMED TANK ONLY.

BARGE STRAPPED AND COMPUTED IN ACCORDANCE WITH MPMS CHAPTER 2.7.
CAPACITY TABLE ONLY APPLIES WHEN BARGE IS ON EVEN KEEL.
CAPACITY TABLE EXTENDS TO EXTREME HEIGHT OF TANK.
CAPACITY TABLE ONLY APPLIES TO INNAGE GAUGES TAKEN AT 2" DIAMETER PIPE.

PRECISION MEASUREMENT
& ANALYSIS, INC.
P.O. Box 2092
Pearland, Texas 77588
<http://www.pmacorp.net>

OWNER: CHEM CARRIERS
 DESCRIPTION: DOUBLE SKIN, RAKE TANK BARGE
 SIZE: 297'-6"x54'-0"x12'-0"

CONTRACT: 96180
 HULL: 4772
 NAME: CCL 403
 DATE: 3-Feb-11

VESSEL DISPLACEMENT AND CARGO DEADWEIGHT TABLE (FRESH WATER)

	DRAFT	2 FT	3 FT	4 FT	5 FT	6 FT	7 FT	8 FT	9 FT	10 FT	11 FT
DISPLACEMENT	0 IN		1370	1833	2303	2778	3259	3743	4232	4725	5222
DEADWEIGHT			372	836	1306	1781	2261	2746	3234	3727	4224
DISPLACEMENT	1 IN		1408	1872	2343	2818	3299	3784	4273	4766	5263
DEADWEIGHT			410	875	1345	1821	2301	2786	3275	3768	4266
DISPLACEMENT	2 IN		1446	1911	2382	2858	3339	3824	4314	4807	5305
DEADWEIGHT			449	914	1384	1861	2341	2827	3316	3810	4307
DISPLACEMENT	3 IN	1026	1485	1950	2422	2898	3379	3865	4355	4849	5346
DEADWEIGHT		29	487	953	1424	1900	2382	2867	3357	3851	4349
DISPLACEMENT	4 IN	1064	1523	1989	2461	2938	3420	3906	4396	4890	5388
DEADWEIGHT		67	526	992	1463	1940	2422	2908	3398	3892	4390
DISPLACEMENT	5 IN	1102	1562	2028	2501	2978	3460	3946	4437	4931	5430
DEADWEIGHT		105	564	1031	1503	1980	2462	2949	3439	3934	4432
DISPLACEMENT	6 IN	1140	1601	2068	2540	3018	3500	3987	4478	4973	5471
DEADWEIGHT		143	603	1070	1543	2020	2503	2989	3480	3975	4474
DISPLACEMENT	7 IN	1178	1639	2107	2580	3058	3541	4028	4519	5014	5513
DEADWEIGHT		181	642	1109	1582	2060	2543	3030	3521	4017	4516
DISPLACEMENT	8 IN	1216	1678	2146	2619	3098	3581	4069	4560	5056	5555
DEADWEIGHT		219	680	1148	1622	2100	2584	3071	3562	4058	4557
DISPLACEMENT	9 IN	1255	1717	2185	2659	3138	3622	4109	4601	5097	5597
DEADWEIGHT		257	719	1188	1662	2141	2624	3112	3604	4099	4599
DISPLACEMENT	10 IN	1293	1756	2225	2699	3178	3662	4150	4642	5139	
DEADWEIGHT		295	758	1227	1701	2181	2665	3153	3645	4141	
DISPLACEMENT	11 IN	1331	1794	2264	2739	3218	3703	4191	4684	5180	
DEADWEIGHT		334	797	1266	1741	2221	2705	3193	3686	4182	

DISPLACEMENT & DEADWEIGHT ARE IN SHORT TONS. ONE SHORT TON (S.TON) = 2000 POUNDS

LIGHTSHIP WEIGHT (LWT) IS DERIVED FROM FREEBOARD READINGS

LWT = 998 S.TON

NOTES:

1. TABLE DATA IS BASED ON DRAFTS IN FRESH WATER AT 32.05 (CU. FT. PER S. TON) OR 62.4 (LBS PER CU. FT.).

2. TO OBTAIN DISPLACEMENT IN SEA WATER AT 31.25 (CU. FT. PER S. TON) OR 64.0 (LBS PER CU. FT.), MULTIPLY THE TABLE DISPLACEMENT BY 1.025, TO OBTAIN THE CORRESPONDING CARGO DEADWEIGHT, SUBTRACT THE LIGHTSHIP WEIGHT (LWT) FROM THE CALCULATED DISPLACEMENT IN SEA WATER.

BY 1.025,
IN SEA

3. ACTUAL DISPLACEMENTS AND DEADWEIGHTS MAY VARY DUE TO ACCURACY OF DRAFT READINGS, WEATHER CONDITIONS, SPECIFIC GRAVITY OF WATER, DECK LOADS, RESIDUE IN BILGES ALTERATIONS OR CHANGES TO THE VESSEL SINCE REFERENCE FREEBOARD READINGS WERE TAKEN, etc.

WITY
:

4. ALL DATA IS BASED ON ZERO TRIM.

U.S. Department of
Homeland Security

United States
Coast Guard



Commanding Officer
United States Coast Guard
Marine Safety Center

2100 2nd Street, S.W. Stop 7102
Washington, DC 20593-7102
Staff Symbol: MSC-3
Phone: (202) 475-3403
Fax: (202) 475-3920
Email: msc@uscg.mil

16710/P016203
Serial: C1-1303247
September 23, 2013

M. Dan Jones & Associates
Attn: Mr. M. Dan Jones
7519 Old Bridge Court
Sugar Land, TX 77479
Email: matdjones@aol.com

Subj: CCL 403, O.N. 1231311, Trinity Ashland City Hull 4772
CCL 404, O.N. 1231312, Trinity Ashland City Hull 4773
CCL 405, O.N. 1236867, Trinity Ashland City Hull 2196-1
CCL 406, O.N. 1236866, Trinity Ashland City Hull 2199-1
297' x 54' x 12' Unmanned Double Hull Type II/III Tank Barges (O/D)
Grade A (max. 25 psia Reid) and Lower Flammable or Combustible Liquids Identified in
46 CFR Table 30.25-1 or 46 CFR Part 153 Table 2 and Specified Hazardous Cargoes
Design Density 8.7 lbs/gal; Maximum Density (slack load) 13.6 lbs/gal
Rivers; Lakes, Bays, and Sounds; Limited Coastwise on unmanned fair weather voyages
only, not more than 12 miles offshore between St. Marks and Carrabelle, Florida
Multi-breasted Tandem Loading

Ref: (a) M. Dan Jones & Associates Doc. 13-36-2, "Vapor Collection Calculation on the Dual
Loading of Trinity Marine Products, Inc. Hulls 2196 & 2199" dated September 16,
2013
(b) Marine Safety Center Letter Serial: C1-1100183, dated January 21, 2011
(c) Marine Safety Center Letter Serial: C1-1103805, dated November 14, 2011
(d) Marine Safety Center Letter Serial: C1-1103914, dated November 22, 2011

Dear Mr. Jones:

In response to your electronic submission dated September 16, 2013, we have reviewed the pressure drop calculations for multi-breasted tandem loading. Reference (a) is "**Examined**". Calculations such as these are not normally marked approved, but are used to verify that the system meets the applicable regulations.

These barges have vapor control systems previously approved by references (b) through (d), and are acceptable for dual loading operations. Based on the calculations in reference (a), tandem loading is limited to simultaneous collection of those cargoes listed in the vessels' CAA at a maximum transfer rate of **5000 bbl/hr** per barge.

For final approval you must submit your request to Commandant (CG-ENG-5) with the name of the facility where the vessels will be conducting dual loading operations. For more information, please email the Coast Guard Hazardous Materials Standards division at HazmatStandards@uscg.mil.

16710/P016203
Serial: C1-1303247
September 23, 2013

Subj: CCL 403, O.N. 1231311, Trinity Ashland City Hull 4772
CCL 404, O.N. 1231312, Trinity Ashland City Hull 4773
CCL 405, O.N. 1236867, Trinity Ashland City Hull 2196-1
CCL 406, O.N. 1236866, Trinity Ashland City Hull 2199-1
Multi-breasted Tandem Loading

If you have any questions concerning our review, please contact Lieutenant Ryan Mowbray at the number listed above.

Sincerely,

M. J. SEXTON
Lieutenant, U. S. Coast Guard
Assistant Chief, Tank Vessel and Offshore Division
By direction

Copy: Supervisor, Coast Guard Marine Safety Detachment Nashville
Commandant, U. S. Coast Guard (CG-ENG-5)